

**IBM® Workload Scheduler**  
**Database Views**  
Version 10.2.2

## Note

Before using this information and the product it supports, read the information in [Notices on page cxxv](#).

This edition applies to version 10, release 2, modification level 1 of IBM® Workload Scheduler (program number 5698-T09) and to all subsequent releases and modifications until otherwise indicated in new editions.

# Contents

About this publication.....	v	PLAN_JOBS_V.....	87
What is new in this release.....	v	PLAN_PROMPT_REFS_V.....	94
Accessibility .....	v	PLAN_PROMPTS_V.....	97
Technical training.....	v	PLAN_RESOURCE_REFS_V.....	98
Support information.....	v	PLAN_RESOURCES_V.....	101
<b>Chapter 1. Overview.....</b>	<b>7</b>	PLAN_WORKSTATIONS_V.....	102
Key to using the table views.....	7	PROMPTS_V.....	106
View names.....	8	Output example.....	106
Displaying a view.....	10	PROMPT_REFS_V.....	106
Granting access to users for displaying		PROPERTIES_V.....	109
views.....	11	REMOTE_JOB_REQUESTS_V.....	109
Displaying a view from a DB2® database.....	11	RESOURCES_V.....	111
Displaying a view from an Oracle schema.....	12	Output example.....	112
<b>Chapter 2. IBM Workload Scheduler views.....</b>	<b>15</b>	RESOURCE_REFS_V.....	112
ACTION_PARAMETERS_V.....	15	Output example.....	116
ACTION_RUNS_V.....	15	RUN_CYCLE_REFS_V.....	116
AUDIT_STORE_RECORDS_V.....	16	Output example.....	120
Output example.....	18	VARIABLES_V.....	121
CALENDARS_V.....	20	Output example.....	121
Output example.....	20	VARIABLE_TABLE_REFS_V.....	122
EVENT_CONDITIONS_V.....	21	Output example.....	123
EVENT_RULE_ACTIONS_V.....	21	Notices.....	cxxv
EVENT_RULE_INSTANCES_V.....	23	Index.....	129
EVENT_RULES_V.....	24		
FILE_REFS_V.....	27		
Output example.....	29		
INTERNETWORK_DEPS_V.....	30		
JOB_DEFINITION_REFS_V.....	33		
Output example.....	34		
JOB_DEPS_V.....	35		
Output example.....	40		
JOB_HISTORY_V.....	41		
JOB_STATISTICS_V.....	46		
JOB_STREAM_DEPS_V.....	49		
Output example.....	55		
JOB_STREAM_REFS_V.....	56		
Output example.....	57		
LOG_MESSAGES_V.....	58		
PLAN_DOMAINS_V.....	59		
PLAN_FILE_REFS_V.....	60		
PLAN_FILES_V.....	63		
PLAN_JOB_PREDECESSORS_V.....	63		
PLAN_JOB_STREAM_PREDECESSORS_V.....	68		
PLAN_JOB_STREAM_SUCCESSORS_V.....	73		
PLAN_JOB_SUCCESSORS_V.....	77		
PLAN_JOB_STREAMS_V.....	81		

## About this publication

IBM® Workload Scheduler *Database Views* describes a set of views created by running queries on a specific set of tables in the IBM® Workload Scheduler database and displays the information obtained in tabular form. You can use reporting tools, such as Crystal Reports or Brio, to define reports based on the information obtained.

## What is new in this release

Learn what is new in this release.

For information about the new or changed functions in this release, see *IBM Workload Automation: Overview*, section *Summary of enhancements*.

For information about the APARs that this release addresses, see the IBM Workload Scheduler Release Notes and the Dynamic Workload Console Release Notes. For information about the APARs addressed in a fix pack, refer to the readme file for the fix pack.

New or changed content is marked with revision bars.

## Accessibility

Accessibility features help users with a physical disability, such as restricted mobility or limited vision, to use software products successfully.

With this product, you can use assistive technologies to hear and navigate the interface. You can also use the keyboard instead of the mouse to operate all features of the graphical user interface.

For full information, see the Accessibility Appendix in the *IBM Workload Scheduler User's Guide and Reference*.

## Technical training

Cloud & Smarter Infrastructure provides technical training.

For Cloud & Smarter Infrastructure technical training information, see: <http://www.ibm.com/software/tivoli/education>

## Support information

IBM provides several ways for you to obtain support when you encounter a problem.

If you have a problem with your IBM software, you want to resolve it quickly. IBM provides the following ways for you to obtain the support you need:

- Searching knowledge bases: You can search across a large collection of known problems and workarounds, Technotes, and other information.
- Obtaining fixes: You can locate the latest fixes that are already available for your product.
- Contacting IBM Software Support: If you still cannot solve your problem, and you need to work with someone from IBM, you can use a variety of ways to contact IBM Software Support.

For more information about these three ways of resolving problems, see the appendix about support information in *IBM Workload Scheduler: Troubleshooting Guide*.

# Chapter 1. Overview

IBM Workload Scheduler Database Views describes a set of predefined views provided with IBM Workload Scheduler in tabular form. A view is a logical table containing the data generated by a query. A view is based on an underlying set of base tables, and the data shown in a view is determined by a SELECT statement that is run on these base tables. See [Displaying a view on page 10](#) for a detailed explanation about how to display a view. Views are described in alphabetic order. Each table shows the names of the columns in the view, a description of each column, and its data type.

This chapter is divided into the following sections:

- [Key to using the table views on page 7](#)
- [View names on page 8](#)
- [Displaying a view on page 10](#)

## Key to using the table views

Each view is described in a table containing the following columns:

### **column**

The name of the column in the view.

### **description**

The description of the column in the view.

### **type**

The data type of the column in the view. Possible values are:

#### **Character**

A single character, typically a flag.

#### **String**

A sequence of characters.

#### **Integer**

A numeric value, indicating a quantity.

#### **Timestamp**

A value designating a date and time. The format depends on the language set for the workstation and on the database you are using.

#### **Date**

A three-part value consisting of a day, month, and year. The format depends on the language set for the workstation and on the database you are using. For example, if the language set for the workstation is Italian and the database you are using is DB2®, the date format is dd/mm/yyyy.

## View names

The name of the view has the following structure:

```
database_schema_name.object_name_v
```

where:

### database\_schema\_name

Depends on the database you are using. It can assume one of the following values:

#### If you are using a DB2® database:

##### EVT

Identifies views containing information about event management object definitions.

##### LOG

Identifies views containing information about event management objects already run.

##### MDL

Identifies views containing information about the IBM Workload Scheduler object except event management objects.

##### PLN

Identifies views containing information about IBM Workload Scheduler objects in the plan

#### If you are using an Oracle database:

The name of the IBM Workload Scheduler Oracle user you defined during the installation.

### object\_name

Represents the name of the object for which you are displaying the information.

For example, if you want to display view information about job history from a DB2® database, the name of the view is:

```
MDL.JOB_HISTORY_V
```

If you want to display view information about job history from an Oracle database and the name of the IBM Workload Scheduler Oracle user you defined during the installation is **tws**, the name of the view is:

```
tws.JOB_HISTORY_V
```

[Table 1: Views available with IBM Workload Scheduler on page 8](#) lists the views you can use with IBM Workload Scheduler.

**Table 1. Views available with IBM Workload Scheduler**

View name	Information obtained
<a href="#">ACTION_PARAMETERS_V on page 15</a>	Displays information about the parameters associated with the actions run.

**Table 1. Views available with IBM Workload Scheduler (continued)**

View name	Information obtained
<a href="#">ACTION_RUNS_V on page 15</a>	Displays the actions run for each event rule.
<a href="#">CALENDARS_V on page 20</a>	Displays information about calendars.
<a href="#">EVENT_CONDITIONS_V on page 21</a>	Displays information about the events associated with each rule.
<a href="#">EVENT_RULE_INSTANCES_V on page 23</a>	Displays information about run event rule history.
<a href="#">EVENT_RULES_V on page 24</a>	Displays information about the event rules.
<a href="#">EVENT_RULE_ACTIONS_V on page 21</a>	Displays information about the actions associated with each event rule.
<a href="#">FILE_REFS_V on page 27</a>	Displays information about jobs and job streams that depend on a file.
<a href="#">INTERNETWORK_DEPS_V on page 30</a>	Displays information about jobs and job streams that depend on an internetwork dependency.
<a href="#">JOB_DEFINITION_REFS_V on page 33</a>	Displays information about the job streams in which a job appears.
<a href="#">JOB_DEPS_V on page 35</a>	Displays information about jobs and job streams that depend on a job.
<a href="#">JOB_HISTORY_V on page 41</a>	Displays information about job history.
<a href="#">JOB_STATISTICS_V on page 46</a>	Displays information about jobs.
<a href="#">JOB_STREAM_DEPS_V on page 49</a>	Displays information about jobs and job streams that depend on a job stream.
<a href="#">JOB_STREAM_REFS_V on page 56</a>	Displays information about job streams.
<a href="#">LOG_MESSAGES_V on page 58</a>	Displays information about the messages logged by log actions.
<a href="#">PLAN_DOMAINS_V on page 59</a>	Displays information about domains in the plan.
<a href="#">PLAN_FILE_REFS_V on page 60</a>	Displays information about jobs and job streams in the plan that depend on a file.
<a href="#">PLAN_FILES_V on page 63</a>	Displays information about files in the plan.
<a href="#">PLAN_JOB_PREDECESSORS_V on page 63</a>	Displays information about jobs and job streams predecessors of a job in the plan.
<a href="#">PLAN_JOB_STREAM_PR EDECESSORS_V on page 68</a>	Displays information about jobs and job streams predecessors of a job stream in the plan.
<a href="#">PLAN_JOB_STREAM_SUCCESSORS_V on page 73</a>	Displays information about jobs and job streams successors of a job stream in the plan.

**Table 1. Views available with IBM Workload Scheduler (continued)**

View name	Information obtained
<a href="#">PLAN_JOB_SUCCESSORS_V on page 77</a>	Displays information about jobs and job streams successors of a job in the plan.
<a href="#">PLAN_JOB_STREAMS_V on page 81</a>	Displays information about job streams in the plan.
<a href="#">PLAN_JOBS_V on page 87</a>	Displays information about jobs in the plan.
<a href="#">PLAN_PROMPT_REFS_V on page 94</a>	Displays information about jobs and job streams in plan that depend on a prompt.
<a href="#">PLAN_PROMPTS_V on page 97</a>	Displays information about prompts in the plan.
<a href="#">PLAN_RESOURCE_REFS_V on page 98</a>	Displays information about jobs and job streams in plan that depend on a resource.
<a href="#">PLAN_RESOURCES_V on page 101</a>	Displays information about resources in the plan.
<a href="#">PLAN_WORKSTATIONS_V on page 102</a>	Displays information about workstations in the plan.
<a href="#">PROMPTS_V on page 106</a>	Displays information about prompts, such as their name and definition.
<a href="#">PROMPT_REFS_V on page 106</a>	Displays information about jobs and job streams that depend on a prompt.
<a href="#">PROPERTIES_V on page 109</a>	Displays information about global options and properties.
<a href="#">REMOTE_JOB_REQUESTS_V on page 109</a>	Displays the details of the request to bind to a job on a remote engine.
<a href="#">RESOURCES_V on page 111</a>	Displays information about resources.
<a href="#">RESOURCE_REFS_V on page 112</a>	Displays information about jobs and job streams that depend on a resource.
<a href="#">RUN_CYCLE_REFS_V on page 116</a>	Displays information about when job streams run.
<a href="#">VARIABLES_V on page 121</a>	Displays information about global parameters, from now on called variables.
<a href="#">VARIABLE_TABLE_REFS_V on page 122</a>	Displays information about job streams, run cycles, and workstations that use variable tables.

## Displaying a view

This section contains information about:

- [Granting access to users for displaying views on page 11](#)
- [Displaying a view from a DB2 database on page 11](#)
- [Displaying a view from an Oracle schema on page 12](#)

## Granting access to users for displaying views

For the procedure that describes how to grant access to users for displaying views, see the *IBM Workload Scheduler: Administration Guide*, section, "Configuring Dynamic Workload Console to view reports". This procedure applies also to views.

## Displaying a view from a DB2® database

### About this task

This section describes how to display a view from a DB2® database using the Command Editor. You can also use the DB2® command line to display a view. Based on the operating system, use one of the following procedures:

- [Displaying a view on a Windows workstation with a DB2 database on page 11](#)
- [Displaying a view on a UNIX workstation with a DB2 database on page 12](#)

## Displaying a view on a Windows™ workstation with a DB2® database

To display a view on a Windows™ workstation with a DB2® database installed, perform the following steps:

1. Select **Start** → **Programs** → **IBM® DB2®** → **Command Line Tools** → **Command Editor**. The Command Editor main window opens.
2. In the **Command** page, enter the following command:
 

```
connect to databasename_db user username
```

where *databasename\_db* is the name of the database you want to connect to. The default is **tw**.

*user name* is the name of the user with which you installed the DB2® database. The default is **db2admin**.
3. Click the green arrow in the upper-left corner of the Command Editor window. The Enter Credentials dialog displays.
4. In the **password** field, type the user password and click **OK**. The Command Editor window shows the database connection information. The Query Results tab displays.
5. From the Command Editor main window, enter the following command:

```
select * from view_name
```

where *view\_name* is the name of the view from which you want to display the information.

For example, to extract information from the MDL.JOB\_HISTORY\_V view, enter the following command:

```
select * from MDL.JOB_HISTORY_V
```

6. Click the green arrow in the upper-left corner of the Command Editor window. The Query Results dialog displays the results of the query.

## Displaying a view on a UNIX™ workstation with a DB2® database

To display a view on a UNIX™ workstation with a DB2® database installed, perform the following steps:

1. From a shell script, enter the following command:

```
su - DB2user
```

where *DB2user* is the name of the user with which you installed the DB2® database. The default name is **db2inst1**. For example, if you installed the DB2® database using the **db2inst1** user name, enter the following command:

```
su - db2inst1
```

2. Ensure that the DB2® environment is initialized using the following command:

```
db2
```

3. Type

```
quit
```

to return to the shell environment.

4. Start the Command Editor using the following command:

```
db2
```

5. Proceed as described from Step 2 of [Displaying a view on a Windows workstation with a DB2 database on page 11](#).

## Displaying a view from an Oracle schema

### About this task

This section describes how to display a view from an Oracle schema using the Oracle Enterprise Manager. You can also use the Oracle command line to display a view. Based on the operating system and on the Oracle release you are working with, use one of the following procedures:

- [Displaying a view on a Windows workstation with an Oracle 11g schema on page 12](#)
- [Displaying a view on a UNIX workstation with an Oracle 11g schema on page 13](#)

## Displaying a view on a Windows™ workstation with an Oracle 11g schema

To display a view on a Windows™ workstation with an Oracle 11g schema installed, perform the following steps:

1. Verify that the Oracle Enterprise Manager Console is accessible from a client browser. This implies that the *dbconsole* process is running on the server. This process starts automatically after the installation. To verify that the *dbconsole* process is running, and start it if it is not running, perform the following steps:
  - a. Select **Start** → **Settings** → **Control Panel** → **Administrative Tools** → **Services**. The Services (Local) window opens.
  - b. Locate the OracleDBConsole*ORACLE\_SID* service, where *ORACLE\_SID* is the name of the Oracle database created on the workstation. The **Status** column shows the status of the service.

**If the Status column is Started:**

The *dbconsole* process is running on the server.

**If the Status column is blank, the process is stopped. To start it, perform the following steps:**

- i. Double-click the **OracleDBConsoleORACLE\_SID** service row. The OracleDBConsoleORACLE\_SID Properties (Local Computer) dialog displays.
  - ii. In the General page, ensure that the **Startup type** is either **Automatic** or **Manual**.
  - iii. In the Service status group, click **Start**.
2. Select **Start** → **Programs** → **Oracle-*installation\_name*** → **DatabaseControl- *database\_name***. The Oracle Enterprise Manager 11g Login to Database *database\_name* web page displays.
  3. Type the following information and click **Login**:

**Username**

It can be:

**Oracle administrator user**

The database administrator user name, for example *SYSTEM*, required to authenticate to the Oracle database.

**IBM Workload Scheduler user**

The owner of the IBM Workload Scheduler schema.

**Password**

The password associated with the user specified in the **Username** field.

The Database Instance: *database\_name* home page displays.

4. In Related Links, select **SQL Worksheet**. The SQL Worksheet: *database\_instance\_name* web page displays.
5. In the **Enter SQL commands** input area, enter the following command:

```
select * from view_name
```

where *view\_name* is the name of the view from which you want to display the information. The view name has the following format:

```
username.JOB_HISTORY_V
```

where *username* is the name of the owner of the IBM Workload Scheduler schema. For example, if the user name is **TWSuser**, to extract information from the *username.JOB\_HISTORY\_V* view, enter the following command:

```
select * from TWSuser.JOB_HISTORY_V
```

6. Click **Execute**. The output area displays the results of the query.

## Displaying a view on a UNIX™ workstation with an Oracle 11g schema

To display a view on a UNIX™ workstation with an Oracle 11g schema installed, perform the following steps:

1. Switch to the Oracle user who owns the Oracle installation, by running the following command:

```
su - oracle_user
```

For example, if the *oracle\_user* is *oracle*, enter the following command:

```
su - oracle
```

2. Verify that the Oracle Enterprise Manager Console is accessible from a client browser. This implies that the *dbconsole* process is running on the server. This process starts automatically after the installation. To verify that it is running, run the following command from the *\$ORACLE\_HOME/bin* directory:

```
./emctl status dbconsole
```

If the *dbconsole* process is stopped, start it by running the following command from the *\$ORACLE\_HOME/bin* directory:

```
./emctl start dbconsole
```

3. Connect to the following website:

```
https://hostname:port/em
```

where:

**hostname**

Specify the name of the host you are working with.

**port**

Specify the port to use for communicating. The default port number is:

**5500**

For Oracle Standard Edition.

**1158**

For Oracle Enterprise Edition.

To verify the port used for communicating, open the *oracle\_home/install/portlist.ini* file and look for the port number specified in the **Enterprise Manager Console HTTP port(instance\_name)=port\_number** line.

4. Launch the Oracle Enterprise Manager and proceed as described from Step 3 of the [Displaying a view on a Windows workstation with an Oracle 11g schema on page 12](#).

# Chapter 2. IBM Workload Scheduler views

This chapter describes the views you can use to extract information from the IBM Workload Scheduler database. You can then use reporting tools, such as Crystal Reports or Brio, to define reports based on this information. It also contains examples of the most significant views.

In the following sections the views are listed in alphabetic order.

## ACTION\_PARAMETERS\_V

The ACTION\_PARAMETERS\_V view displays information about the parameters associated with the actions run.

**Table 2. The ACTION\_PARAMETERS\_V view**

Column name	Description	Type	Length
Log_time	The time when the action run was logged.	timestamp	26 In DB2® 35 In Oracle
Event_rule_name	The name of the event rule associated with the action.	string	40
Action_provider	The name of the plug-in associated with the action.	string	40
Action_scope	The scope of the action. That is the most meaningful information related to the action. The plug-in defines the information to be inserted.	string	120
Action_type	The type of action.	string	40
Parameter_name	The name of the parameter associated with the action.	string	50
Parameter_value	The value of the parameter.	string	256

## ACTION\_RUNS\_V

The ACTION\_RUNS\_V view displays the actions run for each event rule.

**Table 3. The ACTION\_RUNS\_V view**

Column name	Description	Type	Length
Log_time	The time when the action run was logged.	timestamp	26 In DB2®

**Table 3. The ACTION\_RUNS\_V view (continued)**

Column name	Description	Type	Length
			<b>35</b>
			In Oracle
Event_rule_name	The name of the event rule associated with the action.	string	40
Event_rule_type	The type of event rule. Possible values are:  <b>F</b> Filter  <b>Q</b> Sequence  <b>S</b> Set	character	1
Action_provider	The name of the plug-in associated with the action.	string	40
Action_scope	The scope of the action. That is the most meaningful information related to the action. The plug-in defines the information to be inserted.	string	120
Action_type	The type of action.	string	40
Action_status	The status of the actions run. Possible values are:  <b>S</b> Successful  <b>W</b> Warning  <b>E</b> Error	character	1
Action_result	The result of the action. It depends on the plug-in associated with the action.	string	128
Message	The text of the message that is logged by the action plug-in when the action is run. It provides information about how the action completed.	string	512

## AUDIT\_STORE\_RECORDS\_V

The AUDIT\_STORE\_RECORDS\_V view displays information about the auditing records stored in the database.

**Table 4. The AUDIT\_STORE\_RECORDS\_V view**

Column name	Description	Type	Length
Log_time	The date and time the log was created.	Timestamp	10
Log_type	An eight character value indicating the source of the log record. This value is for internal use only.	Character	1
Object_type	The type of the object that was affected by an action.	Varchar	128
Action_type	The type of action was performed on the object.	Varchar	128
User_name	The logon user who performed the particular action.	Varchar	128
Object_key	The fully qualified name of the object.	Varchar	128
Object_name	The name of the object.	Varchar	128
Workstation_name	The name of the workstation of the object	Varchar	128
Justification_category	The justification category of the object	Varchar	128
Justification_ticket_num	The ticket number of the object specified in the justification information.	Varchar	128
Justification_description	The description of the object specified in the justification information.	Varchar	512
Object_definition_differences	The differences between two versions of the same object definition	Varchar	4095
Related_workstation_name	The workstation name of the object which is related to the audited object	Varchar	128

**Table 4. The AUDIT\_STORE\_RECORDS\_V view (continued)**

Column name	Description	Type	Length
Related_object_name	The name of the object which is related to the audited object	Varchar	128
Object_definition	The definition of the scheduling object.	Clob	1048576
Object_identifier	The identifier of the audited object.	Character	16
Log_id	The identifier of the log record.	Decimal	20

### Output example

Table 5: AUDIT\_STORE\_RECORDS\_V view output example on page 18 shows an example of the output for the AUDIT\_STORE\_RECORDS\_V view.

**Table 5. AUDIT\_STORE\_RECORDS\_V view output example**

LOG_TIME ----- 2011-02-10 09:12:28.0
LOG_TYPE ----- D
OBJECT_TYPE ----- DBJOB
OBJECT_IDENTIFIER ----- 7DB8E17BF4013E8D8018E5F48E939858
ACTION_TYPE ----- MODIFY
LOG_ID ----- 70

**Table 5. AUDIT\_STORE\_RECORDS\_V view output example (continued)**

```
LOG_TIME
-----
2019-11-22 12:57:55
```

```
LOG_TYPE
-----
D
```

```
OBJECT_TYPE
-----
DBJOB
```

```
ACTION_TYPE
-----
ADD
```

```
USER_NAME
-----
wa952ora
```

```
OBJECT_KEY
-----
/FOLDER1/FOLDER2/WA952FTA#/FOLDER1/NETSTAT_JOB
```

```
WORKSTATION_NAME
-----
/FOLDER1/FOLDER2/WA952FTA
```

```
JUSTIFICATION_CATEGORY
-----
(null)
```

```
JUSTIFICATION_TICKET_NUM
-----
(null)
```

```
JUSTIFICATION_DESCRIPTION
-----
(null)
```

```
OBJECT_DEFINITION_DIFFERENCES
-----
(null)
```

```
RELATED_WORKSTATION_NAME
-----
(null)
```

**Table 5. AUDIT\_STORE\_RECORDS\_V view output example (continued)**

```

RELATED_OBJECT_NAME
-----
(null)

OBJECT_NAME
-----
NETSTAT_JOB

OBJECT_DEFINITION
-----
/FOLDER1/FOLDER2/WA952FTA#/FOLDER1/NETSTAT_JOB
DOCMMAND "netstat -a"
STREAMLOGON wa952fta
TASKTYPE UNIX
RECOVERY STOP
    
```

## CALENDARS\_V

The CALENDARS\_V view displays information about calendars.

**Table 6. The CALENDARS\_V view**

Column name	Description	Type	Length
Calendar_identifier	The identifier of the calendar.	character	16
Calendar_name	The name of the calendar.	string	16
Calendar_description	The description of the calendar.	string	120
Calendar_dates	A list of scheduling dates that define the calendar. The format is: yyyymmdd[,yyyymmdd ,...,yyyymmdd]	string	not defined
Calendar_folder_id	The identifier of the folder where the calendar is stored.	character	16
Calendar_folder_name	The name of the folder where the calendar is stored.	string	801

## Output example

[Table 7: CALENDARS\\_V output example on page 20](#) shows an example of the output for the CALENDARS\_V view.

**Table 7. CALENDARS\_V output example**

```

CALENDAR_NAME    CALENDAR_DESCRIPTION    CALENDAR_DATES
-----
PMHOLIDAYS      Post meridiem holidays  20061101,20061208,20061225,20061226,20060101,20060106,20060428
AMHOLIDAYS      Ante meridiem holidays  20060129,20060226,20060327,20060428,20060528,20060626,20030729
HOLIDAYS        Holidays                20060101,20060106,20060417,20060425,20060501,20060602,20060815
    
```

**Table 7. CALENDARS\_V output example (continued)**

```
ANN-1-GL      Rome Patron saint      20060629
4 record(s) selected.
```

## EVENT\_CONDITIONS\_V

The EVENT\_CONDITIONS\_V view displays information about the events associated with each event rule.

**Table 8. The EVENT\_CONDITIONS\_V view**

Column name	Description	Type	Length
Event_rule_name	The name of the event rule.	string	40
Event_name	The name of the event associated with the event rule.	string	50
Event_provider	The name of the plug-in associated with the event.	string	40
Event_type	The type of event.	string	40
Event_scope	The scope of the event. That is the most meaningful information related to the event. The plug-in defines the information to be inserted.	string	120
Filtering_predicate	The content in XML format of the <b>filteringPredicate</b> keyword in the event rule definition file.	string	not defined
Event_rule_folder_id	The identifier of the folder where the event rule is stored.	character	16
Event_rule_folder_name	The name of the folder where the event rule is stored.	string	801

## EVENT\_RULE\_ACTIONS\_V

The EVENT\_RULE\_ACTIONS\_V view displays information about actions associated with each event rule.

**Table 9. The EVENT\_RULE\_ACTIONS\_V view**

Column name	Description	Type	Length
Event_rule_identifier	The identifier of the event rule.	character	40
Event_rule_folder_id	The identifier of the folder where the event rule is stored.	character	16
Event_rule_folder_name	The name of the folder where the event rule is stored.	string	801
Event_rule_name	The name of the event rule.	string	40
Action_identifier	The identifier of the action associated with the event rule.	character	120
Action_description	The description of the action associated with the event rule.	string	120

Table 9. The EVENT\_RULE\_ACTIONS\_V view (continued)

Column name	Description	Type	Length
Action_provider	The name of the plug-in associated with the action.	string	40
Action_type	The type of action associated with the event rule.	string	40
Response_type	When the action must be run. Possible values are:  <b>D</b>  onDetection. The action starts when the event rule is run. The event rule is run according to its rule type. This might be on detection of a single event or when all the events of a set or sequence are captured.  <b>T</b>  onTimeOut. The action starts when the first event of a set or sequence is captured, but the set or sequence of events does not complete in the time interval defined in the <b>timeInterval</b> keyword.	character	1
Action_scope	The scope of the action. That is the most meaningful information related to the action. The plug-in defines the information to be inserted.	string	120
Parameter_list	A comma separated list of parameters associated with the action and their value. The list is in the format <i>parameter name=value</i> .	string	not defined
Job_wks_identifier	The identifier of the workstation where the job specified in the <b>Job_identifier</b> column is defined.	character	16
Job_wks_name	The name of the workstation where the job specified in the <b>Job_name</b> column is defined.	string	16
Job_identifier	The identifier of the job submitted by the action.	character	16
Job_name	The name of the job submitted by the action.	string	40
Job_stream_wks_identifier	The identifier of the workstation where the job stream is defined.	character	16
Job_stream_wks_name	The name of the workstation where the job stream is defined.	string	16
Job_stream_folder_id	The identifier of the folder that contains the job stream submitted by the action.	character	16

**Table 9. The EVENT\_RULE\_ACTIONS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_folder_name	The name of the folder that contains the job stream submitted by the action.	string	4000 Oracle 4095 DB2
Job_stream_identifier	The identifier of the job stream submitted by the action.	character	16
Job_stream_name	The name of the job stream submitted by the action.	string	16
Variable_table_identifier	The identifier of the variable table of the job stream submitted by the action.	character	16
Variable_table	The name of the variable table of the job stream submitted by the action.	string	80
Variable_table_folder_id	The identifier of the folder where the variable table is stored.	character	16
Variable_table_folder_name	The name of the folder where the variable table is stored.	string	801

## EVENT\_RULE\_INSTANCES\_V

The EVENT\_RULE\_INSTANCES\_V view displays information about run event rule history.

**Table 10. The EVENT\_RULE\_INSTANCES\_V view**

Column name	Description	Type	Length
Log_time	The time when the event rule instance was logged.	timestamp	26 In D B2® 35 In Or a cle
Event_rule_name	The name of the event rule.	string	40
Event_rule_type	The type of event rule. Possible values are:  F  Filter	character	1

**Table 10. The EVENT\_RULE\_INSTANCES\_V view (continued)**

Column name	Description	Type	Length
	<p><b>Q</b> Sequence</p> <p><b>S</b> Set</p>		
Event_rule_instance_status	The status of the event rule. Possible values are:	character	1
	<p><b>S</b> Successful</p> <p><b>R</b> Running</p> <p><b>E</b> Error</p> <p><b>W</b> Warning</p>		
Is_timeout_expired	If the timeout associated with event rule is expired. Possible values are:	character	1
	<p><b>Y</b> Yes</p> <p><b>N</b> No</p>		

## EVENT\_RULES\_V

The EVENT\_RULES\_V view displays information about event rules.

**Table 11. The EVENT\_RULES\_V view**

Column name	Description	Type	Length
Event_rule_name	The name of the event rule.	string	40
Event_rule_description	The description of the event rule.	string	120
Event_rule_type	The type of rule. Possible values are:	character	1
	<p><b>F</b> Filter</p>		

Table 11. The EVENT\_RULES\_V view (continued)

Column name	Description	Type	Length
	<p><b>Q</b> Sequence</p> <p><b>S</b> Set</p>		
Is_draft	<p>If the event rule definition is currently enabled. Possible values are:</p> <p><b>Y</b> Yes</p> <p><b>N</b> No</p>	character	1
Event_rule_status	<p>The status of the event rule. Possible values are:</p> <p><b>active</b> The event rule was activated successfully.</p> <p><b>update pending</b> The event rule whose status is active was updated and must be deployed again.</p> <p><b>error during update</b> An error occurred deploying the active event rule that has been updated.</p> <p><b>activation pending</b> The event rule is waiting to be activated.</p> <p><b>error during activation</b> An error occurred activating the event rule.</p> <p><b>deactivation pending</b> The event rule was set to <b>isDraft</b> and must be deployed again to reflect the new status.</p> <p><b>error during deactivation</b> An error occurred deactivating the event rule.</p> <p><b>not active</b> The event rule is not active.</p>	character	1

**Table 11. The EVENT\_RULES\_V view (continued)**

Column name	Description	Type	Length
Valid_from	The starting date from which the event rule is ready to be activated and therefore deployed.	date	10 In D B2® 9 In Or a cle
Valid_to	The last date that the event rule is active and therefore deployed.	date	10 In D B2® 9 In Or a cle
Start_offset	The start time when the event rule becomes active and ready to be deployed. This time is expressed in milliseconds calculated as an offset starting from 00.00 a.m. For example, if the start time is 11:30 a.m. the value is $((11 * 60) + 30) * 60 * 1000 = 41400000$ .	integer	12
End_offset	The end time when the event rule is no longer active. This time is expressed in milliseconds calculated as an offset starting from 00.00 a. m. For example, if the end time is 11:30 a. m. the value is $((11 * 60) + 30) * 60 * 1000 = 41400000$ .	integer	12
Time_zone	The time zone defined for the event rule that the product uses to deploy the rule.	string	40
Time_interval	The length of time after which the timeout action is to start.	integer	12
Group_attribute_list	A comma-separated list of attributes on which are correlated the events defined for the rule.	string	not defined

## FILE\_REFS\_V

The FILE\_REFS\_V view displays information about jobs and job streams that depend on a file.

**Table 12. The FILE\_REFS\_V view**

Column name	Description	Type	Length
Workstation_identifier	The identifier of the workstation where the file is defined.	character	16
Workstation_name	The name of the workstation where the file is defined.	string	16
File_identifier	The identifier of the file on which jobs and job streams depend.	character	16
File_name	The name of the file on which jobs and job streams depend.	string	148
File_fol_id	The identifier of the folder where the file is stored.	character	16
File_fol_name	The name of the folder where the file is stored.	string	801
Dep_job_stream_wks_identifier	The identifier of the workstation where the job stream that depends on the file specified in the <b>File_name</b> column is defined.	character	16
Dep_job_stream_wks_name	The name of the workstation where the job stream that depends on the file specified in the <b>File_name</b> column is defined.	string	16
Dep_job_stream_folder_id	The identifier of the folder containing the job stream that depends on the file specified in the <b>File_identifier</b> column.	character	16
Dep_job_stream_folder_name	The name of the folder containing the job stream that depends on the file specified in the <b>File_identifier</b> column.	string	801
Dep_job_stream_identifier	The identifier of the job stream that depends on the file specified in the <b>File_identifier</b> column.	character	16
Dep_job_stream_name	The name of the job stream that depends on the file specified in the <b>File_name</b> column.	string	16
Dep_job_stream_valid_from	The starting date from which the dependent job stream is included in a production plan if selected by a run cycle.	date	<b>10</b> In D B2®

Table 12. The FILE\_REFS\_V view (continued)

Column name	Description	Type	Length
			9
			In Ora cle
Dep_job_stream_valid_to	The last date that the dependent job stream is included in a production plan if selected by a run cycle.	date	10
			In D B2®
			9
			In Ora cle
Dep_job_wks_identifier	The identifier of the workstation where the job that depends on the file specified in the <b>File_identifier</b> column is defined. If this field is not displayed, the job does not depend on any file.	character	16
Dep_job_wks_name	The name of the workstation where the job that depends on the file specified in the <b>File_name</b> column is defined. If this field is not displayed, the job does not depend on any file.	string	16
Dep_job_folder_id	The identifier of the folder containing the job that depends on the file specified in the <b>File_identifier</b> column.	character	16
Dep_job_folder_name	The name of the folder containing the job that depends on the file specified in the <b>File_identifier</b> column.	string	801
Dep_job_identifier	The identifier of the job that depends on the file specified in the <b>File_identifier</b> column. If this field is not displayed, the job does not depend on any file.	character	16
Dep_job_name	The name of the job that depends on the file specified in the <b>File_name</b> column. If this field is not displayed, the job does not depend on any file.	string	40
Dep_job_definition_identifier	The identifier of the job definition of the job that depends on the file specified in the <b>File_identifier</b>	character	16

**Table 12. The FILE\_REFS\_V view (continued)**

Column name	Description	Type	Length
	column. If this field is not displayed the job does not depend on a file.		
Dep_job_definition_name	The name of the job definition of the job that depends on the file specified in the <b>File_name</b> column. If this field is not displayed, the job does not depend on a file.	string	40
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Workstation_symphony_id	An identifier used in the Symphony file to identify the workstation.	string	16
Dep_job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the file specified in the <b>File_id</b> column.	character	16
Dep_job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream that depends on the file specified in the <b>File_id</b> column.	string	801
Dep_job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream that depends on the file specified in the <b>File_id</b> column.	string	16
Dep_job_wks_folder_id	The identifier of the folder containing the workstation of the job that depends on the file specified in the <b>File_id</b> column.	character	16
Dep_job_wks_folder_name	The name of the folder containing the workstation of the job that depends on the file specified in the <b>File_id</b> column.	string	801
Dep_job_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job that depends on the file specified in the <b>File_id</b> column.	string	16

## Output example

[Table 13: FILE\\_REFS\\_V output example on page 30](#) shows an example of the output for the FILE\_REFS\_V view.

Table 13. FILE\_REFS\_V output example

WORKSTATION_NAME	FILE_NAME	DEP_JOB_STREAM_WKS_NAME	DEP_JOB_STREAM_FOLDER_NAME	DEP_JOB_STREAM_NAME	DEP_JOB_STREAM_VALID_FROM
JA_BAT01	/ii_aa/A1.tt	JA_BAT01	PAYROLL	BD601C200N06110D	-
JA_BAT01	/aa_11/AR.t8	JA_BAT01	PAYROLL	BD601C200N07040E	-
JA_BAT02	/ae_bb/AR.t^	JA_BAT02	PAYROLL	BD601C200N136051	-
JA_BAT02	/ac_ab/EX.tx	JA_BAT02	PAYROLL	BD601C200N083409	-
JA_BAT03	/ad_ab/ET.tx	JA_BAT03	PAYROLL	BD601C200N062102	-
JA_BAT03	/af_ff/TP.t^	JA_BAT03	PAYROLL	BM100F600N800401	-
JA_BAT04	/ag_rd/AS.P^	JA_BAT04	PAYROLL	BD601C200N136808	-
JA_BAT04	/as_dd/YE.P^	JA_BAT04	PAYROLL	BY100F900N081701	-
JA_BAT05	/xi_rr/FT.Z9	JA_BAT05	PAYROLL	BD101C200N113401	-
JA_BAT05	/ci_jj/YE.CL	JA_BAT05	PAYROLL	BDENE-DMYN017009	-

10 record(s) selected.

DEP_JOB_STREAM_VALID_TO	DEP_JOB_WKS_NAME	DEP_JOB_FOLDER_NAME	DEP_JOB_NAME	DEP_JOB_DEFINITION_NAME
-	-	/REPORT1/	-	-
-	-	/REPORT1	-	-
-	-	/REPORT3/	-	-
-	-	/REPORT6/	-	-
-	-	/REPORT5/	-	-
-	-	/REPORT2/	-	-
-	-	/REPORT2/	-	-
-	-	/REPORT6/	-	-
-	-	/REPORT6/	-	-
-	-	/REPORT6/	-	-

WORKSTATION_FOLDER_NAME	DEP_JOB_STREAM_WKS_FOLDER_NAME
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/
/	/FOLDER1/

## INTERNETWORK\_DEPS\_V

The INTERNETWORK\_DEPS\_V view displays information about jobs and job streams that depend on an internetwork dependency.

Table 14. The INTERNETWORK\_DEPS\_V view

Column name	Description	Type	Length
Internetwork_dependency	The internetwork dependency on which the job and job stream depend.	string	255
Network_agent_identifier	The identifier of the network agent where the internetwork dependency is resolved.	character	16
Network_agent_name	The name of the network agent where the internetwork dependency is resolved.	string	16
Dep_job_stream_wks_identifier	The identifier of the workstation where the job stream that depends on the internetwork dependency is defined.	character	16

**Table 14. The INTERNETWORK\_DEPS\_V view (continued)**

Column name	Description	Type	Length
Dep_job_stream_wks_name	The name of the workstation where the job stream that depends on the internetwork dependency is defined.	string	16
Dep_job_stream_folder_id	The identifier of the folder containing the job stream that depends on the internetwork dependency.	character	16
Dep_job_stream_folder_name	The name of the folder containing the job stream that depends on the internetwork dependency.	string	801
Dep_job_stream_identifier	The identifier of the job stream that depends on the internetwork dependency.	character	16
Dep_job_stream_name	The name of the job stream that depends on the internetwork dependency.	string	16
Dep_job_stream_valid_from	The starting date from which the dependent job stream is included in a production plan if selected by a run cycle.	date	<b>10</b> In DB2® <b>9</b> In Oracle
Dep_job_stream_valid_to	The last date that the dependent job stream is included in a production plan if selected by a run cycle.	date	<b>10</b> In DB2® <b>9</b> In Oracle
Dep_job_wks_identifier	The identifier of the workstation where the job that depends on the internetwork dependency is defined. If this field is not displayed, the job does not depend on any internetwork dependency.	character	16
Dep_job_wks_name	The name of the workstation where the job that depends on the internetwork dependency is defined. If this field is not displayed, the job does not depend on any internetwork dependency.	string	16

**Table 14. The INTERNETWORK\_DEPS\_V view (continued)**

Column name	Description	Type	Length
Dep_job_identifier	The identifier of the job that depends on the internetwork dependency. If this field is not displayed, the job does not depend on any internetwork dependency.	character	16
Dep_job_name	The name of the job that depends on the internetwork dependency. If this field is not displayed, the job does not depend on any internetwork dependency.	string	40
Dep_job_folder_id	The identifier of the folder containing the job that depends on the internetwork dependency.	character	16
Dep_job_folder_name	The name of the folder containing the job that depends on the internetwork dependency.	string	801
Dep_job_definition_identifier	The identifier of the job definition that depends on the internetwork dependency. If this field is not displayed, the job does not depend on any internetwork dependency.	character	16
Dep_job_definition_name	The name of the job definition that depends on the internetwork dependency. If this field is not displayed, the job does not depend on any internetwork dependency.	string	40
Dep_job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the internetwork dependency.	character	16
Dep_job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream that depends on the internetwork dependency.	string	801
Dep_job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream that depends on the internetwork dependency.	string	16
Dep_job_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job that depends on the internetwork dependency.	character	16
Dep_job_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job that depends on the internetwork dependency.	string	801
Dep_job_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job that depends on the internetwork dependency.	string	16

## JOB\_DEFINITION\_REFS\_V

The JOB\_DEFINITION\_REFS\_V view displays information about the job streams in which a job appears.

**Table 15. The JOB\_DEFINITION\_REFS\_V view**

Column name	Description	Type	Length
Job_stream_wks_identifier	The identifier of the workstation where the job streams in which the job appears are defined.	character	16
Job_stream_wks_name	The name of the workstation where the job streams in which the job appears are defined.	string	16
Job_stream_folder_id	The identifier of the folder containing the job stream in which the job appears.	character	16
Job_stream_folder_name	The name of the folder containing the job stream in which the job appears.	string	801
Job_stream_identifier	The identifier of the job stream in which the job appears.	character	16
Job_stream_name	The name of the job stream in which the job appears.	string	16
Job_stream_valid_from	The starting date from which the job stream is included in a production plan if selected by a run cycle.	date	10 In D B2® 9 In Or a cle
Job_stream_valid_to	The last date that the job stream is included in a production plan if selected by a run cycle.	date	10 In D B2® 9 In Or a cle

**Table 15. The JOB\_DEFINITION\_REFS\_V view (continued)**

Column name	Description	Type	Length
Job_wks_identifier	The identifier of the workstation where the job specified in the <b>Job_definition_identifier</b> column is defined.	character	16
Job_wks_name	The name of the workstation where the job specified in the <b>Job_name</b> column is defined.	string	16
Job_folder_id	The identifier of the folder containing the job.	character	16
Job_folder_name	The name of the folder containing the job.	string	801
Job_name	The name of the job that appears in the job stream.	string	40
Job_definition_identifier	The identifier of the job definition of the job specified in the <b>Job_name</b> column.	character	16
Job_definition_name	The name of the job definition of the job specified in the <b>Job_name</b> column.	string	40
Job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream.	character	16
Job_stream_wks_folder_name	The name of the folder containing the workstation of the job's job stream.	string	801
Job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job's job stream.	string	16
Job_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job specified in the <b>Job_name</b> column.	character	16
Job_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job specified in the <b>Job_name</b> column.	string	801
Job_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job specified in the <b>Job_name</b> column.	string	16

## Output example

[Table 16: JOB\\_DEFINITION\\_REFS\\_V view output example on page 34](#) shows the output for the JOB\_DEFINITION\_REFS\_V view.

**Table 16. JOB\_DEFINITION\_REFS\_V view output example**

JOB_STREAM_WKS_NAME	JOB_STREAM_FOLDER_NAME	JOB_STREAM_NAME	JOB_STREAM_VALID_FROM	JOB_STREAM_VALID_TO	JOB_WKS_NAME	JOB_NAME
-----	-----	-----	-----	-----	-----	-----

Table 16. JOB\_DEFINITION\_REFS\_V view output example (continued)

F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_206
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_151
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_181
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_107
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_45
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_137
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_46
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_50
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_12
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_5
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_31
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_61
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_165
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_159
F135079S1_07	EUROPE	JOBSTREAM_0035	-	-	F135079S1_07	JOB_105

15 record(s) selected.

JOB_DEFINITION_NAME	JOB_STREAM_WKS_FOLDER_NAME	JOB_WKS_FOLDER_NAME
JOB_206	/	/
JOB_207	/	/
JOB_208	/	/
JOB_209	/	/
JOB_201	/	/
JOB_202	/	/
JOB_203	/	/
JOB_204	/	/
JOB_205	/	/
JOB_206	/	/
JOB_207	/	/
JOB_208	/	/
JOB_209	/	/
JOB_201	/	/
JOB_202	/	/

JOB_WKS_FOLDER_NAME	JOB_WKS_SYMPHONY_ID
/	/

## JOB\_DEPS\_V

The JOB\_DEPS\_V view displays information about jobs and job streams that depend on a job.

Table 17. The JOB\_DEPS\_V view

Column name	Description	Type	Length
Type_of_dependency	The type of dependency. Possible values are: <ul style="list-style-type: none"> <li>Internal job dependency</li> <li>Internal conditional job dependency</li> <li>External job dependency</li> <li>External conditional job dependency</li> <li>External job stream dependency</li> <li>External conditional job stream dependency</li> </ul>	character	42
Job_identifier	The identifier of the job on which the jobs and job streams depend.	character	16
Job_name	The name of the job on which the jobs and job streams depend.	string	40

Table 17. The JOB\_DEPS\_V view (continued)

Column name	Description	Type	Length
Job_stream_wks_identifier	The identifier of the workstation where the job stream that contains the job on which the jobs and job streams depend is defined.	character	16
Job_stream_wks_name	The name of the workstation where the job stream that contains the job on which the jobs and job streams depend is defined.	string	16
Job_stream_folder_id	The identifier of the folder that includes the job stream containing the job on which the jobs and job streams depend.	character	16
Job_stream_folder_name	The name of the folder that includes the job stream containing the job on which the jobs and job streams depend.	string	801
Job_stream_identifier	The identifier of the job stream that contains the job on which the jobs and job streams depend.	character	16
Job_stream_name	The name of the job stream that contains the job on which the jobs and job streams depend.	string	16
Dep_job_stream_wks_identifier	The identifier of the workstation where the job stream that depends on the job specified in the <b>Job_identifier</b> column is defined.	character	16
Dep_job_stream_wks_name	The name of the workstation where the job stream that depends on the job specified in the <b>Job_name</b> column is defined.	string	16
Dep_job_stream_folder_id	The identifier of the folder containing the job stream that depends on the job specified in the <b>Job_identifier</b> column.	character	16
Dep_job_stream_folder_name	The name of the folder containing the job stream that depends on the job specified in the <b>Job_identifier</b> column.	string	801
Dep_job_stream_identifier	The identifier of the job stream that depends on the job specified in the <b>Job_identifier</b> column.	character	16
Dep_job_stream_name	The name of the job stream that depends on the job specified in the <b>Job_name</b> column.	string	16

Table 17. The JOB\_DEPS\_V view (continued)

Column name	Description	Type	Length
Dep_job_stream_valid_from	The starting date from which the dependent job stream is included in a production plan if selected by a run cycle.	date	10 In D B2® 9 In Or a cle
Dep_job_stream_valid_to	The last date that the dependent job stream is included in a production plan if selected by a run cycle.	date	10 In D B2® 9 In Or a cle
Dep_job_identifier	The identifier of the job that depends on the job specified in the Job_name column. If this field is not displayed, the job or the job stream does not depend on any job.	Character	16
Dep_job_name	The name of the job that depends on the job specified in the Job_name column. If this field is not displayed, the job or the job stream does not depend on any job.	string	40
Dep_job_critical	The job specified in the Dep_job_name column is a critical job. Possible values are:  Y Yes  N No	character	1
Conditional_dep_id	The identifier of the dependency where the output conditions are specified. Valid only for the Type_of_dependency column:	character	16

Table 17. The JOB\_DEPS\_V view (continued)

Column name	Description	Type	Length
	<ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>		
Condition_on_success	<p>The condition on SUCCESS status is enabled. Possible values are:</p> <p><b>Y</b> Yes</p> <p><b>N</b> No</p> <p>Valid only for the <b>Type_of_dependency</b> column:</p> <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>	character	1
Condition_on_abend	<p>The condition on ABEND status is enabled. Possible values are:</p> <p><b>Y</b> Yes</p> <p><b>N</b> No</p> <p>Valid only for the <b>Type_of_dependency</b> column:</p> <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>	character	1
Condition_on_fail	<p>The condition on FAIL status is enabled. Possible values are:</p> <p><b>Y</b> Yes</p> <p><b>N</b> No</p>	character	1

Table 17. The JOB\_DEPS\_V view (continued)

Column name	Description	Type	Length
	Valid only for the <b>Type_of_dependency</b> column:  <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>		
Condition_on_execute	The condition on EXECUTE status is enabled. Possible values are:  <b>Y</b>  Yes  <b>N</b>  No  Valid only for the <b>Type_of_dependency</b> column:  <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>	character	1
Condition_on_suppress	The condition on SUPPRESS status is enabled. Possible values are:  <b>Y</b>  Yes  <b>N</b>  No  Valid only for the <b>Type_of_dependency</b> column:  <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>	character	1
Join_id	The identifier of the join containing more than one conditional dependency. Valid only for the <b>Type_of_dependency</b> column:	character	16

**Table 17. The JOB\_DEPS\_V view (continued)**

Column name	Description	Type	Length
	<ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>		
Join_name	<p>The name of the join containing more than one conditional dependency. Valid only for the <b>Type_of_dependency</b> column:</p> <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>	string	16
Join_quantity	<p>The number of dependencies that must be satisfied in the join specified by <b>Join_name</b>. Valid only for the <b>Type_of_dependency</b> column:</p> <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>	integer	5
Job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream.	character	16
Job_stream_wks_folder_name	The name of the folder containing the workstation of the job's job stream.	string	801
Job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job's job stream.	string	16
Dep_job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the job.	character	16
Dep_job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream that depends on the job.	string	801
Dep_job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream that depends on the job.	string	16

## Output example

Table 18: JOB\_DEPS\_V view output example on page 41 shows an example of the output for the JOB\_DEPS\_V view.

Table 18. JOB\_DEPS\_V view output example

TYPE_OF_DEPENDENCY	JOB_NAME	JOB_STREAM_WKS_NAME	JOB_STREAM_NAME	DEP_JOB_STREAM_WKS_NAME	DEP_JOB_STREAM_NAME
Internal Job dependency	BD690C200	JA_BAT02	BD601C200N06110D	JA_BAT02	BD601C200N06110D
Internal Job dependency	BD690C200	JA_BAT02	BD601C200N07040E	JA_BAT02	BD601C200N07040E
Internal Job dependency	BD690C200	JA_BAT02	BD601C200N136051	JA_BAT02	BD601C200N136051
Internal Job dependency	BD690C200	JA_BAT02	BD601C200N083409	JA_BAT02	BD601C200N083409
Internal Job dependency	BD690C200	JA_BAT03	BD601C200N062102	JA_BAT03	BD601C200N062102
Internal Job dependency	BM110F600	JA_BAT03	BM100F600N800401	JA_BAT03	BM100F600N800401
Internal Job dependency	BD600C200	JA_BAT05	BD601C200N136808	JA_BAT05	BD601C200N136808
Internal Job dependency	BY153F900	JA_BAT04	BY100F900N081701	JA_BAT04	BY100F900N081701
Internal Job dependency	BD121C200	JA_BAT04	BD101C200N113401	JA_BAT04	BD101C200N113401
Internal Job dependency	BSGDE-BTS	JA_BAT04	BDENE-DMYN017009	JA_BAT04	BDENE-DMYN017009
Internal Job dependency	BD121C200	JA_BAT01	BD101C200N051001	JA_BAT01	BD101C200N051001
Internal Job dependency	BR114B100	JA_BAT01	BR100B100N053401	JA_BAT01	BR100B100N053401
Internal Job dependency	BD690C200	JA_BAT01	BD601C200N80060A	JA_BAT01	BD601C200N80060A
Internal Job dependency	BM100F700	JA_BAT01	BM100F700N112701	JA_BAT01	BM100F700N112701
Internal Job dependency	BY107F000	JA_BAT01	BY105F000N070501	JA_BAT01	BY105F000N070501

15 record(s) selected.

DEP_JOB_STREAM_VALID_FROM	DEP_JOB_STREAM_VALID_TO	DEP_JOB_NAME	DEP_JOB_CRITICAL
-	-	BD611C200	Y
-	-	BD608C200	N
-	-	BD604C200	N
-	-	BD611C200	Y
-	-	BD607C200	Y
-	-	BM111F600	N
-	-	BD691C200	N
-	-	BY154F900	N
-	-	BD122C200	Y
-	-	BDENE-DMY	N
-	-	BD122C200	Y
-	-	BR115B100	N
-	-	BD608C200	N
-	-	BM101F700	N
-	-	BY105F000	N

JOB_STREAM_WKS_FOLDER_NAME	JOB_WKS_FOLDER_NAME
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/
/	/PRD/APP/APP1/

## JOB\_HISTORY\_V

The JOB\_HISTORY\_V view displays information about job history.

Table 19. The JOB\_HISTORY\_V view

Column name	Description	Type	Length
Workstation_name	The name of the workstation or workstation class where the job was scheduled to run.	string	16
Job_stream_wks_name_in_run	The name of the workstation or workstation class where the job stream ran.	string	16
Job_stream_folder_name	The name of the folder where the job stream that ran is contained.	string	801

**Table 19. The JOB\_HISTORY\_V view (continued)**

Column name	Description	Type	Length
Job_definition_identifier	The identifier of the job definition.	character	16
Job_name	The name of the job.	string	40
Job_folder_id	The identifier of the folder that includes the job for which you want information displayed.	character	16
Job_folder_name	The name of the folder containing the job for which you want information displayed.	string	801
Job_run_date_time	The date and time when the job ran.	timestamp	<b>26</b> In D B2® <b>35</b> In Or a cle
Late_start_time	How late the job started with respect to the latest start time. This time is expressed in milliseconds.	integer	12
Late_end_time	How late the job ended with respect to the deadline. This time is expressed in milliseconds.	integer	12
Planned_duration	The time that a job was expected to complete. This time is expressed in milliseconds.	integer	12
Job_start_time	The date and time when the job was scheduled to start running.	timestamp	<b>26</b> In D B2® <b>35</b> In Or a cle

Table 19. The JOB\_HISTORY\_V view (continued)

Column name	Description	Type	Length
Job_end_time	The date and time when the job was scheduled to stop running.	timestamp	26 In D B2® 35 In Or a cle
Workstation_name_in_run	The name of the workstation or workstation class where the job ran.	string	16
Actual_workstation_name_in_run	The name of the workstation where the job actually ran. Useful for jobs defined on X-AGENT, POOL and D-POOL workstation types.	string	16
Workstation_license_type	The type of license associated with the <b>Actual_workstation_name_in_run</b> . Supported values are:  <b>J</b> PER_JOB  <b>S</b> PER_SERVER	character	1
Job_stream_name_in_run	The name of the job stream to which the job belonged when it ran.	string	16
Job_name_in_run	The name of the job when it ran.	string	40
Job_identifier_in_run	The identifier of the job when it ran.	character	16
Total_elapsed_time	The amount of time that the job took to run, for this run. This time is expressed in milliseconds.	integer	12
Total_cpu_time	The total amount of CPU time the job used to run, for this run. This time is expressed in milliseconds.	integer	12
Long_duration	If the job lasted longer than planned. Possible values are:  <b>Y</b> Yes	character	1

Table 19. The JOB\_HISTORY\_V view (continued)

Column name	Description	Type	Length
Job_status	<b>N</b>		
	No		
	The status of the job. Possible values are:	character	1
	<b>A</b>		
	Abend		
	<b>S</b>		
	Successful		
Rerun_type	<b>U</b>		
	Unknown		
	<b>E</b>		
	Error		
	The type of run associated with the job instance. Possible values are:	character	1
	<b>R</b>		
	Rerun; the instance is a rerun of the job present in the plan.		
<b>E</b>			
Rerun every; the rerun of a job for which you defined an every option.			
<b>F</b>			
Rerun from; the rerun of a job for which you defined a from option.			
<b>C</b>			
Recovery: the job is a recovery job associated with the planned job.			
<b>N</b>			
Regular: the job is not a rerun			
Rerun_number	The position that this run has in the ordered list of all the runs if the job ran multiple times.	integer	10
Return_code	The return code assigned to the job instance.	integer	10
Job_number	The numeric identifier of the job instance.	integer	10

Table 19. The JOB\_HISTORY\_V view (continued)

Column name	Description	Type	Length
Job_stream_instance_id	The identifier of the job stream instance to which the job belonged when it ran.	integer	20
job_critical_latest_time	The latest date and time when the critical job should have started to complete on time.	timestamp	<b>26</b> In D B2® <b>35</b> In Or a cle
Job_critical	If the job was flagged as critical. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Job_promoted	If the job was promoted to prioritize its execution. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Log_time	The date and time when the job run is logged.	timestamp	<b>26</b> In D B2® <b>35</b> In Or a cle
User_login	The user name under which the job instance ran.	string	47

**Table 19. The JOB\_HISTORY\_V view (continued)**

Column name	Description	Type	Length
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Workstation_symphony_id	An identifier used in the Symphony file to identify the workstation.	string	16

## JOB\_STATISTICS\_V

The JOB\_STATISTICS\_V view displays information about jobs.

**Table 20. The JOB\_STATISTICS\_V view**

Column name	Description	Type	Length
Workstation_name	The name of the workstation or workstation class where the job was defined.	string	16
Job_definition_identifier	The identifier of the job definition.	character	16
Job_name	The name of the job.	string	40
Job_description	A description of the job.	string	120
Job_login_user	The user name under which the job runs.	string	47
Job_script_name	The script or the command that the job runs.	string	<b>4095</b> In DB2® <b>4000</b> In Oracle
Job_folder_id	The identifier of the folder that includes the job for which you want information displayed.	character	16
Job_folder_name	The name of the folder containing the job for which you want information displayed.	string	801
Recovery_job_definition_id	The identifier of the job definition to be run, if the job specified in the job_definition_identifier column ends abnormally.	character	16

Table 20. The JOB\_STATISTICS\_V view (continued)

Column name	Description	Type	Length
Recovery_job_name	The name of the job to run if the job specified in the <b>Job_name</b> column ends abnormally.	string	40
Recovery_option	The recovery options for the job. Possible values are:  <b>C</b> Continue  <b>R</b> Rerun  <b>S</b> Stop	character	1
Recovery_repeat_interval	The interval in milliseconds after which a new execution of the job is launched if the job failed	integer	12
Recovery_repeat_occurrences	The number of maximum attempts to launch the job if it failed	integer	5
Recovery_repeat_affinity	Specify whether the failed job must be rerun on the same workstation or the target workstation must be selected by the broker. Supported values are:  <b>Y</b> Yes: rerun on the same workstation.  <b>N</b> No: the target workstation must be selected by the broker.	character	1
Recovery_prompt	The text of the recovery prompt to display if the job ends abnormally.	string	200
Job_modify_user	The name of the user who created or modified the job definition.	string	50
Successful_runs	The number of times the job ran successfully.	integer	10
Abended_runs	The number of times the job ended abnormally.	integer	10
Long_duration_runs	The number of times the jobs with long duration ran.	integer	10
Suppressed_runs	The number of jobs that have been suppressed, that is the number of jobs whose until time has been reached, but the job has not yet started.	integer	10

**Table 20. The JOB\_STATISTICS\_V view (continued)**

Column name	Description	Type	Length
Late_start_runs	The number of times the jobs ended after the latest start time was reached.	integer	10
Late_end_runs	The number of times the jobs ended after the deadline was reached.	integer	10
Total_reruns	The total number of times the job reran.	integer	10
Average_cpu_time	The average amount of CPU time the job took to run. This time is expressed in milliseconds.	integer	12
Average_elapsed_time	The average time the job took to run. This time is expressed in milliseconds.	integer	12
Total_elapsed_time	The sum of the times the job used the CPU and the time the job waited for other processes to release the CPU for all its runs. This time is expressed in milliseconds.	integer	12
Total_cpu_time	The total amount of CPU time the job used to run, for all its runs. This time is expressed in milliseconds.	integer	12
Last_cpu_time	Specifies how much CPU time the job used the last time it ran. This time is expressed in milliseconds.	integer	12
Last_elapsed_time	The elapsed time recorded during the job last run of the job. This time is expressed in milliseconds.	integer	12
Last_run_date	The date and time the job last ran.	timestamp	<b>26</b> In DB2® <b>35</b> In Oracle
Max_cpu_time	The maximum CPU time recorded for all the job runs. This time is expressed in milliseconds.	integer	12
Max_elapsed_time	The maximum elapsed time recorded for all its runs. This time is expressed in milliseconds.	integer	12
Max_run_date	The date and time when the job took the longest time to run.	timestamp	<b>26</b> In DB2®

**Table 20. The JOB\_STATISTICS\_V view (continued)**

Column name	Description	Type	Length
			<b>35</b>
			In Ora cle
Min_cpu_time	The minimum CPU time recorded for all the runs. This time is expressed in milliseconds.	integer	12
Min_elapsed_time	The minimum elapsed time recorded for all its runs.	integer	12
Min_run_date	The date and time when the job took the shortest time to run.	timestamp	<b>26</b>
			In DB2®
			<b>35</b>
			In Ora cle
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Workstation_symphony_id	An identifier used in the Symphony file to identify the workstation.	string	16

## JOB\_STREAM\_DEPS\_V

The JOB\_STREAM\_DEPS\_V view displays information about jobs and job streams that depend on a job stream.

**Table 21. The JOB\_STREAM\_DEPS\_V view**

Column name	Description	Type	Length
Type_of_dependency	The type of dependency. Possible values are: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>	character	33

**Table 21. The JOB\_STREAM\_DEPS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_wks_identifier	The identifier of the workstation where the job stream on which the jobs or job streams depend is defined.	character	16
Job_stream_wks_name	The name of the workstation where the job stream on which the jobs or job streams depend is defined.	string	16
Job_stream_folder_id	The identifier of the folder that includes the job stream on which the jobs and job streams depend.	character	16
Job_stream_folder_name	The name of the folder that includes the job stream on which the jobs and job streams depend.	string	801
Job_stream_identifier	The identifier of the job stream on which the jobs and job streams depend.	character	16
Job_stream_name	The name of the job stream on which the job or job stream depends.	string	16
Dep_job_stream_wks_identifier	The identifier of the workstation where the job stream that depends on the job stream is defined.	character	16
Dep_job_stream_wks_name	The name of the workstation where the job stream that depends on the job stream is defined.	string	16
Dep_job_stream_folder_id	The identifier of the folder containing the job stream that depends on the job stream.	character	16
Dep_job_stream_folder_name	The name of the folder containing the job stream that depends on the job stream.	string	801
Dep_job_stream_identifier	The identifier of the job stream that depends on the job stream.	character	16
Dep_job_stream_name	The name of the job stream that depends on the job stream.	string	16
Dep_job_stream_valid_from	The starting date from which the dependent job stream is included in a production plan if selected by a run cycle.	date	<b>10</b> In D B2® <b>9</b> In Ora cle

Table 21. The JOB\_STREAM\_DEPS\_V view (continued)

Column name	Description	Type	Length
Dep_job_stream_valid_to	The last date that the dependent job stream is included in a production plan if selected by a run cycle.	date	10 In D B2@ 9 In Ora cle
Dep_job_wks_identifier	The identifier of the workstation where the job that depends on the job stream is defined. If this field is not displayed, the job does not depend on any job stream.	character	16
Dep_job_wks_name	The name of the workstation where the job that depends on the job stream is defined. If this field is not displayed, the job does not depend on any job stream.	string	16
Dep_job_identifier	The identifier of the job that depends on the job stream. If this field is not displayed, the job does not depend on any job stream.	character	16
Dep_job_name	The name of the job that depends on the job stream. If this field is not displayed, the job does not depend on any job stream.	string	40
Dep_job_critical	The job specified in the <b>Dep_job_name</b> column is a critical job. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Dep_job_folder_id	The identifier of the folder containing the job that depends on the job stream.	character	16
Dep_job_folder_name	The name of the folder containing the job that depends on the job stream.	string	801
Dep_job_definition_identifier	The identifier of the job definition that depends on the job stream. If this field is not displayed, the job does not depend on any job stream.	character	16

**Table 21. The JOB\_STREAM\_DEPS\_V view (continued)**

Column name	Description	Type	Length
Dep_job_definition_name	The name of the job definition that depends on the job stream. If this field is not displayed, the job does not depend on any job stream.	string	40
Conditional_dep_id	The identifier of the dependency where the output conditions are specified. Valid only for the <b>Type_of_dependency</b> column: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>	character	16
Condition_on_success	The condition on SUCCESS status is enabled. Possible values are: <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p> Valid only for the <b>Type_of_dependency</b> column: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>	character	1
Condition_on_abend	The condition on ABEND status is enabled. Possible values are: <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p> Valid only for the <b>Type_of_dependency</b> column: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> </ul>	character	1

Table 21. The JOB\_STREAM\_DEPS\_V view (continued)

Column name	Description	Type	Length
	<ul style="list-style-type: none"> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>		
Condition_on_fail	<p>The condition on FAIL status is enabled. Possible values are:</p> <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p> <p>Valid only for the <b>Type_of_dependency</b> column:</p> <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>	character	1
Condition_on_execute	<p>The condition on EXECUTE status is enabled. Possible values are:</p> <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p> <p>Valid only for the <b>Type_of_dependency</b> column:</p> <ul style="list-style-type: none"> <li>• Internal conditional job dependency</li> <li>• External conditional job dependency</li> <li>• External conditional job stream dependency</li> </ul>	character	1
Condition_on_suppress	<p>The condition on SUPPRESS status is enabled. Possible values are:</p> <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p>	character	1

Table 21. The JOB\_STREAM\_DEPS\_V view (continued)

Column name	Description	Type	Length
	Valid only for the <b>Type_of_dependency</b> column: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>		
Job_stream_identifier	The identifier of the job stream on which the job or job stream depends.	character	16
Join_id	The identifier of the join containing more than one conditional dependency. Valid only for the <b>Type_of_dependency</b> column: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>	character	16
Join_name	The name of the join containing more than one conditional dependency. Valid only for the <b>Type_of_dependency</b> column: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>	string	16
Join_quantity	The number of dependencies that must be satisfied in the join specified by <b>Join_name</b> . Valid only for the <b>Type_of_dependency</b> column: <ul style="list-style-type: none"> <li>• Job dependency</li> <li>• Conditional job dependency</li> <li>• Job stream dependency</li> <li>• Conditional job stream dependency</li> </ul>	integer	5
Job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream.	character	16

**Table 21. The JOB\_STREAM\_DEPS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream.	string	801
Job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream.	string	16
Dep_job_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job stream on which the job or job stream depends.	character	16
Dep_job_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job stream on which the job or job stream depends.	string	801
Dep_job_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream on which the job or job stream depends.	string	16
Dep_job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream on which the job or job stream depends.	character	16
Dep_job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream on which the job or job stream depends.	string	801
Dep_job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream on which the job or job stream depends.	string	16

## Output example

Table 22: JOB\_STREAM\_DEPS\_V view output example on page 55 shows an example of the output for the JOB\_STREAM\_DEPS\_V view.

**Table 22. JOB\_STREAM\_DEPS\_V view output example**

JOB_STREAM_WKS_NAME	JOB_STREAM_FOLDER_NAME	JOB_STREAM_NAME	DEP_JOB_STREAM_WKS_NAME	DEP_JOB_STREAM_FOLDER_NAME
AAPBC1	/E_EUROPE/	JOBSTREAM_1041	JA_BAT01	/PAYROLL/
BAPBC2	/E_EUROPE/	JOBSTREAM_1042	JA_BAT02	/PAYROLL/
BAPBS3	/E_EUROPE/	JOBSTREAM_1043	JA_BAT03	/HEALTHPLAN/
CAPBD4	/E_EUROPE/	JOBSTREAM_1044	JA_BAT04	/PAYROLL
XAPBZ5	/E_EUROPE/	JOBSTREAM_1045	JA_BAT05	/VACATION/
QAPSS6	/E_EUROPE/	JOBSTREAM_1046	JA_BAT06	/HEALTHPLAN/
SSAPA7	/E_EUROPE/	JOBSTREAM_1047	JA_BAT07	/BENEFITS/
RRPBE8	/E_EUROPE/	JOBSTREAM_1048	JA_BAT08	/BENEFITS/
RTPBE9	/E_EUROPE/	JOBSTREAM_1049	JA_BAT09	/PAYROLL/
YYPBE1	/E_EUROPE/	JOBSTREAM_1060	JA_BAT02	/ABSENCES/
UUPBE2	/E_EUROPE/	JOBSTREAM_1060	JA_BAT02	/HEALTHPLAN/
IIPBE3	/E_EUROPE/	JOBSTREAM_1040	JA_BAT02	/BENEFITS/
OOD333	/E_EUROPE/	JOBSTREAM_1040	JA_BAT02	/ABSENCES/
SAP001	/E_EUROPE/	JOBSTREAM_1040	JA_BAT02	/LEAVE/
SAPEE2	/E_EUROPE/	JOBSTREAM_1040	JA_BAT02	/LEAVE/

15 record(s) selected.

**Table 22. JOB\_STREAM\_DEPS\_V view output example (continued)**

DEP_JOB_STREAM_NAME	DEP_JOB_STREAM_VALID_FROM	DEP_JOB_STREAM_VALID_TO	DEP_JOB_WKS_NAME	DEP_JOB_NAME	DEP_JOB_CRITICAL
BD601C200N06111D	-	-	JA_BAT02	BD611C200	Y
BD601C200N06111D	-	-	JA_BAT02	BD608C200	Y
BD601C200N06115D	-	-	JA_BAT05	BM111F600	N
BD601C200N06116D	-	-	JA_BAT05	BD691C200	N
BD601C200N06117D	-	-	JA_BAT01	BY154F900	N
BD601C200N06118D	-	-	JA_BAT01	BD122C200	N
BD601C200N06119D	-	-	JA_BAT01	BDENE-DMY	N
BD601C200N06110D	-	-	JA_BAT01	BD122C200	N
BD601C200N06110D	-	-	JA_BAT04	BR115B100	N
BD601C200N06110D	-	-	JA_BAT04	BD608C200	Y
BBD601C200N06110	-	-	JA_BAT04	BM101F700	Y
BD601C200N06110D	-	-	JA_BAT04	BY105F000	N

  

DEP_JOB_DEFINITION_NAME	JOB_STREAM_WKS_FOLDER_NAME	DEP_JOB_WKS_FOLDER_NAME	DEP_JOB_STREAM_WKS_FOLDER_NAME
BD611C200	/	/FOLDER1/	/
BD608C200	/	/FOLDER1/	/
BD604C200	/	/FOLDER1/	/
BD611C200	/	/FOLDER2/	/
BD607C200	/	/FOLDER2/	/
BM111F600	/	/FOLDER2/	/
BD691C200	/	/FOLDER2/	/
BY154F900	/	/FOLDER2/	/
BD122C200	/	/FOLDER1/	/
BDENE-DMY	/	/FOLDER3/	/
BD122C200	/	/FOLDER3/	/
BR115B100	/	/FOLDER3/	/
BD608C200	/	/FOLDER1/	/
BM101F700	/	/FOLDER1/	/
BY105F000	/	/FOLDER1/	/

## JOB\_STREAM\_REFS\_V

The JOB\_STREAM\_REFS\_V view displays information about job streams.

**Table 23. The JOB\_STREAM\_REFS\_V view**

Column name	Description	Type	Length
Workstation_identifier	The identifier of the workstation where the job stream is defined.	character	16
Workstation_name	The name of the workstation where the job stream is defined.	string	16
Job_stream_folder_id	The identifier of the folder containing the job stream for which you want information displayed.	character	16
Job_stream_folder_name	The name of the folder containing the job stream for which you want information displayed.	string	801
Job_stream_identifier	The identifier of the job stream for which you want information displayed.	character	16
Job_stream_name	The name of the job stream for which you want information displayed.	string	16

**Table 23. The JOB\_STREAM\_REFS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_valid_from	The starting date from which the job stream is included in a production plan if selected by a run cycle.	date	10 In DB2® 9 In Oracle
Job_stream_valid_to	The last date that the job stream is included in a production plan if selected by a run cycle.	date	10 In DB2® 9 In Oracle
Calendar_identifier	The identifier of the non-working days calendar.	character	16
Calendar_name	The name of the non-working days calendar.	string	16
Calendar_folder_id	The identifier of the folder where the calendar is stored.	character	16
Calendar_folder_name	The name of the folder where the calendar is stored.	string	801
Workstation_folder_id	The identifier of the folder in which the workstation of the job stream is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation of the job stream is defined.	string	801
Workstation_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream.	string	16

## Output example

[Table 24: JOB\\_STREAM\\_REFS\\_V view output example on page 57](#) shows an example of the output for the JOB\_STREAM\_REFS\_V view.

**Table 24. JOB\_STREAM\_REFS\_V view output example**

WORKSTATION_NAME	JOB_STREAM_NAME	JOB_STREAM_VALID_FROM	JOB_STREAM_VALID_TO	CALENDAR_NAME
F134091S1_17	JOBSTREAM_1040	-	-	-
F237024S1_10	JOBSTREAM_2125	-	-	-
F135079S1_19	JOBSTREAM_1455	-	-	-
F134092S1_17	JOBSTREAM_0600	-	-	-
F237024S1_11	JOBSTREAM_2155	-	-	-
F237024S1_09	JOBSTREAM_2025	-	-	-

**Table 24. JOB\_STREAM\_REFS\_V view output example (continued)**

```

F134091S1_04      JOBSTREAM_0735      -      -      -
F237024S1_05      JOBSTREAM_2055      -      -      -
F135079S1_05      OBSTREAMM_0045      -      -      -
F237024S1_18      JOBSTREAM_2200      -      -      -
F134091S1_16      JOBSTREAM_1020      -      -      -
F237024S1_17      JOBSTREAM_2235      -      -      -
F134091S1_03      JOBSTREAM_0715      -      -      -
F237024S1_14      JOBSTREAM_2120      -      -      -
F135187S1_14      JOBSTREAM_1740      -      -      -

15 record(s) selected.

WORKSTATION_FOLDER_NAME
-----
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/
/PRD/APP/APP1/

```

## LOG\_MESSAGES\_V

The LOG\_MESSAGES\_V view displays information about the messages logged by the actions.

**Table 25. The LOG\_MESSAGES\_V view**

Column name	Description	Type	Length
Log_time	The time when the message associated with the action was logged.	timestamp	26 In D B2@ 35 In Or a cle
Information_type	The type of message that was logged. Possible values are:  I Informational  W Warning	character	1

**Table 25. The LOG\_MESSAGES\_V view (continued)**

Column name	Description	Type	Length
	<b>E</b>		
	Error		
Event_rule_name	The name of the event rule associated with the action.	string	40
Event_rule_type	The type of event rule. Possible values are:	character	1
	<b>F</b>		
	Filter		
	<b>Q</b>		
	Sequence		
	<b>S</b>		
	Set		
Event_scope	The scope of the event. That is the most meaningful information related to the event. The plug-in defines the information to be inserted.	string	120
Event_type	The type of event.	string	40
Source	The source string defined in the log action	string	128
Line_of_business	The line of business defined in the log action.	string	128
Owner_group	The owner group defined in the log action.	string	128
Message	The text of the message written to the log file.	string	512
workstation_name	The name of the workstation where the log is triggered.	string	128

## PLAN\_DOMAINS\_V

The PLAN\_DOMAINS\_V view displays information about the domains in the plan.

**Table 26. The PLAN\_DOMAINS\_V view**

Column name	Description	Type	Length
Domain_id	The identifier of the domain.	character	16
Parent_domain_id	The identifier of the parent domain.	character	16
Domain_Name	The name of the domain specified in the <b>Domain_id</b> column.	string	16

**Table 26. The PLAN\_DOMAINS\_V view (continued)**

Column name	Description	Type	Length
Parent_domain_name	The name of the domain that is parent of the domain specified in the Domain_id column.	string	16
Domain_manager_name	A hexadecimal identifier used in the Symphony file to identify the domain manager of the domain specified in the <b>Domain_id</b> column.	string	16
Domain_manager_orig_name	The name of the domain manager of the domain specified in the <b>Domain_id</b> column.	string	16
Domain_manager_folder_id	The identifier of the folder containing the domain manager specified in the <b>Domain_id</b> column.	character	16
Domain_manager_folder_name	The name of the folder containing the domain manager specified in the <b>Domain_id</b> column.	string	801

## PLAN\_FILE\_REFS\_V

The PLAN\_FILE\_REFS\_V view displays information about jobs and job streams in plan that depend on a file.

**Table 27. The PLAN\_FILE\_REFS\_V view**

Column name	Description	Type	Length
File_name	The name of the file where the dependency is defined.	string	148
Qualifiers	The qualifier of the file specified in the <b>File_id</b> column.	string	148
File_id	The identifier of the file where the dependency is defined.	character	16
File_wks_id	The identifier of the workstation where the file specified in the <b>File_id</b> column is defined.	character	16
File_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation. The name of the workstation where the file specified in the <b>File_id</b> column is defined.	string	16
Workstation_original_name	The name of the workstation where the file specified in the <b>File_id</b> column is defined.	string	16
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Job_stream_refs_id	The identifier of the job stream that depends on the file specified in the <b>File_id</b> column.	character	16

Table 27. The PLAN\_FILE\_REFS\_V view (continued)

Column name	Description	Type	Length
Job_refs_id	The identifier of the job that depends on the file specified in the <b>File_id</b> column.	character	16
Job_refs_js_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream that depends on the file specified in the <b>File_id</b> column.	string	16
Job_refs_js_wks_original_name	The name of the workstation of the job's job stream that depends on the file specified in the <b>File_id</b> column.	string	16
Jobs_refs_js_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job's job stream that depends on the file specified in the <b>File_id</b> column.	character	16
Jobs_refs_js_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job's job stream that depends on the file specified in the <b>File_id</b> column.	string	801
Job_refs_js_id	The identifier of the job's job stream that depends on the file specified in the <b>File_id</b> column.	character	16
Job_refs_js_name	The name of the job's job stream that depends on the file specified in the <b>File_id</b> column.	string	16
Job_refs_js_sched_time	The input arrival time of the job's job stream that depends on the file specified in the <b>File_id</b> column.	timestamp	10
Job_refs_wks_id	The identifier of the workstation of the job that depends on the file specified in the <b>File_id</b> column.	character	16
Job_refs_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the of the job that depends on the file specified in the <b>File_id</b> column.	string	16
Job_refs_wks_original_name	The name of the workstation of the job that depends on the file specified in the <b>File_id</b> column.	string	16
Jobs_refs_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job that depends on the file specified in the <b>File_id</b> column.	character	16
Jobs_refs_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job that depends on the file specified in the <b>File_id</b> column.	string	801
Job_refs_name	The name of the job that depends on the file specified in the <b>File_id</b> column.	string	40

**Table 27. The PLAN\_FILE\_REFS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_refs_wks_id	The identifier of the workstation of the job stream that depends on the file specified in the <b>File_id</b> column.	character	16
Job_stream_refs_wks_name	A hexiadecimal identifier used in the Symphony file to identify the workstation of the of the job stream that depends on the file specified in the <b>File_id</b> .	string	16
Job_stream_wks_original_name	The name of the workstation of the job stream that depends on the file specified in the <b>File_id</b> column.	string	16
Job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the file specified in the <b>File_id</b> column.	character	16
Job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream that depends on the file specified in the <b>File_id</b> column.	string	801
Job_stream_refs_folder_name	The name of the folder that includes the job stream that depends on the file specified in the <b>File_id</b> column.	string	801
Job_stream_refs_folder_id	The identifier of the folder that includes the job stream that depends on the file specified in the <b>File_id</b> column.	character	16
Job_stream_refs_name	The name of the job stream that depends on the file specified in the <b>File_id</b> column.	string	16
Job_stream_refs_sched_time	The input arrival time of the job stream that depends on the file specified in the <b>File_id</b> column.	timestamp	10
Satisfied	If the file dependency is satisfied. Possible values are:  <b>Y</b>  Yes  <b>N</b>  No	character	1
Status	The file dependency status. Possible values are:  <b>S</b>  Satisfied  <b>N</b>  Not_satisfied  <b>U</b>  Undecided	character	1

## PLAN\_FILES\_V

The PLAN\_FILES\_V view displays information about the files in the plan.

**Table 28. The PLAN\_FILES\_V view**

Column name	Description	Type	Length
File_id	The identifier of the file.	character	16
File_name	The name of the file.	string	148
Workstation_id	The identifier of the workstation where the file specified in the <b>File_id</b> column is defined.	character	16
Workstation_name	A hexadecimal identifier used in the Symphony file to identify the workstation.	string	16
Workstation_original_name	The workstation name.	string	16
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Status	The file status. Possible values are:  <b>A</b> Available  <b>N</b> Not_available  <b>U</b> Undecided	character	16
Qualifiers	The qualifier of the file specified in the <b>File_id</b> column.	string	148

## PLAN\_JOB\_PREDECESSORS\_V

The PLAN\_JOB\_PREDECESSORS\_V view displays information about jobs and job streams predecessors of a job in the plan.

**Table 29. The PLAN\_JOB\_PREDECESSORS\_V view**

Column name	Description	Type	Length
Job_name	The name of the job on which the dependency is defined.	string	40

**Table 29. The PLAN\_JOB\_PREDECESSORS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_wks_id	The identifier of the workstation of the job's job stream on which the dependency is defined.	character	16
Job_stream_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream on which the dependency is defined.	string	16
Job_stream_wks_original_name	The name of the workstation of the job stream.	string	16
Job_stream_wks_folder_name	The name of the folder where the workstation of the job stream is defined.	string	801
Job_stream_wks_folder_id	The identifier of the folder where the workstation of the job stream is defined.	character	16
Job_stream_name	The name of the job's job stream on which the dependency is defined.	string	16
Job_wks_id	The identifier of the workstation of the job on which the dependency is defined.	character	40
Job_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job on which the dependency is defined.	string	40
Job_wks_original_name	The name of the workstation of the job.	string	16
Job_wks_folder_name	The name of the folder where the workstation of the job is defined.	string	801
Job_wks_folder_id	The identifier of the folder where the workstation of the job is defined.	character	16
Job_id	The identifier of the job on which the dependency is defined.	character	16
Job_stream_pred_id	The identifier of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_pred_id	The identifier of the job that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_pred_js_wks_id	The identifier of the workstation of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_pred_js_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	string	16

Table 29. The PLAN\_JOB\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
Job_pred_js_wks_original_name	The name of the workstation of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	string	16
Job_pred_js_wks_folder_name	The name of the folder containing the workstation of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	string	801
Job_pred_js_wks_folder_id	The identifier of the folder containing the workstation of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_pred_js_name	The name of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	string	16
Job_pred_js_sched_time	The input arrival time of the job's job stream that depends on the job specified in the <b>Job_id</b> column.	timestamp	10
Job_pred_wks_id	A hexadecimal identifier used in the Symphony file to identify the workstation of the job that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_pred_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job that depends on the job specified in the <b>Job_id</b> column.	string	16
Job_pred_wks_original_name	The name of the workstation of the job that depends on the job specified in the <b>Job_id</b> column.	string	16
Job_pred_wks_folder_name	The name of the folder containing the workstation of the job that depends on the job specified in the <b>Job_id</b> column.	string	861
Job_pred_wks_folder_id	The identifier of the folder containing the workstation of the job that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_pred_name	The name of the job that depends on the job specified in the <b>Job_id</b> column.	string	40
Job_stream_pred_wks_id	The identifier of the workstation of the job stream that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_stream_pred_wks_name	The name of the workstation of the job stream that depends on the job specified in the <b>Job_id</b> column.	string	16
Job_stream_pred_wks_orig_name	The original name of the workstation of the job stream that depends on the job specified in the <b>Job_id</b> column.	string	16
Job_stream_pred_wks_fol_name	The name of the folder containing the workstation of the job stream that depends on the job specified in the <b>Job_id</b> column.	string	801

**Table 29. The PLAN\_JOB\_PREDECESSORS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_pred_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_stream_pred_folder_id	The identifier of the folder containing the job stream that depends on the job specified in the <b>Job_id</b> column.	character	16
Job_stream_pred_folder_name	The name of the folder containing the job stream that depends on the job specified in the <b>Job_id</b> column.	string	801
Job_stream_pred_name	The name of the job stream that depends on the job specified in the <b>Job_id</b> column.	string	16
Job_stream_pred_sched_name	The input arrival time of job stream that depends on the job specified in the <b>Job_id</b> column.	timestamp	10
Satisfied	If the job's dependency is satisfied. Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Status	The job's dependency status. Possible values are: <b>S</b> Satisfied <b>N</b> Not_atisfied <b>U</b> Undecided	character	1
Dependency_type	The job's dependency type. Possible values are: <b>I</b> Internal <b>J</b> External_job <b>S</b> External_job_stream <b>N</b> Internetwork	character	1

Table 29. The PLAN\_JOB\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
Is_conditional_dependency	The job's dependency is a conditional dependency. Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Cond_dep_on_success	The condition is on SUCCESS. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> . Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Cond_dep_on_abend	The condition is on ABEND. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> . Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Cond_dep_on_fail	The condition is on FAIL. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> . Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Cond_dep_on_execute	The condition is on EXECUTE. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> . Possible values are: <b>Y</b> Yes	character	1

Table 29. The PLAN\_JOB\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
Cond_dep_on_suppress	<p><b>N</b> No</p> <p>The condition is on SUPPRESS. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b>. Possible values are:</p> <p><b>Y</b> Yes</p> <p><b>N</b> No</p>	character	1
Join_name	The name of the container of more of one conditional dependency. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> .	string	16
Join_quantity	The number of dependencies that must be satisfied in the join specified in <b>Join_name</b> . Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> .	integer	5
Output_cond_list	The list of output conditions for this job stream dependency. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> .	string	2000

## PLAN\_JOB\_STREAM\_PREDECESSORS\_V

The PLAN\_JOB\_STREAM\_PREDECESSORS\_V view displays information about job and job stream predecessors of a job stream in the plan.

Table 30. The PLAN\_JOB\_STREAM\_PREDECESSORS\_V view

Column name	Description	Type	Length
Job_stream_id	The identifier of the job stream on which the dependency is defined.	character	16
Job_stream_wks_id	The identifier of the workstation of the job stream on which the dependency is defined.	character	16
Job_stream_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job stream on which the dependency is defined.	string	16
Job_stream_wks_original_name	The name of the workstation of the job stream on which the dependency is defined.	string	16

Table 30. The PLAN\_JOB\_STREAM\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
Job_stream_wks_folder_name	The name of the folder in which the workstation of the job stream is defined. The job stream being that on which the dependency is defined.	string	801
Job_stream_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation being that of the job stream on which the dependency is defined.	character	16
Job_stream_folder_id	The identifier of the folder containing the job stream on which the dependency is defined.	character	16
Job_stream_folder_name	The name of the folder containing the job stream on which the dependency is defined.	string	801
Job_stream_name	The name of the job stream on which the dependency is defined.	string	16
Job_stream_pred_id	The identifier of the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_pred_id	The identifier of the job that depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_pred_js_wks_id	The identifier of the workstation of the job's job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_pred_js_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_pred_js_wks_original_name	The name of the workstation of the job's job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
job_pred_js_wks_folder_name	The name of the folder in which the workstation of the job's job stream is defined. The job stream being that which depends on the job stream specified in the <b>Job_stream_id</b> column.	string	801
job_pred_js_wks_folder_id	The identifier of the folder in which the workstation of the job's job stream is defined. The workstation being that of the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16

Table 30. The PLAN\_JOB\_STREAM\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
Job_pred_js_name	The name of the job's job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_pred_js_sched_time	The input arrival time of the job's job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	timestamp	10
Job_pred_wks_id	The identifier of the workstation of the job that depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_pred_wks_name	The name used in the Symphony file to identify the workstation of the job that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_pred_wks_orig_name	The name of the workstation of the job that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_pred_wks_folder_name	The name of the folder in which the workstation of the job is defined. The job being that which depends on the job stream specified in the <b>Job_stream_id</b> column.	string	801
Job_pred_wks_folder_id	The identifier of the folder in which the workstation of the job is defined. The job being that which depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_pred_name	The name of the job that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	40
Job_stream_pred_wks_id	The identifier of the workstation of the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_stream_pred_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_stream_pred_wks_orig_name	The name of the workstation of the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_stream_pred_wks_fol_name	The name of the folder in which the workstation of the job stream is defined. The job stream being that which depends on the job stream specified in the <b>Job_stream_id</b> column.	string	801

Table 30. The PLAN\_JOB\_STREAM\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
Job_stream_pred_wks_folder_id	The identifier of the folder in which the workstation of the job stream is defined. The job stream being that which depends on the job stream specified in the <b>Job_stream_id</b> column.	character	
Job_stream_pred_folder_id	The identifier of the folder containing the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_stream_pred_folder_name	The name of the folder containing the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	801
Job_stream_pred_name	The name of the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_stream_pred_sched_time	The input arrival time of the job stream that depends on the job stream specified in the <b>Job_stream_id</b> column.	timestamp	10
Satisfied	If the job stream's dependency is satisfied. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Status	The job stream's dependency status. Possible values are:  <b>S</b> Satisfied  <b>N</b> Not_satisfied  <b>U</b> Undecided	character	1
Dependency_type	The job stream's dependency type. Possible values are:  <b>I</b> Internal  <b>J</b> External_job	character	1

Table 30. The PLAN\_JOB\_STREAM\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
	<p><b>S</b></p> <p>External_job_stream</p> <p><b>N</b></p> <p>Internetwork</p>		
Is_conditional_dependency	<p>The job stream's dependency is a conditional dependency. Possible values are:</p> <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p>	character	1
Cond_dep_on_success	<p>The condition is on SUCCESS. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b>. Possible values are:</p> <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p>	character	1
Cond_dep_on_abend	<p>The condition is on ABEND. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b>. Possible values are:</p> <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p>	character	1
Cond_dep_on_fail	<p>The condition is on FAIL. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b>. Possible values are:</p> <p><b>Y</b></p> <p>Yes</p> <p><b>N</b></p> <p>No</p>	character	1

Table 30. The PLAN\_JOB\_STREAM\_PREDECESSORS\_V view (continued)

Column name	Description	Type	Length
Cond_dep_on_execute	The condition is on EXECUTE. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> . Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Cond_dep_on_suppress	The condition is on SUPPRESS. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> . Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Join_name	The name of the container of more of one conditional dependency. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> .	string	16
Join_quantity	The number of dependencies that must be satisfied in the join specified in <b>Join_name</b> . Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> .	integer	5
Output_cond_list	The list of output conditions for this job stream dependency. Valid only if the <b>Is_conditional_dependency</b> column is set to <b>Y</b> .	string	2000

## PLAN\_JOB\_STREAM\_SUCCESSORS\_V

The PLAN\_JOB\_STREAM\_SUCCESSORS\_V view displays information about jobs and job streams successors of a job stream in the plan.

Table 31. The PLAN\_JOB\_STREAM\_SUCCESSORS\_V view

Column name	Description	Type	Length
Job_stream_name	The name of the job stream on which the successor is defined.	string	16

**Table 31. The PLAN\_JOB\_STREAM\_SUCCESSORS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_wks_id	The identifier of the workstation of the job stream on which the successor is defined.	character	16
Job_stream_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job stream on which the dependency is defined.	string	16
Job_stream_wks_original_name	The name of the workstation of the job stream on which the dependency is defined.	string	16
Job_stream_wks_folder_name	The name of the folder in which the workstation of the job stream is defined. The job stream being that on which the dependency is defined.	string	801
Job_stream_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation being that of the job stream on which the dependency is defined.	character	16
Job_stream_folder_id	The identifier of the folder containing the job stream on which the successor is defined.	character	16
Job_stream_folder_name	The name of the folder containing the job stream on which the successor is defined.	string	801
Job_stream_id	The identifier of the job stream on which the successor is defined.	character	16
Job_stream_succ_id	The identifier of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_succ_js_wks_id	The identifier of the workstation of the job's job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_succ_js_wks_name	A hexadecimal identifier used in the Symphony file to identify the	string	16

Table 31. The PLAN\_JOB\_STREAM\_SUCCESORS\_V view (continued)

Column name	Description	Type	Length
	workstation of the job's job stream that follows the job stream specified in the <b>Job_stream_id</b> column.		
Job_succ_js_wks_original_name	The name of the workstation of the job's job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_succ_js_wks_folder_name	The name of the folder containing the workstation of the job's job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	801
Job_succ_js_wks_folder_id	The identifier of the folder containing the workstation of the job's job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_succ_js_name	The name of the job's job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_succ_js_sched_time	The input arrival time of the job's job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	timestamp	10
Job_succ_wks_id	The identifier of the workstation of the job that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_succ_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job that follows the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_succ_wks_original_name	The name of the workstation of the job that follows the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_succ_wks_folder_name	The name of the folder containing the workstation of the job that follows the job stream specified in the <b>Job_stream_id</b> column.	string	801

**Table 31. The PLAN\_JOB\_STREAM\_SUCCESSORS\_V view (continued)**

Column name	Description	Type	Length
Job_succ_wks_folder_id	The identifier of the folder containing the workstation of the job that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_succ_name	The name of the job that follows the job stream specified in the <b>Job_stream_id</b> column.	string	40
Job_stream_succ_wks_id	The identifier of the workstation of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_stream_succ_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_stream_succ_wks_orig_name	The name of the workstation of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	16
Job_stream_succ_wks_folder_name	The name of the folder containing the workstation of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	801
Job_stream_succ_wks_folder_id	The identifier of the folder containing the workstation of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_stream_succ_folder_id	The identifier of the folder containing the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_stream_succ_folder_name	The name of the folder containing the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	801
Job_stream_succ_name	The name of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	string	16

**Table 31. The PLAN\_JOB\_STREAM\_SUCCESORS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_succ_sched_time	The input arrival time of the workstation of the job stream that follows the job stream specified in the <b>Job_stream_id</b> column.	timestamp	10
Satisfied	If the job stream's dependency is satisfied. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Status	The job stream's dependency status. Possible values are:  <b>S</b> Satisfied  <b>N</b> Not_satisfied  <b>U</b> Undecided	character	1

## PLAN\_JOB\_SUCCESORS\_V

The PLAN\_JOBS\_SUCCESORS\_V view displays information about jobs and job streams successors of a job in the plan.

**Table 32. The PLAN\_JOBS\_SUCCESORS\_V view**

Column name	Description	Type	Length
Job_name	The name of the job on which the successor is defined.	string	40
Job_stream_wks_id	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream on which the successor is defined.	character	16

**Table 32. The PLAN\_JOBS\_SUCCESSORS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_wks_original_name	The name of the workstation of the job's job stream on which the successor is defined.	string	16
Job_stream_wks_folder_name	The name of the folder where the workstation of the job stream is defined.	string	801
Job_stream_wks_folder_id	The identifier of the folder where the workstation of the job stream is defined.	character	16
Job_stream_wks_name	The name of the workstation of the job's job stream on which the successor is defined.	string	16
Job_wks_original_name	The original name of the workstation of the job.	string	16
Job_wks_folder_name	The name of the folder where the workstation of the job is defined.	string	801
Job_wks_folder_id	The identifier of the folder where the workstation of the job is defined.	character	16
Job_stream_name	The name of the job's job stream on which the successor is defined.	string	16
Job_wks_id	The identifier of the workstation of the job on which the successor is defined.	character	16
Job_wks_name	The name of the workstation of the job on which the successor is defined.	string	16
Job_id	The identifier of the job on which the successor is defined.	character	16
Job_stream_succ_id	The identifier of the job stream that follows the job specified in the <b>Job_id</b> column.	character	16
Job_succ_id	The identifier of the job that follows the job specified in the <b>Job_id</b> column.	character	16
Job_succ_js_wks_id	The identifier of the workstation of the job's job stream that follows the job specified in the <b>Job_id</b> column.	character	16

Table 32. The PLAN\_JOBS\_SUCCESSORS\_V view (continued)

Column name	Description	Type	Length
Job_succ_js_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream that follows the job specified in the <b>Job_id</b> column.	string	16
Job_succ_js_wks_original_name	The name of the workstation of the job's job stream that follows the job specified in the <b>Job_id</b> column.	string	16
Job_succ_js_wks_folder_name	The name of the folder containing the workstation of the job's job stream that follows the job specified in the <b>Job_id</b> column.	string	801
Job_succ_js_wks_folder_id	The identifier of the folder containing the workstation of the job's job stream that follows the job specified in the <b>Job_id</b> column.	character	16
Job_succ_js_name	The name of the job's job stream that follows the job specified in the <b>Job_id</b> column.	string	16
Job_succ_js_sched_time	The input arrival time of the job's job stream that follows the job specified in the <b>Job_id</b> column.	timestamp	10
Job_succ_wks_id	The identifier of the workstation of the job that follows the job specified in the <b>Job_id</b> column.	character	16
Job_succ_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job that follows the job specified in the <b>Job_id</b> column.	string	16
Job_succ_wks_original_name	The name of the workstation of the job that follows the job specified in the <b>Job_id</b> column.	string	16
Job_succ_wks_folder_name	The name of the folder containing the workstation of the job that follows the job specified in the <b>Job_id</b> column.	string	801

**Table 32. The PLAN\_JOBS\_SUCCESSORS\_V view (continued)**

Column name	Description	Type	Length
Job_succ_wks_folder_id	The identifier of the folder containing the workstation of the job that follows the job specified in the <b>Job_id</b> column.	character	16
Job_succ_name	The name of the job that follows the job specified in the <b>Job_id</b> column.	string	40
Job_stream_succ_wks_name	The name of the workstation of the job stream that follows the job specified in the <b>Job_id</b> column.	string	16
Job_stream_succ_wks_orig_name	The original name of the workstation of the job stream that follows the job specified in the <b>Job_id</b> column.	string	16
Job_stream_succ_wks_folder_name	The name of the folder containing the workstation of the job stream that follows the job specified in the <b>Job_id</b> column.	string	801
Job_stream_succ_wks_folder_id	The identifier of the folder containing the workstation of the job stream that follows the job specified in the <b>Job_id</b> column.	character	16
Job_stream_succ_folder_id	The identifier of the folder containing the job stream that follows the job specified in the <b>Job_id</b> column.	character	16
Job_stream_succ_folder_name	The name of the folder containing the job stream that follows the job specified in the <b>Job_id</b> column.	string	801
Job_stream_succ_name	The name of the job stream that follows the job specified in the <b>Job_id</b> column.	string	16
Job_stream_succ_sched_time	The input arrival time of the workstation of the job stream that follows the job specified in the <b>Job_id</b> column.	timestamp	10
Satisfied	If the job's dependency is satisfied. Possible values are:  <b>Y</b>  Yes	character	1

**Table 32. The PLAN\_JOBS\_SUCCESSORS\_V view (continued)**

Column name	Description	Type	Length
Status	<b>N</b>		
	No		
	The job's dependency status. Possible values are:	character	1
	<b>S</b>		
	Satisfied		
	<b>N</b>		
Not_satisfied			
<b>U</b>			
Undecided			

## PLAN\_JOB\_STREAMS\_V

The PLAN\_JOB\_STREAMS\_V view displays information about job streams in the plan.

**Table 33. The PLAN\_JOB\_STREAMS\_V view**

Column name	Description	Type	Length
Job_stream_id	The job stream identifier.	character	16
Workstation_id	The identifier of the workstation of the job stream specified in the <b>Job_stream_id</b> column.	character	16
Workstation_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job stream specified in the <b>Job_stream_id</b> column.	string	16
Workstation_original_name	The name of the workstation.	string	16
Workstation_folder_name	The name of the folder where the workstation is defined.	string	801
Workstation_folder_id	The identifier of the folder where the workstation is defined.	character	16

Table 33. The PLAN\_JOB\_STREAMS\_V view (continued)

Column name	Description	Type	Length
Job_stream_folder_id	The identifier of the folder containing the job stream specified in the <b>Job_stream_id</b> column.	character	16
Job_stream_folder_name	The name of the folder containing the job stream specified in the <b>Job_stream_id</b> column.	string	801
Job_stream_name	The name of the job stream specified in the <b>Job_stream_id</b> column.	string	16
Scheduled_time	The input arrival time of the job stream specified in the <b>Job_stream_id</b> column.	timestamp	10
Internal_identifier	The unique alphanumeric job stream identifier that is automatically generated by IBM Workload Scheduler and assigned to the job stream.	character	16
Actual_start	The time at which the job stream specified in the <b>Job_stream_id</b> column actually started, if it has completed running.	timestamp	10
Deadline	The time within which the job stream specified in the <b>Job_stream_id</b> column must complete.	timestamp	10
Earliest_start	The date and time at which the job stream specified in the <b>Job_stream_id</b> column is planned to start.	timestamp	10
Latest_start	The latest time at which the job stream specified in the <b>Job_stream_id</b> column must be completed.	timestamp	10
Estimated_duration	The expected duration time of the job stream specified in the <b>Job_stream_id</b> column.	integer	12
Jobs_limit	The number of jobs in the job stream specified in the <b>Job_stream_id</b> column that can run concurrently.	integer	4
Status	The job stream status. Possible values are:  <b>C</b>  Canceled	character	1

Table 33. The PLAN\_JOB\_STREAMS\_V view (continued)

Column name	Description	Type	Length
	<b>H</b> Held		
	<b>W</b> Waiting		
	<b>B</b> Blocked		
	<b>R</b> Ready		
	<b>S</b> Running		
	<b>O</b> Successful		
	<b>E</b> Error		
	<b>U</b> Undecided		
	<b>X</b> Suppressed		
Internal_status	The job stream internal status. Possible values are:	character	1
	<b>A</b> Ready		
	<b>B</b> Hold		
	<b>C</b> Exec		
	<b>D</b> Exec_bm		
	<b>E</b> Stuck		

Table 33. The PLAN\_JOB\_STREAMS\_V view (continued)

Column name	Description	Type	Length
<b>F</b>	Abend		
<b>G</b>	Succ		
<b>H</b>	Cancel		
<b>I</b>	Unknown		
<b>J</b>	User_stream		
<b>K</b>	Cancel_p		
<b>L</b>	Add		
<b>M</b>	Restart_job		
<b>N</b>	Fail		
<b>O</b>	Mpe_susp		
<b>P</b>	Mpe_wait		
<b>Q</b>	Mpe_intro		
<b>R</b>	Mpe_intro_bm		
<b>S</b>	Mpe_waitd		
<b>T</b>	Mpe_sched		

Table 33. The PLAN\_JOB\_STREAMS\_V view (continued)

Column name	Description	Type	Length
	<b>U</b> Abend_p		
	<b>V</b> Succ_p		
	<b>W</b> End_p		
	<b>X</b> Extrn		
	<b>Y</b> Error		
	<b>Z</b> Held		
	<b>1</b> Jss		
	<b>2</b> Fence		
	<b>3</b> Bound		
Late	If the job stream is late. Possible values are:	character	1
	<b>Y</b> Yes		
	<b>N</b> No		
Monitored	If the job stream is monitored. Possible values are:	character	1
	<b>Y</b> Yes		
	<b>N</b> No		

**Table 33. The PLAN\_JOB\_STREAMS\_V view (continued)**

Column name	Description	Type	Length
Original_job_stream	The original name of the job stream, for job streams that are submitted with an alias name.	string	16
Record_number	The record number.	integer	12
Elapsed_time	The amount of time that the job stream took to run, for this run.	integer	12
Priority	The priority assigned to the job stream specified in the <b>Job_stream_id</b> column.	integer	3
Original_priority	The original priority assigned to the job stream specified in the <b>Job_stream_id</b> column.	integer	3
Total_jobs	The number of total jobs in the job stream specified in the <b>Job_stream_id</b> column.	integer	10
Abend_jobs	The number of abended jobs in the job stream specified in the <b>Job_stream_id</b> column.	integer	10
Executing_jobs	The number of executing jobs in the job stream specified in the <b>Job_stream_id</b> column.	integer	10
Failed_jobs	The number of failed jobs in the job stream specified in the <b>Job_stream_id</b> column.	integer	10
Successful_jobs	The number of successful jobs in the job stream specified in the <b>Job_stream_id</b> column.	integer	10
Not_running_jobs	The number of not running jobs in the job stream specified in the <b>Job_stream_id</b> column.	integer	10
Undecided_jobs	The number of undecided jobs in the job stream specified <b>Job_stream_id</b> column.	integer	10
Total_dependencies	The number of dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5
Job_dependencies	The number of job dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5

**Table 33. The PLAN\_JOB\_STREAMS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_dependencies	The number of job stream dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5
Internetwork_dependencies	The number of internetwork dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5
Prompt_dependencies	The number of prompt dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5
Resource_dependencies	The number of resource dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5
File_dependencies	The number of file dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5
Unresolved_dependencies	The number of unresolved dependencies of the job stream specified in the <b>Job_stream_id</b> column.	integer	5
Timezone	Time zone of the job stream specified in the <b>Job_stream_id</b> column.	string	40

## PLAN\_JOBS\_V

The PLAN\_JOBS\_V view displays information about jobs in plan.

**Table 34. The PLAN\_JOBS\_V view**

Column name	Description	Type	Length
Job_id	The job identifier.	character	16
Job_workstation_id	The identifier of the workstation of the job specified in the <b>Job_id</b> column.	character	16
Job_workstation_folder_id	The identifier of the folder containing the workstation of the job specified in the <b>Job_id</b> column.	character	16
Job_workstation_folder_name	The name of the folder containing the workstation of the job specified in the <b>Job_id</b> column.	string	801

**Table 34. The PLAN\_JOBS\_V view (continued)**

Column name	Description	Type	Length
Job_workstation_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job specified in the <b>Job_id</b> column.	string	16
Job_workstation_original_name	The identifier of the workstation of the job specified in the <b>Job_id</b> column.	string	16
Job_name	The name of the job specified in the <b>Job_id</b> column.	string	40
Job_stream_workstation_id	The identifier of the workstation of the job's job stream specified in the <b>Job_id</b> column.	character	16
Job_stream_id	The identifier of the job stream of the job specified in the <b>Job_id</b> column.	character	16
Job_stream_wks_fol_id	The identifier of the folder containing the workstation of the job's job stream specified in the <b>Job_id</b> column.	character	16
Job_stream_wks_fol_name	The name of the folder containing the workstation of the job's job stream specified in the <b>Job_id</b> column.	string	801
Job_stream_workstation_name	The name of the workstation of the job's job stream specified in the <b>Job_id</b> column.	string	16
Job_stream_wks_orig_name	The identifier of the original workstation of the job's job stream specified in the <b>Job_id</b> column.	string	16
Job_stream_name	The name of the job's job stream specified in the <b>Job_id</b> column.	string	16
Scheduled_time	The input arrival time of the job's job stream specified in the <b>Job_id</b> column.	timestamp	10
Job_type	The type of job specified in the <b>Job_id</b> column.	string	50
Actual_start	The time at which the job specified in the <b>Job_id</b> column actually started, if it has completed running.	timestamp	10
Actual_end	The time at which the job specified in the <b>Job_id</b> column actually finished, if it has completed running.	timestamp	10
Deadline	The time within which the job specified in the <b>Job_id</b> column must complete.	timestamp	10
Earliest_start	The date and time at which the job specified in the <b>Job_id</b> column is planned to start.	timestamp	10
Estimated_duration	The estimated run time for the job specified in the <b>Job_id</b> column.	integer	12
Status	The job status. Possible values are:	character	1

Table 34. The PLAN\_JOBS\_V view (continued)

Column name	Description	Type	Length
	<b>C</b> Canceled		
	<b>H</b> Held		
	<b>W</b> Waiting		
	<b>B</b> Blocked		
	<b>R</b> Ready		
	<b>S</b> Running		
	<b>O</b> Successful		
	<b>E</b> Error		
	<b>U</b> Undecided		
	<b>X</b> Suppressed		
Internal_status	The job internal status. Possible values are:	character	1
	<b>A</b> Ready		
	<b>B</b> Hold		
	<b>C</b> Exec		
	<b>D</b> Exec_bm		

**Table 34. The PLAN\_JOBS\_V view (continued)**

Column name	Description	Type	Length
<b>E</b>	Stuck		
<b>F</b>	Abend		
<b>G</b>	Succ		
<b>H</b>	Cancel		
<b>I</b>	Unknown		
<b>J</b>	User_stream		
<b>K</b>	Cancel_p		
<b>L</b>	Add		
<b>M</b>	Restart_job		
<b>N</b>	Fail		
<b>O</b>	Mpe_susp		
<b>P</b>	Mpe_wait		
<b>Q</b>	Mpe_intro		
<b>R</b>	Mpe_intro_bm		
<b>S</b>	Mpe_waitd		

Table 34. The PLAN\_JOBS\_V view (continued)

Column name	Description	Type	Length
	<b>T</b> Mpe_sched		
	<b>U</b> Abend_p		
	<b>V</b> Succ_p		
	<b>W</b> End_p		
	<b>X</b> Extrn		
	<b>Y</b> Error		
	<b>Z</b> Held		
	<b>1</b> Jss		
	<b>2</b> Fence		
	<b>3</b> Bound		
Job_number	For UNIX, the process identification number (PID) of the job. For Windows, the an incremental number assigned by IBM Workload Scheduler.	integer	10
Priority	The priority assigned to the job specified in the <b>Job_id</b> column.	integer	3
Original_priority	The original priority assigned to the job specified in the <b>Job_id</b> column.	integer	3
Return_code	The return code assigned to the job specified in the <b>Job_id</b> column.	integer	10
Record_number	The record number.	integer	12
Maximum_duration	The maximum amount of time that the job run can last.	integer	12
Minimum_duration	The minimum amount of time that the job run must last.	integer	12

Table 34. The PLAN\_JOBS\_V view (continued)

Column name	Description	Type	Length
Critical	If the job is critical. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Critical_latest_start	The latest time that the specified in the <b>Job_id</b> column can start, so as to allow the critical job (for which this job is a predecessor) to complete successfully.	timestamp	10
Monitored	If the job is monitored. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Promoted	If the job is promoted. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Every_frequency	The time interval in hours and minutes between runs of the job specified in the <b>Job_id</b> column.	integer	12
Latest_start	The latest time that the job specified in the <b>Job_id</b> column can start, expressed in the time zone set.	timestamp	10
Interactive	If the job is interactive. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Return_code_mapping	The mapping between the job return code and the expression.	string	256
Task_string	The task that the job performs.	string	1048 576

Table 34. The PLAN\_JOBS\_V view (continued)

Column name	Description	Type	Length
Total_dependencies	The total number of dependencies that depend on the job specified in the <b>Job_id</b> column.	integer	5
Job_dependencies	The number of jobs that depend on the job specified in the <b>Job_id</b> column.	integer	5
Job_stream_dependencies	The number of job streams that depend on the job specified in the <b>Job_id</b> column.	integer	5
Internetwork_dependencies	The number of internetwork jobs that depend on the job specified in the <b>Job_id</b> column.	integer	5
Prompt_dependencies	The number of prompts that depend on the job specified in the <b>Job_id</b> column.	integer	5
Resource_dependencies	The number of resources that depend on the job specified in the <b>Job_id</b> column.	integer	5
File_dependencies	The number of files that depend on the job specified in the <b>Job_id</b> column.	integer	5
Not_satisfied_dependencies	The number of dependencies that depend on the job specified in the <b>Job_id</b> column but that are not satisfied.	integer	5
Login	The name of the operating system user who launches the job specified in the <b>Job_id</b> column.	string	47
Last_in_chain	If the job is the last in the rerun chain. Possible values are: <b>Y</b> Yes <b>N</b> No	character	1
Rerun_type	The job rerun type. Possible values are: <b>R</b> Rerun as <b>E</b> Rerun every <b>F</b> Rerun from	character	1

Table 34. The PLAN\_JOBS\_V view (continued)

Column name	Description	Type	Length
	<b>C</b> Recovery rerun		
Recovery_option	The job recovery option. Possible values are:	character	1
	<b>S</b> Stop		
	<b>C</b> Continue		
	<b>R</b> Rerun		
Recovery_repeat_interval	The interval in milliseconds after which a new execution of the job is launched if the job failed	integer	12
Recovery_repeat_occurrences	The number of maximum attempts to rerun the job if it failed	integer	5
Recovery_repeat_affinity	Specify whether the failed job must be rerun on the same workstation or the target workstation must be selected by the broker. Supported values are:	character	1
	<b>Y</b> Yes: rerun on the same workstation.		
	<b>N</b> No: the target workstation must be selected by the broker.		
Recovery_repeat_iterations	The actual number of attempts to rerun the failed job	integer	5
Recovery_job_id	The identifier of the recovery job.	character	16
Head_job_id	The identifier of the head job of the rerun chain related to the job specified in the <b>Job_id</b> column.	character	16
Head_job_name	The name of the head job of the rerun chain related to the job specified in the <b>Job_id</b> column.	string	40

## PLAN\_PROMPT\_REFS\_V

The PLAN\_PROMPT\_REFS\_V view displays information about jobs and job streams in the plan that depend on a prompt.

Table 35. The PLAN\_PROMPT\_REFS\_V view

Column name	Description	Type	Length
Prompt	The name of the prompt on which the dependency is defined.	string	148
Prompt_number	The number of the prompt specified in the <b>Prompt_id</b> column.	integer	10
Message_text	The text message of the prompt specified in the <b>Prompt_id</b> column.	string	200
Prompt_id	The identifier of the prompt on which the dependency is defined.	character	16
Job_stream_refs_id	The identifier of the job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Job_refs_id	The identifier of the job that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Job_refs_js_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	16
Job_refs_js_wks_original_name	The name of the workstation of the job's job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	16
Jobs_refs_js_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job's job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Jobs_refs_js_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job's job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	801
Job_refs_js_id	The identifier of the job's job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Job_refs_js_name	The name of the job's job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	16
Job_refs_js_sched_time	The input arrival time of the job's job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	timestamp	10
Job_refs_wks_id	The identifier of the workstation of the job that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Job_refs_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the of the job that depends on the prompt specified in the <b>Prompt_id</b> column.	string	16
Job_refs_wks_original_name	The name of the workstation of the job that depends on the prompt specified in the <b>Prompt_id</b> column.	string	16

**Table 35. The PLAN\_PROMPT\_REFS\_V view (continued)**

Column name	Description	Type	Length
Jobs_refs_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Jobs_refs_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job that depends on the prompt specified in the <b>Prompt_id</b> column.	string	801
Job_stream_refs_folder_name	The name of the folder in which the job stream is defined. The job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	801
Job_stream_refs_folder_id	The identifier of the folder in which the job stream is defined. The job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Job_refs_name	The name of the job that depends on the prompt specified in the <b>Prompt_id</b> column.	string	40
Job_stream_refs_wks_id	The identifier of the workstation of the job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Job_stream_refs_wks_name	A hexiadecimal identifier used in the Symphony file to identify the workstation of the of the job stream that depends on the prompt specified in the <b>Prompt_id</b> .	string	16
Job_stream_wks_original_name	The name of the workstation of the job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	16
Job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	character	16
Job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	801
Job_stream_refs_name	The name of the job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	string	16
Job_stream_refs_sched_time	The input arrival time of the job stream that depends on the prompt specified in the <b>Prompt_id</b> column.	timestamp	10
Satisfied	If the prompt dependency is satisfied. Possible values are:  <b>Y</b>  Yes	character	1

**Table 35. The PLAN\_PROMPT\_REFS\_V view (continued)**

Column name	Description	Type	Length
Prompt_type	<b>N</b> No	character	1
	The prompt type. Possible values are:		
	<b>L</b> Ad-hoc		
	<b>G</b> Predefined		
Status	<b>R</b> Restart	character	1
	The prompt status. Possible values are:		
	<b>A</b> Asked		
	<b>T</b> Not_asked		
	<b>Y</b> Answered_yes		
	<b>N</b> Answered_no		

## PLAN\_PROMPTS\_V

The PLAN\_PROMPTS\_V view displays information about prompts in the plan.

**Table 36. The PLAN\_PROMPTS\_V view**

Column name	Description	Type	Length
Prompt_id	The identifier of the prompt.	character	16
Prompt_name	The name of the prompt.	string	148
Prompt_number	The number of the prompt.	integer	10
Workstation_id	The workstation identifier.	character	16
Workstation_name	A hexadecimal identifier used in the Symphony file to identify the workstation.	string	16

**Table 36. The PLAN\_PROMPTS\_V view (continued)**

Column name	Description	Type	Length
Workstation_original_name	The workstation name.	string	16
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Asked_time	The time on which the prompt is asked.	timestamp	10
Status	The prompt status. Possible values are:  <b>A</b> Available  <b>N</b> Not_available  <b>U</b> Undecided	character	1
Message_text	Text of the message.	string	200
Prompt_type	The prompt type. Possible values are:  <b>L</b> Local  <b>G</b> Global  <b>R</b> Restart	character	1

## PLAN\_RESOURCE\_REFS\_V

The PLAN\_RESOURCE\_REFS\_V view displays information about jobs and job streams in the plan that depend on a resource.

**Table 37. The PLAN\_RESOURCE\_REFS\_V view**

Column name	Description	Type	Length
Resource_name	The name of the resource on which the dependency is defined.	string	148
Quantity_defined	The total quantity defined on the resource specified in the <b>Resource_id</b> column.	integer	4
Quantity_available	The quantity of the resource specified in the <b>Resource_id</b> column that is not used.	integer	4

Table 37. The PLAN\_RESOURCE\_REFS\_V view (continued)

Column name	Description	Type	Length
In_use	The quantity in use on the resource specified in the <b>Resource_id</b> column.	integer	4
Resource_wks_id	The identifier of the workstation on which the resource specified in the <b>Resource_id</b> column is defined.	character	16
Resource_wks_name	A hexiadecimal identifier used in the Symphony file to identify the workstation	string	16
Resource_wks_original_name	The name of the workstation on which the resource specified in the <b>Resource_id</b> column is defined.	string	16
Resource_wks_folder_id	The identifier of the folder containing the workstation on which the resource specified in the <b>Resource_id</b> column is defined.	character	16
Resource_wks_folder_name	The name of the folder containing the workstation on which the resource specified in the <b>Resource_id</b> column is defined. .	string	801
Resource_id	The identifier of the resource on which the dependency is defined.	character	16
Job_stream_refs_id	The identifier of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Job_refs_id	The identifier of the job that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Job_refs_js_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Job_refs_js_wks_original_name	The name of the workstation of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Jobs_refs_js_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Jobs_refs_js_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	801
Job_refs_js_id	The identifier of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Job_refs_js_name	The name of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16

**Table 37. The PLAN\_RESOURCE\_REFS\_V view (continued)**

Column name	Description	Type	Length
Job_refs_js_sched_time	The input arrival time of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	timestamp	10
Job_refs_wks_id	The identifier of the workstation of the job that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Job_refs_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the of the job that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Job_refs_wks_original_name	The name of the workstation of the job that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Jobs_refs_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Jobs_refs_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job that depends on the resource specified in the <b>Resource_id</b> column.	string	801
Job_refs_name	The name of the job that depends on the resource specified in the <b>Resource_id</b> column.	string	40
Job_stream_refs_wks_id	The identifier of the workstation of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Job_stream_refs_wks_name	A hexadecimal identifier used in the Symphony file to identify the workstation of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Job_stream_wks_original_name	The name of the workstation of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Job_stream_wks_folder_id	The identifier of the folder in which the workstation of the job stream is defined. The job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Job_stream_wks_folder_name	The name of the folder in which the workstation of the job stream is defined. The job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	801
Job_stream_refs_name	The name of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Job_stream_refs_folder_id	The identifier of the folder containing the job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16

**Table 37. The PLAN\_RESOURCE\_REFS\_V view (continued)**

Column name	Description	Type	Length
Job_stream_refs_folder_name	The name of the folder containing the job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	801
Job_stream_refs_sched_time	The input arrival time of the workstation of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	timestamp	10
Satisfied	If the resource dependency is satisfied. Possible values are:  <b>Y</b> Yes  <b>N</b> No	character	1
Status	The resource status. Possible values are:  <b>A</b> Available  <b>N</b> Not_available  <b>N</b> Undecided	character	1

## PLAN\_RESOURCES\_V

The PLAN\_RESOURCES\_V view displays information about resources in the plan.

**Table 38. The PLAN\_RESOURCES\_V view**

Column name	Description	Type	Length
Resource_id	The identifier of the resource.	character	16
Resource_name	The name of the resource.	string	148
Resource_number	The number of the resource.	integer	10
Workstation_id	The identifier of the workstation.	character	16
Workstation_name	A hexadecimal identifier used in the Symphony file to identify the workstation.	string	16
Workstation_original_name	The workstation name.	string	16
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16

**Table 38. The PLAN\_RESOURCES\_V view (continued)**

Column name	Description	Type	Length
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Status	The resource status. Possible values are:  <b>A</b> Available  <b>N</b> Not_available  <b>U</b> Undecided	character	1
Available	The number of units available for the resource specified in the <b>Resource_id</b> column.	integer	4
Not_used	The number of units for the resource specified in the <b>Resource_id</b> column that are not used.	integer	4
In_use	The number of units in use for the resource specified in the <b>Resource_id</b> column.	integer	4

## PLAN\_WORKSTATIONS\_V

The PLAN\_WORKSTATIONS\_V view displays information about workstations in the plan.

**Table 39. The PLAN\_WORKSTATIONS\_V view**

Column name	Description	Type	Length
Workstation_id	The identifier of the workstation.	character	16
Domain_id	The identifier of the domain of the workstation specified in the <b>Workstation_id</b> column.	character	16
Host_workstation_id	The identifier of the workstation that hosts the workstation specified in the <b>Workstation_id</b> column.	character	16
Method	The name of the access method for extended agents workstations.	string	40
Workstation_type	The workstation type status. Possible values are:  <b>M</b> Manager	character	1

Table 39. The PLAN\_WORKSTATIONS\_V view (continued)

Column name	Description	Type	Length
	<b>F</b> FTA		
	<b>X</b> XA		
	<b>S</b> SA		
	<b>B</b> Broker		
	<b>A</b> Agent		
	<b>L</b> Pool		
	<b>Y</b> Dynamic_pool		
	<b>E</b> Remote_engine		
Behind_firewall	If the workstation is behind the firewall. Possible values are:	character	1
	<b>Y</b> Yes		
	<b>N</b> No		
Fence	The job fence for the workstation specified in the <b>Workstation_id</b> column.	integer	3
Agent_initialized	If the jobman process is initialized. Possible values are:	character	1
	<b>Y</b> Yes		
	<b>N</b> No		
Agent_running	If the jobman process is running. Possible values are:	character	1

Table 39. The PLAN\_WORKSTATIONS\_V view (continued)

Column name	Description	Type	Length
	<b>Y</b> Yes		
	<b>N</b> No		
Limit	The total number of jobs that can be run concurrently on the workstation specified in the <b>Workstation_id</b> column.	integer	4
Link_status	The workstation link status. Possible values are:	character	1
	<b>L</b> Linked		
	<b>U</b> Unlinked		
	<b>F</b> Fully_linked		
	<b>N</b> Not_applicable		
Workstation_name	A hexadecimal identifier used in the Symphony file to identify the workstation.	string	16
Workstation_original_name	The name of the workstation	string	16
Node_name	The node name of the workstation.	string	51
Ssl_communication	The workstation SSL communication level. Possible values are:	character	1
	<b>O</b> On		
	<b>N</b> None		
	<b>E</b> Enabled		
	<b>F</b> Force		
	<b>H</b> Http		

Table 39. The PLAN\_WORKSTATIONS\_V view (continued)

Column name	Description	Type	Length
	<b>S</b>		
	Https		
Mailman_server	The name of the mailman server responsible for the <b>Workstation_id</b> on the domain manager. It is for fault-tolerant and standard agents only.	character	1
Ssl_port	The number of the secure port to be used for SSL communication.	integer	5
Monitor_config_updated	If the monitor configuration is updated. Possible values are:	character	1
	<b>Y</b>		
	Yes		
	<b>N</b>		
	No		
Start_time	The date and time when the <code>batchman</code> process was started on the workstation.	timestamp	10
Run_number	The run number of the current plan running on the workstation. This is used to synchronize the workstations in a IBM Workload Scheduler network.	integer	10
Node_port	The port number of the workstation.	integer	5
Time_zone	The time zone set on the workstation.	string	40
Node_information	The operating system information of the workstation.	string	64
Version	The IBM Workload Scheduler version that runs on the workstation.	string	8
Writer_running	If the writer is running. Possible values are:	character	1
	<b>Y</b>		
	Yes		
	<b>N</b>		
	No		
Event_processor	If the event processor is running. Possible values are:	character	1
	<b>Y</b>		
	Yes		
	<b>N</b>		
	No		
Event_monitoring	If the event monitoring is running. Possible values are:	character	1

**Table 39. The PLAN\_WORKSTATIONS\_V view (continued)**

Column name	Description	Type	Length
	Y Yes		
	N No		
Workstation_folder_name	The name of the folder where the workstation is defined.	string	801
Workstation_folder_id	The identifier of the folder where the workstation is defined.	character	16

## PROMPTS\_V

The PROMPTS\_V view displays information about prompts.

**Table 40. The PROMPTS\_V view**

Column name	Description	Type	Length
Prompt_identifier	The identifier of the prompt.	character	16
Prompt_name	The name of the prompt.	string	148
Prompt_fo_id	The identifier of the folder where the prompt is stored.	character	16
Prompt_fol_name	The name of the folder where the prompt is stored.	string	801
Prompt_Symphony_id	The Symphony ID of the folder where the prompt is stored.	string	16
Prompt_value	The text associated with the prompt.	string	200

## Output example

[Table 41: PROMPTS\\_V view output example on page 106](#) shows an example of the output for the PROMPTS\_V view.

**Table 41. PROMPTS\_V view output example**

```
PROMPT_NAME      PROMPT_VALUE
-----
JOBSTATCOMP      Reply y when statistics complete
JOBSALCOMP       Reply y when salary has been calculated
PROMPTSTAT       Reply y when statistics completed successfully

3 record(s) selected.
```

## PROMPT\_REFS\_V

The PROMPT\_REFS\_V view displays information about jobs and job streams that depend on a prompt.

Table 42. The PROMPT\_REFS\_V view

Column name	Description	Type	Length
Prompt_identifier	The identifier of the prompt on which the jobs and job streams depend.	character	16
Prompt_name	The name of the prompt on which the jobs and job streams depend.	string	148
Prompt_fol_id	The identifier of the folder where the prompt is stored.	character	16
Prompt_fol_name	The name of the folder where the prompt is stored.	string	801
Prompt_Symphony_id	The Symphony ID of the folder where the prompt is stored.	string	16
Prompt_text	The text associated with the prompt.	string	200
Dep_job_stream_wks_identifier	The identifier of the workstation where the job stream that depends on the prompt specified in the <b>Prompt_identifier</b> column is defined.	character	16
Dep_job_stream_wks_name	The name of the workstation where the job stream that depends on the prompt specified in the <b>Prompt_name</b> column is defined.	string	16
Dep_job_stream_folder_id	The identifier of the folder containing the job stream that depends on the prompt specified in the <b>Prompt_identifier</b> column.	character	16
Dep_job_stream_folder_name	The name of the folder containing job stream that depends on the prompt specified in the <b>Prompt_identifier</b> column.	string	801
Dep_job_stream_identifier	The identifier of the job stream that depends on the prompt specified in the <b>Prompt_identifier</b> column.	string	16
Dep_job_stream_name	The name of the job stream that depends on the prompt specified in the <b>Prompt_name</b> column.	string	16
Dep_job_stream_valid_from	The starting date from which the dependent job stream is included in a production plan if selected by a run cycle.	date	10 In D B2® 9 In Or

**Table 42. The PROMPT\_REFS\_V view (continued)**

Column name	Description	Type	Length
			a cle
Dep_job_stream_valid_to	The last date that the dependent job stream is included in a production plan if selected by a run cycle.	date	10
			In D B2®
			9
			In Or a cle
Dep_job_wks_identifier	The identifier of the workstation where the job that depends on the prompt specified in the <b>Prompt_identifier</b> column is defined.	character	16
Dep_job_wks_name	The name of the workstation where the job that depends on the prompt specified in the <b>Prompt_name</b> column is defined.	string	16
Dep_job_name	The name of the job that depends on the prompt specified in the <b>Prompt_name</b> column.	string	40
Dep_job_identifier	The identifier of the job that depends on the prompt specified in the <b>Prompt_identifier</b> column.	character	16
Dep_job_folder_id	The identifier of the folder containing the job that depends on the prompt specified in the <b>Prompt_identifier</b> column.	character	16
Dep_job_folder_name	The name of the folder containing job that depends on the prompt specified in the <b>Prompt_identifier</b> column.	string	801
Dep_job_definition_identifier	The identifier of the job definition that depends on the prompt specified in the <b>Prompt_identifier</b> column.	character	16
Dep_job_definition_name	The name of the job definition that depends on the prompt specified in the <b>Prompt_name</b> column.	string	40
Dep_job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the prompt specified in the <b>Prompt_name</b> column.	character	16

**Table 42. The PROMPT\_REFS\_V view (continued)**

Column name	Description	Type	Length
Dep_job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream that depends on the prompt specified in the <b>Prompt_name</b> column.	string	801
Dep_job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream that depends on the prompt specified in the <b>Prompt_name</b> column.	string	16
Dep_job_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job that depends on the prompt specified in the <b>Prompt_name</b> column.	character	16
Dep_job_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job that depends on the prompt specified in the <b>Prompt_name</b> column.	string	801
Dep_job_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job that depends on the prompt specified in the <b>Prompt_name</b> column.	string	16

## PROPERTIES\_V

The PROPERTIES\_V view displays information about global options and properties.

**Table 43. The PROPERTIES\_V view**

Column name	Description	Type	Length
Property_name	The name of the property.	string	50
Property_value	The value of the property.	string	256

## REMOTE\_JOB\_REQUESTS\_V

This view shows the details of the request to bind to a job on a remote engine. The bind request is sent to the remote engine where the job instance resides. Every bind request contains the information to identify the job's instance in the remote engine plan.

**Table 44. The REMOTE\_JOB\_REQUESTS\_V view**

Column name	Description	Type	Length
Remote_job_identifier	The identifier of the shadow job in the remote engine.	varchar	1000
Remote_job_start_time	The time used to identify the remote job instance in the local plan.	timestamp	10

**Table 44. The REMOTE\_JOB\_REQUESTS\_V view (continued)**

Column name	Description	Type	Length
Interval_start_offset	The relative or absolute offset to define the start of the interval where to look for remote predecessor job instance in the local plan. This column is filled in when a <i>relative</i> or <i>absolute</i> interval based matching criteria is specified in the shadow job definition.	decimal	10
Interval_end_offset	The relative or absolute offset to define the end of the interval where to look for remote predecessor job instance in the local plan. This column is filled in when a <i>relative</i> or <i>absolute</i> interval based matching criteria is specified in the shadow job definition.	decimal	10
Local_workstation_name	The name of the job stream workstation to match in the local plan. It is referenced in the shadow job definition on the remote engine.	varchar	1000
Local_job_stream_name	The name of the job stream to match in the local engine plan. It is referenced in the shadow job definition on the remote engine.	varchar	1000
Local_job_name	The name of the job to match in the local plan. It is referenced in the shadow job definition on the remote engine.	varchar	1000
Local_job_start_time	The time of the job stream instance matched in the local plan.	timestamp	10
Matching_criteria	The matching criteria used to find the required job stream instance to match in the local plan. These are the possible values for this field:  <b>B</b> Closest preceding  <b>D</b> On the same day  <b>A</b> Within an absolute interval  <b>R</b> Within a relative interval	character	1
Request_status	The result of the bind request. The request status says whether an existing job instance in the local engine plan matched or not the remote job information specified in the shadow job definition. These are the possible values for this field:  <b>0</b> The subscription has been received.	decimal	2

**Table 44. The REMOTE\_JOB\_REQUESTS\_V view (continued)**

Column name	Description	Type	Length
	<b>1</b>		
	The subscription is waiting for the bind in the Long Term Plan (LTP).		
	<b>2</b>		
	The subscription has been bound in the Long Term Plan.		
	<b>3</b>		
	The subscription is waiting for the bind in the Current Plan (CP).		
	<b>4</b>		
	The subscription has been bound in the Current Plan.		
	<b>5</b>		
	The bind in Long Term Plan failed.		
	<b>6</b>		
	The bind in Current Plan failed.		
Notification_URI	The URI where to send back the notification about the remote job status. It is the URI identifying the remote engine where the shadow job is defined.	varchar	1024

## RESOURCES\_V

The RESOURCES\_V view displays information about resources.

**Table 45. The RESOURCES\_V view**

Column name	Description	Type	Length
Workstation_identifier	The identifier of the workstation or workstation class associated with the resource.	character	16
Workstation_name	The name of the workstation or workstation class associated with the resource.	string	16
Resource_name	The name of the resource.	string	148
Resource_fol_id	The identifier of the folder where the resource is stored.	character	16
Resource_fol_name	The name of the folder where the resource is stored.	string	801
Resource_Symphony_id	The Symphony ID of the folder where the resource is stored.	string	16

**Table 45. The RESOURCES\_V view (continued)**

Column name	Description	Type	Length
Resource_identifier	The identifier of the resource.	character	16
Resource_description	The description associated with the resource.	string	120
Resource_units	The number of this resource available.	integer	4
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Workstation_symphony_id	An identifier used in the Symphony file to identify the workstation.	string	16

## Output example

Table 46: RESOURCES\_V view output example on page 112 shows an example of the output for the RESOURCES\_V view.

**Table 46. RESOURCES\_V view output example**

WORKSTATION_NAME	RESOURCE_NAME	RESOURCE_DESCRIPTION	RESOURCE_UNITS	WORKSTATION_FOLDER_NAME
JA_DWH01	D01-0120	tape type 01	5.	/
JA_DWH01	D01-0168	tape type 02	6.	/
JA_DWH01	D01-0170	printer type 777	7.	/
JA_DWH01	D01-0202	printer type 11	7.	/
JA_DWH01	D01-0213	printer type 2	7.	/
JA_DWH01	D01-0217	tape type 01	2.	/
JA_DWH01	D01-0222	tape type 01	2.	/
JA_DWH01	D01-0303	tape type 01	7.	/
JA_DWH01	D01-0306	tape type 01	5.	/
JA_DWH01	D01-0310	printer type 777	5.	/
JA_DWH01	D01-0314	printer type 777	7.	/
JA_DWH01	D01-0363	printer type 777	5.	/
JA_DWH01	D01-0364	printer type 777	8.	/
JA_DWH01	D01-0365	printer type 777	5.	/
JA_DWH01	D01-0367	printer type 777	5.	/

15 record(s) selected.

## RESOURCE\_REFS\_V

The RESOURCE\_REFS\_V view displays information about jobs and job streams that depend on a resource.

**Table 47. The RESOURCE\_REFS\_V view**

Column name	Description	Type	Length
Workstation_identifier	The identifier of the workstation where the resource is defined.	character	16
Workstation_name	The name of the workstation where the resource is defined.	string	16

**Table 47. The RESOURCE\_REFS\_V view (continued)**

Column name	Description	Type	Length
Resource_identifier	The identifier of the resource on which the jobs and job streams depend.	character	16
Resource_name	The name of the resource on which the jobs and job streams depend.	string	148
Resource_fol_id	The identifier of the folder where the resource is stored.	character	16
Resource_fol_name	The name of the folder where the resource is stored.	string	801
Resource_Symphony_id	The Symphony ID of the folder where the resource is stored.	string	16
Units_available	The number of this resource available for allocation.	integer	4
Units_allocated	The number of this resource to be allocated to satisfy the dependency.	integer	4
Dep_job_stream_wks_identifier	The identifier of the workstation where the job stream that depends on the resource specified in the <b>Resource_identifier</b> column is defined.	character	16
Dep_job_stream_wks_name	The name of the workstation where the job stream that depends on the resource specified in the <b>Resource_name</b> column is defined.	string	16
Dep_job_stream_folder_id	The identifier of the folder containing the job stream that depends on the resource specified in the <b>Resource_name</b> column.	character	16
Dep_job_stream_folder_name	The name of the folder containing the job stream that depends on the resource specified in the <b>Resource_name</b> column	string	801
Dep_job_stream_identifier	The identifier of the job stream that depends on the resource specified in the <b>Resource_identifier</b> column.	character	16
Dep_job_stream_name	The name of the job stream that depends on the resource specified in the <b>Resource_name</b> column.	string	16
Dep_job_stream_valid_from	The starting date from which the dependent job stream is included in a production plan if selected by a run cycle.	date	<b>10</b> In DB2®

Table 47. The RESOURCE\_REFS\_V view (continued)

Column name	Description	Type	Length
			9
			In Oracle
Dep_job_stream_valid_to	The last date that the dependent job stream is included in a production plan if selected by a run cycle.	date	10
			In DB2®
			9
			In Oracle
Dep_job_wks_identifier	The identifier of the workstation where the job that depends on the prompt specified in the <b>Prompt_identifier</b> column is defined.	character	16
Dep_job_wks_name	The name of the workstation where the job that depends on the prompt specified in the <b>Prompt_name</b> column is defined.	string	16
Dep_job_folder_id	The identifier of the folder containing the job that depends on the resource specified in the <b>Resource_name</b> column.	character	16
Dep_job_folder_name	The name of the folder containing the job that depends on the resource specified in the <b>Resource_name</b> column	string	801
Dep_job_identifier	The identifier of the job that depends on the resource specified in the <b>Resource_identifier</b> column.	character	16
Dep_job_name	The name of the job that depends on the resource specified in the <b>Resource_name</b> column.	string	40
Dep_job_definition_identifier	The identifier of the job definition that depends on the resource specified in the <b>Resource_identifier</b> column.	character	16
Dep_job_definition_name	The name of the job definition that depends on the resource specified in the <b>Resource_name</b> column.	string	40
Job_refs_js_id	The identifier of the job's job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16

Table 47. The RESOURCE\_REFS\_V view (continued)

Column name	Description	Type	Length
Workstation_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job or job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Workstation_folder_name	The name of the folder in which the workstation of the job or job stream is defined. The job or job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	801
Workstation_symphony_id	An identifier used in the Symphony file to identify the workstation of the job or job stream. The job or job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Dep_job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Dep_job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	801
Dep_job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream that depends on the resource specified in the <b>Resource_id</b> column.	string	16
Dep_job_wks_folder_id	The identifier of the folder in which the workstation is defined. The workstation is of the job that depends on the resource specified in the <b>Resource_id</b> column.	character	16
Dep_job_wks_folder_name	The name of the folder in which the workstation is defined. The workstation is of the job that depends on the resource specified in the <b>Resource_id</b> column.	string	801
Dep_job_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job that depends on the resource specified in the <b>Resource_id</b> column.	string	16

## Output example

Table 48: RESOURCE\_REFS\_V view output example on page 116 shows an example of the output for the RESOURCE\_REFS\_V view.

Table 48. RESOURCE\_REFS\_V view output example

WORKSTATION_NAME	RESOURCE_NAME	UNITS_AVAILABLE	UNITS_ALLOCATED	DEP_JOB_STREAM_WKS_NAME	DEP_JOB_STREAM_NAME	DEP_JOB_STREAM_VALID_FROM
JA_BAT02	B02-0611	4.	1.	JA_BAT02	BD601C200N06110D	-
JA_BAT02	B02-0704	4.	1.	JA_BAT02	BD601C200N07040E	-
JA_BAT03	B03-0621	5.	1.	JA_BAT03	BD601C200N062102	-
JA_BAT03	B03-0711	5.	1.	JA_BAT03	BR172C200N071101	-
JA_BAT03	B03-0639	8.	1.	JA_BAT03	BM201F600N063901	-
JA_BAT05	B05-1206	5.	1.	JA_BAT05	BR230F700N120601	-
JA_BAT05	B05-5013	5.	1.	JA_BAT05	BR081M000N501301	-
JA_BAT05	B05-1368	4.	1.	JA_BAT05	BD601C200N136808	-
JA_BAT05	B05-1363	5.	1.	JA_BAT05	BM601D100N136304	-
JA_BAT04	B05-1156	5.	1.	JA_BAT04	BR062H100N085001	-
JA_BAT04	B04-0817	5.	1.	JA_BAT04	BY100F900N081701	-
JA_BAT04	B04-1176	4.	1.	JA_BAT04	BR184C200N117601	-
JA_BAT01	B01-0510	5.	1.	JA_BAT01	BD101C200N051001	-
JA_BAT01	B01-0614	4.	1.	JA_BAT01	BDEND-DMYN061409	-

15 record(s) selected.

DEP_JOB_STREAM_VALID_TO	DEP_JOB_WKS_NAME	DEP_JOB_FOLDER_NAME	DEP_JOB_NAME	DEP_JOB_DEFINITION_NAME
-	JA_BAT02	/PAYROLL/	BD611C200	BD611C200
-	JA_BAT02	/PAYROLL/	BD608C200	BD608C200
-	JA_BAT03	/LEAVE/	BD607C200	BD607C200
-	JA_BAT03	/LEAVE/	BR172C200	BR172C200
-	JA_BAT03	/LEAVE/	BM201F600	BM201F600
-	JA_BAT05	/BONUS/	BR223F700	BR223F700
-	JA_BAT05	/BONUS/	BR081M000	BR081M000
-	JA_BAT05	/BONUS/	BD691C200	BD691C200
-	JA_BAT05	/BONUS/	BM601D100	BM601D100
-	JA_BAT04	/HOLIDAY/	BR062H100	BR062H100
-	JA_BAT04	/HOLIDAY/	BY154F900	BY154F900
-	JA_BAT04	/HOLIDAY/	BR184C200	BR184C200
-	JA_BAT01	/BENEFIT/	BD122C200	BD122C200
-	JA_BAT01	/BENEFIT/	BDEND-DMY	BDEND-DMY

WORKSTATION_FOLDER_NAME	JOB_STREAM_WKS_FOLDER_NAME	DEP_JOB_WKS_FOLDER_NAME	DEP_JOB_STREAM_WKS_FOLDER_NAME
/PRD/FINANCIAL/	/	/FOLDER1/	/
/PRD/FINANCIAL/	/	/FOLDER1/	/
/PRD/FINANCIAL/	/	/FOLDER1/	/
/PRD/ATMS/	/	/FOLDER2/	/
/PRD/FINANCIAL/	/	/FOLDER2/	/
/PRD/ATMS/	/	/FOLDER2/	/
/PRD/FINANCIAL/	/	/FOLDER2/	/
/PRD/FINANCIAL/	/	/FOLDER2/	/
/PRD/ATMS/	/	/FOLDER1/	/
/PRD/ATMS/	/	/FOLDER3/	/
/PRD/ATMS/	/	/FOLDER3/	/
/PRD/FINANCIAL/	/	/FOLDER3/	/
/PRD/FINANCIAL/	/	/FOLDER1/	/
/PRD/FINANCIAL/	/	/FOLDER1/	/
/PRD/FINANCIAL/	/	/FOLDER1/	/

## RUN\_CYCLE\_REFS\_V

The RUN\_CYCLE\_REFS\_V view displays information about when job streams run.

**Table 49. The RUN\_CYCLE\_REFS\_V view**

Column name	Description	Type	Length
Job_stream_wks_identifier	The identifier of the workstation where the job stream is defined.	character	16
Job_stream_wks_name	The name of the workstation where the job stream is defined.	string	16
Job_stream_folder_id	The identifier of the folder that contains the job stream.	character	16
Job_stream_folder_name	The name of the folder that contains the job stream.	string	4000 Oracle 4095 DB2
Job_stream_identifier	The identifier of the job stream.	character	16
Job_stream_name	The name of the job stream.	string	16
Job_stream_valid_from	The starting date from which the job stream is included in a production plan if selected by a run cycle.	date	<b>10</b> In D B2® <b>9</b> In Or a cle
Job_stream_valid_to	The last date that the job stream is included in a production plan if selected by a run cycle.	date	<b>10</b> In D B2® <b>9</b> In Or a cle
Run_cycle_identifier	The identifier of the run cycle associated with the job stream.	character	16
Run_cycle_name	The name of the run cycle associated with the job stream.	string	40

**Table 49. The RUN\_CYCLE\_REFS\_V view (continued)**

Column name	Description	Type	Length
Run_cycle_valid_from	The starting date from which the run cycle is included in a production plan.	date	10 In D B2® 9 In Or a cle
Run_cycle_valid_to	The last date that the run cycle is included in a production plan.	date	10 In D B2® 9 In Or a cle
Run_cycle_type	The type of run cycle associated with the job stream. Possible values are:  <b>S</b> Simple  <b>C</b> Calendar-based  <b>R</b> Rule-based	character	1
Run_cycle_definition	The rules defined for the run cycle. If this field is not specified, the run cycle associated with the job stream and specified in the <b>Run_cycle_type</b> column is calendar-based.	string	not defined
Free_days_rule	The non-working day rule associated with the run cycle. Possible values are:	character	1

Table 49. The RUN\_CYCLE\_REFS\_V view (continued)

Column name	Description	Type	Length
	<p><b>N</b></p> <p>None. Follow no rule. Schedule the job stream regardless of whether the schedule falls on a non-working day or on a workday.</p> <p><b>B</b></p> <p>Nearest workday before a non-working day. Counts both workdays and non-working days. If the scheduled date falls on a non-working day, schedule the job stream on the preceding workday.</p> <p><b>A</b></p> <p>Nearest workday after a non-working day. Counts both workdays and non-working days. If the scheduled date falls on a non-working day, schedule the job stream on the following workday.</p> <p><b>X</b></p> <p>Do not select. Counts both workdays and non-working days. If the scheduled date falls on a non-working day, do not schedule the job stream.</p>		
Run_cycle_inclusive	Whether the run cycle associated with the job stream is inclusive or exclusive. Possible values are:	character	1
	<p><b>Y</b></p> <p>Inclusive</p> <p><b>N</b></p> <p>Exclusive</p>		
Calendar_identifier	The identifier of the calendar on which the run cycle is defined.	character	16
Calendar_name	The name of the calendar on which the run cycle is defined.	string	16
Calendar_folder_id	The identifier of the folder where the calendar is stored.	character	16

**Table 49. The RUN\_CYCLE\_REFS\_V view (continued)**

Column name	Description	Type	Length
Calendar_folder_name	The name of the folder where the calendar is stored.	string	801
Offset_type	The type of offset associated with the calendar on which the run cycle is defined. Possible values are:  <b>D</b>  Days. The day indicated in the calendar plus the specified offset value.  <b>W</b>  Workdays. The day indicated in the calendar plus the number of workdays.  <b>A</b>  Weekdays. The day indicated in the calendar plus the weekdays (Monday to Friday).	character	1
Offset_value	The value of the offset associated with the offset type.	integer	4
Job_stream_wks_folder_id	The identifier of the folder containing the workstation of the job stream.	character	16
Job_stream_wks_folder_name	The name of the folder containing the workstation of the job stream.	string	801
Job_stream_wks_symphony_id	An identifier used in the Symphony file to identify the workstation of the job stream.	string	16

### Output example

Table 50: RUN\_CYCLE\_REFS\_V view output example on page 120 shows an example of the output for the RUN\_CYCLE\_REFS\_V view.

**Table 50. RUN\_CYCLE\_REFS\_V view output example**

JOB_STREAM_WKS_NAME	JOB_STREAM_NAME	JOB_STREAM_VALID_FROM	JOB_STREAM_VALID_TO	RUN_CYCLE_NAME	RUN_CYCLE_TYPE	RUN_CYCLE_DEFINITION
ASPTTY	BD601C200N061	-	-	CALENDARHOLIDAY	C	-
SAYYUSI	BD601C200N062	-	-	CALENDARHOLIDAY	C	-
QQRSIT	BD601C200N063	-	-	CALENDARHOLIDAY	C	-
DDPDSFR	BD601C200N064	-	-	CALENDARHOLIDAY	C	-
CCCRDJT	BD601C200N065	-	-	CALENDARHOLIDAY	C	-
ZZXETO	BD601C200N066	-	-	CALENDARHOLIDAY	C	-
VVVMMMO	BD601C200N067	-	-	CALENDARHOLIDAY	C	-
GGGRDJT	BD601C200N068	-	-	CALENDARHOLIDAY	C	-
NBMFDSA	BD601C200N069	-	-	CALENDARHOLIDAY	C	-
ASDFGHC	BD601C200N060	-	-	CALENDARHOLIDAY	C	-
RCVBNTRE	BD601C200N06Q	-	-	CALENDARHOLIDAY	C	-
GFYUIOPO	BD601C200N06W	-	-	CALENDARHOLIDAY	C	-
SWERQAZE	BD601C200N06E	-	-	CALENDARHOLIDAY	C	-
XSWQADFR	BD601C200N06R	-	-	CALENDARHOLIDAY	C	-

Table 50. RUN\_CYCLE\_REFS\_V view output example (continued)

FREE_DAYS_RULE	RUN_CYCLE_INCLUSIVE	CALENDAR_NAME	OFFSET_TYPE	OFFSET_VALUE	JOB_STREAM_WKS_FOLDER_NAME
N	Y	CH-CH	W	-1.	/E_EUROPE/PRD/APP1/
N	Y	CH-CH	W	-1.	/E_EUROPE/PRD/APP1/
N	Y	CH-CH	W	-1.	/N_EUROPE/PRD/APP1/
N	Y	CH-CH	W	-1.	/W_EUROPE/PRD/APP1/
N	Y	CH-CH	D	0.	/E_EUROPE/PRD/APP1/
N	Y	CH-CH	D	0.	/N_EUROPE/PRD/APP1/
N	Y	CH-CH	D	0.	/E_EUROPE/PRD/APP1/
N	Y	CH-CH	D	0.	/S_EUROPE/PRD/APP1/
N	Y	CH-CH	D	0.	/W_EUROPE/PRD/APP1/
N	Y	CH-CH	D	0.	/N_EUROPE/PRD/APP1/
N	Y	CH-CH	D	0.	/S_EUROPE/PRD/APP1/
N	Y	PAYDAYS	D	0.	/E_EUROPE/PRD/APP1/
N	Y	PAYDAYS	D	0.	/W_EUROPE/PRD/APP1/
N	Y	PAYDAYS	D	0.	/S_EUROPE/PRD/APP1/
N	Y	PAYDAYS	D	0.	/S_EUROPE/PRD/APP1/

## VARIABLES\_V

Table 51. The VARIABLES\_V view

The VARIABLES\_V view displays information about global parameters, from now on variables.

Column name	Description	Type	Length
Variable_table_identifier	The identifier of the variable table that contains the variable.	character	16
Variable_table	The name of the variable table that contains the variable.	string	80
Variable_identifier	The identifier of the variable.	character	16
Variable_name	The name of the variable.	string	8
Variable_value	The value associated with the variable.	string	72

For more information, see *User's Guide and Reference - Customizing your workload using variable tables*.

## Output example

Table 52: VARIABLES\_V view output example on page 121 shows an example of the output for the VARIABLES\_V view.

Table 52. VARIABLES\_V view output example

VARIABLE_TABLE	VARIABLE_NAME	VARIABLE_VALUE
ENVIRONMENT_UNIX	DB2_PATH	/home/db2inst1/sqllib
ENVIRONMENT_UNIX	TEMP_DIR	/tmp
ENVIRONMENT_WINDOWS	DB2_PATH	C:\Program Files\IBM\SQLLIB
ENVIRONMENT_WINDOWS	OFFICE_PATH	C:\Program Files\Microsoft Office
ENVIRONMENT_WINDOWS	TEMP_DIR	C:\Temp

## VARIABLE\_TABLE\_REFS\_V

**Table 53. The VARIABLE\_TABLE\_REFS\_V view**

The VARIABLE\_TABLE\_REFS\_V view displays information about job streams, run cycles, and workstations that use variable tables.

Column name	Description	Type	Length
Variable_table_identifier	The identifier of the variable table that contains the variable.	character	16
Variable_table	The name of the variable table that contains the variable.	string	80
Variable_table_folder_id	The identifier of the folder where the variable table is stored.	character	16
Variable_table_folder_name	The name of the folder where the variable table is stored.	string	801
Is_default	If the variable table is the default variable table. Possible values are:  <b>Y</b>  Yes  <b>N</b>  No	character	1
Workstation_identifier	The identifier of the workstation that uses the variable table or the name of the workstation on which the job stream that uses the variable table is defined.	character	16
Workstation_name	The name of the workstation that uses the variable table or the name of the workstation on which the job stream that uses the variable table is defined.	string	16
Job_stream_folder_id	The identifier of the folder that contains the job stream that uses the variable table.	character	16

Column name	Description	Type	Length
Job_stream_folder_name	The name of the folder that contains the job stream that uses the variable table.	string	4000 Oracle 4095 DB2
Job_stream_identifier	The identifier of the job stream that uses the variable table.	character	16
Job_stream_name	The name of the job stream that uses the variable table.	string	16
Job_stream_valid_from	The starting date from which the job stream that uses the variable table is included in a production plan if selected by a run cycle.	date	10 In DB2® 9 In Oracle
Job_stream_valid_to	The last date that the dependent job stream that uses the variable table is included in a production plan if selected by a run cycle.	date	10 In DB2® 9 In Oracle
Run_cycle_identifier	The identifier of the run cycle that uses the variable table.	character	16
Run_cycle_name	The name of the run cycle that uses the variable table.	string	40
Workstation_folder_id	The identifier of the folder in which the workstation is defined.	character	16
Workstation_folder_name	The name of the folder in which the workstation is defined.	string	801
Workstation_symphony_id	An identifier used in the Symphony file to identify the workstation.	string	16

## Output example

Table 54: VARIABLE\_TABLE\_REFS\_V view output example on page 123 shows an example of the output for the VARIABLE\_TABLE\_REFS\_V view.

Table 54. VARIABLE\_TABLE\_REFS\_V view output example

VARIABLE_TABLE	IS_DEFAULT	WORKSTATION_NAME	JOB_STREAM_NAME	JOB_STREAM_VALID_FROM	JOB_STREAM_VALID_TO	RUN_CYCLE_NAME
TABLE2	N	CPU1	FINAL	-	-	WORKDAYS2
TABLE1	N	CPU1	FINAL	-	-	WORKDAYS1
TABLE1	N	FTA3	JS4	03/31/2008	04/30/2008	-
TABLE4	N	FTA3	JS4	04/30/2008	-	-
TABLE4	N	FTA3	JS4	-	03/31/2008	-

Table 54. VARIABLE\_TABLE\_REFS\_V view output example (continued)

TABLE3	N	FTA3	-	-	-	-
6 record(s) selected.						

# Notices

This document provides information about copyright, trademarks, terms and conditions for product documentation.

© Copyright IBM Corporation 1993, 2016 / © Copyright HCL Technologies Limited 2016, 2024

This information was developed for products and services offered in the US. This material might be available from IBM in other languages. However, you may be required to own a copy of the product or product version in that language in order to access it.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing*  
*IBM Corporation*  
*North Castle Drive, MD-NC119*  
*Armonk, NY 10504-1785*  
*US*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing*  
*Legal and Intellectual Property Law*  
*IBM Japan Ltd.*  
*19-21, Nihonbashi-Hakozakicho, Chuo-ku*  
*Tokyo 103-8510, Japan*

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Director of Licensing*  
*IBM Corporation*  
*North Castle Drive, MD-NC119*  
*Armonk, NY 10504-1785*  
*US*

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data discussed herein is presented as derived under specific operating conditions. Actual results may vary.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

#### COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

© (HCL Technologies Limited) (2024).

Portions of this code are derived from IBM Corp. Sample Programs.

© Copyright IBM Corp. 2016

## Trademarks

IBM, the IBM logo, and [ibm.com](http://ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM® or other companies. A current list of IBM® trademarks is available on the web at "Copyright and trademark information" at [www.ibm.com/legal/copytrade.shtml](http://www.ibm.com/legal/copytrade.shtml).

Adobe™, the Adobe™ logo, PostScript™, and the PostScript™ logo are either registered trademarks or trademarks of Adobe™ Systems Incorporated in the United States, and/or other countries.

IT Infrastructure Library™ is a Registered Trade Mark of AXELOS Limited.

Linear Tape-Open™, LTO™, the LTO™ Logo, Ultrium™, and the Ultrium™ logo are trademarks of HP, IBM® Corp. and Quantum in the U.S. and other countries.

Intel™, Intel™ logo, Intel Inside™, Intel Inside™ logo, Intel Centrino™, Intel Centrino™ logo, Celeron™, Intel Xeon™, Intel SpeedStep™, Itanium™, and Pentium™ are trademarks or registered trademarks of Intel™ Corporation or its subsidiaries in the United States and other countries.

Linux™ is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft™, Windows™, Windows NT™, and the Windows™ logo are trademarks of Microsoft™ Corporation in the United States, other countries, or both.



Java™ and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Cell Broadband Engine™ is a trademark of Sony Computer Entertainment, Inc. in the United States, other countries, or both and is used under license therefrom.

ITIL™ is a Registered Trade Mark of AXELOS Limited.

UNIX™ is a registered trademark of The Open Group in the United States and other countries.

## Terms and conditions for product documentation

Permissions for the use of these publications are granted subject to the following terms and conditions.

## **Applicability**

These terms and conditions are in addition to any terms of use for the IBM website.

## **Personal use**

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of IBM.

## **Commercial use**

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of IBM.

## **Rights**

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

IBM reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by IBM, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

IBM MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

# Index

## Special Characters

.JOB\_DEPS\_V view 35

## A

abended\_runs column  
JOB\_STATISTICS\_V view 47  
access  
to display views 11  
accessibility v  
action  
action description  
EVENT\_RULE\_ACTIONS\_V view 21  
action identifier  
EVENT\_RULE\_ACTIONS\_V view 21  
action provider  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
EVENT\_RULE\_ACTIONS\_V view 22  
action result  
ACTION\_RUNS\_V view 16  
action scope  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
EVENT\_RULE\_ACTIONS\_V view 22  
action status  
ACTION\_RUNS\_V view 16  
action type  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
AUDIT\_STORE\_RECORDS\_V view 17  
EVENT\_RULE\_ACTIONS\_V view 22  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 15  
event rule identifier  
EVENT\_RULE\_ACTIONS\_V view 21  
event rule name  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
EVENT\_RULE\_ACTIONS\_V view 21  
LOG\_MESSAGES\_V view 59  
event rule type  
ACTION\_RUNS\_V view 16  
LOG\_MESSAGES\_V view 59  
event scope  
LOG\_MESSAGES\_V view 59  
event type  
LOG\_MESSAGES\_V view 59  
EVENT\_RULE\_ACTIONS\_V view 21  
information type  
LOG\_MESSAGES\_V view 58  
job identifier  
EVENT\_RULE\_ACTIONS\_V view 22  
job name  
EVENT\_RULE\_ACTIONS\_V view 22  
job workstation identifier  
EVENT\_RULE\_ACTIONS\_V view 22  
job workstation name  
EVENT\_RULE\_ACTIONS\_V view 22  
justification category  
AUDIT\_STORE\_RECORDS\_V view 17  
justification description  
AUDIT\_STORE\_RECORDS\_V view 17  
justification ticket num column  
AUDIT\_STORE\_RECORDS\_V view 17  
line of business  
LOG\_MESSAGES\_V view 59  
log time

ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 15  
AUDIT\_STORE\_RECORDS\_V view 17  
LOG\_MESSAGES\_V view 58  
log type  
AUDIT\_STORE\_RECORDS\_V view 17  
log\_id  
AUDIT\_STORE\_RECORDS\_V view 18  
message  
ACTION\_RUNS\_V view 16  
LOG\_MESSAGES\_V view 59  
object definition  
AUDIT\_STORE\_RECORDS\_V view 18  
object definition differences  
AUDIT\_STORE\_RECORDS\_V view 17  
object identifier  
AUDIT\_STORE\_RECORDS\_V view 18  
object key  
AUDIT\_STORE\_RECORDS\_V view 17  
object name  
AUDIT\_STORE\_RECORDS\_V view 17  
object type  
AUDIT\_STORE\_RECORDS\_V view 17  
owner group  
LOG\_MESSAGES\_V view 59  
parameter list  
EVENT\_RULE\_ACTIONS\_V view 22  
parameter name type  
ACTION\_PARAMETERS\_V view 15  
parameter value type  
ACTION\_PARAMETERS\_V view 15  
related object name  
AUDIT\_STORE\_RECORDS\_V view 18  
related workstation name  
AUDIT\_STORE\_RECORDS\_V view 17  
response type  
EVENT\_RULE\_ACTIONS\_V view 22  
source  
LOG\_MESSAGES\_V view 59  
user name type  
AUDIT\_STORE\_RECORDS\_V view 17  
workstation name  
AUDIT\_STORE\_RECORDS\_V view 17  
workstation\_name  
LOG\_MESSAGES\_V view 59  
action\_description column  
EVENT\_RULE\_ACTIONS\_V view 21  
action\_identifier column  
EVENT\_RULE\_ACTIONS\_V view 21  
ACTION\_PARAMETERS\_V view 15  
action\_provider column  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
EVENT\_RULE\_ACTIONS\_V view 22  
action\_result column  
ACTION\_RUNS\_V view 16  
ACTION\_RUNS\_V view 15  
action\_scope column  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
EVENT\_RULE\_ACTIONS\_V view 22  
action\_status column  
ACTION\_RUNS\_V view 16  
action\_type column  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
AUDIT\_STORE\_RECORDS\_V view 17  
EVENT\_RULE\_ACTIONS\_V view 22

actual\_workstation\_name\_in\_run column  
JOB\_HISTORY\_V view 43  
AUDIT\_STORE\_RECORDS\_V  
output example 18  
AUDIT\_STORE\_RECORDS\_V view 16  
average\_cpu\_time column  
JOB\_STATISTICS\_V view 48  
average\_elapsed\_time column  
JOB\_STATISTICS\_V view 48

## B

bind request  
interval end offset  
REMOTE\_JOB\_REQUESTS\_V view 110  
interval start offset  
REMOTE\_JOB\_REQUESTS\_V view 110  
local job name  
REMOTE\_JOB\_REQUESTS\_V view 110  
local job start time  
REMOTE\_JOB\_REQUESTS\_V view 110  
local job stream name  
REMOTE\_JOB\_REQUESTS\_V view 110  
local workstation name  
REMOTE\_JOB\_REQUESTS\_V view 110  
matching criteria  
REMOTE\_JOB\_REQUESTS\_V view 110  
notification URI  
REMOTE\_JOB\_REQUESTS\_V view 111  
remote job identifier  
REMOTE\_JOB\_REQUESTS\_V view 109  
remote job start time  
REMOTE\_JOB\_REQUESTS\_V view 109  
request status  
REMOTE\_JOB\_REQUESTS\_V view 110

## C

calendar  
CALENDARS\_V view 20  
output example 20  
calendar\_identifier column  
RUN\_CYCLE\_REFS\_V view 119  
calendar\_name column  
JOB\_STREAM\_REFS\_V view 57, 57  
RUN\_CYCLE\_REFS\_V view 119  
CALENDARS\_V view 20  
output example 20  
Cloud & Smarter Infrastructure technical training v  
column  
abended\_runs  
JOB\_STATISTICS\_V view 47  
action\_provider  
ACTION\_PARAMETERS\_V view 15  
EVENT\_RULE\_ACTIONS\_V view 22  
action\_result  
ACTION\_RUNS\_V view 16  
action\_scope  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
EVENT\_RULE\_ACTIONS\_V view 22  
action\_status  
ACTION\_RUNS\_V view 16  
action\_type  
ACTION\_PARAMETERS\_V view 15  
ACTION\_RUNS\_V view 16  
AUDIT\_STORE\_RECORDS\_V view 17  
EVENT\_RULE\_ACTIONS\_V view 22  
actual\_workstation\_name\_in\_run

JOB\_HISTORY\_V view 43  
 average\_cpu\_time  
   JOB\_STATISTICS\_V view 48  
 average\_elapsed\_time  
   JOB\_STATISTICS\_V view 48  
 calendar\_identifier  
   RUN\_CYCLE\_REFS\_V view 119  
 calendar\_name  
   RUN\_CYCLE\_REFS\_V view 119  
 calendar\_identifier  
   JOB\_STREAM\_REFS\_V view 57  
 calendar\_name  
   JOB\_STREAM\_REFS\_V view 57  
 condition\_on\_abend  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 52  
 condition\_on\_execute  
   JOB\_DEPS\_V view 39  
   JOB\_STREAM\_DEPS\_V view 53  
 condition\_on\_fail  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 53  
 condition\_on\_success  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 52  
 condition\_on\_suppress  
   JOB\_DEPS\_V view 39  
   JOB\_STREAM\_DEPS\_V view 53  
 conditional\_dep\_id  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 52  
 dep\_job\_critical  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 51  
 dep\_job\_definition\_identifier  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 32  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_definition\_name  
   FILE\_REFS\_V view 29  
   INTERNETWORK\_DEPS\_V view 32  
   JOB\_STREAM\_DEPS\_V view 51, 52  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_folder\_id  
   FILE\_REFS\_V view 28  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 Dep\_job\_folder\_id  
   INTERNETWORK\_DEPS\_V view 32  
 dep\_job\_folder\_name  
   FILE\_REFS\_V view 28  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 Dep\_job\_folder\_name  
   INTERNETWORK\_DEPS\_V view 32  
 dep\_job\_identifier  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 32  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_name  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 32  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_stream\_folder\_id  
   FILE\_REFS\_V view 27  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 Dep\_job\_stream\_folder\_id  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
 dep\_job\_stream\_folder\_name  
   FILE\_REFS\_V view 27  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 Dep\_job\_stream\_folder\_name  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
 dep\_job\_stream\_identifier  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_name  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50, 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_valid\_from  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_valid\_to  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
   VARIABLE\_TABLE\_REFS\_V view 123  
 dep\_job\_stream\_wks\_identifier  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_wks\_name  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_wks\_identifier  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_wks\_name  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dependent\_job\_stream\_valid\_from\_date  
   FILE\_REFS\_V view 27  
 end\_offset  
   EVENT\_RULES\_V view 26  
 event\_name  
   EVENT\_CONDITIONS\_V view 21  
 event\_provider  
   ACTION\_RUNS\_V view 16  
   EVENT\_CONDITIONS\_V view 21  
 event\_rule\_description column  
   EVENT\_RULE\_ACTIONS\_V view 21  
   EVENT\_RULES\_V view 24  
 event\_rule\_identifier  
   EVENT\_RULE\_ACTIONS\_V view 21  
 event\_rule\_identifier column  
   EVENT\_RULE\_ACTIONS\_V view 21  
 event\_rule\_instance\_status  
   EVENT\_RULE\_INSTANCES\_V view 24  
 event\_rule\_name  
   ACTION\_PARAMETERS\_V view 15  
   ACTION\_RUNS\_V view 16  
   EVENT\_CONDITIONS\_V view 21  
   EVENT\_RULE\_ACTIONS\_V view 21  
   EVENT\_RULE\_INSTANCES\_V view 23  
   EVENT\_RULES\_V view 24  
   LOG\_MESSAGES\_V view 59  
 event\_rule\_status  
   EVENT\_RULES\_V view 25  
 event\_rule\_type  
   ACTION\_RUNS\_V view 16  
   EVENT\_RULE\_INSTANCES\_V view 23  
   EVENT\_RULES\_V view 24  
   LOG\_MESSAGES\_V view 59  
 event\_scope  
   EVENT\_CONDITIONS\_V view 21  
   LOG\_MESSAGES\_V view 59  
 event\_type  
   EVENT\_CONDITIONS\_V view 21  
   LOG\_MESSAGES\_V view 59  
 file\_identifier  
   FILE\_REFS\_V view 27  
 file\_name  
   FILE\_REFS\_V view 27  
 filtering\_predicate  
   EVENT\_CONDITIONS\_V view 21  
 free\_days\_rule  
   RUN\_CYCLE\_REFS\_V view 118  
 group\_attribute\_list  
   EVENT\_RULES\_V view 26  
 information\_type  
   LOG\_MESSAGES\_V view 58  
 internetwork\_dependency  
   INTERNETWORK\_DEPS\_V view 30  
 interval\_end\_offset  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 interval\_start\_offset  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 is\_default  
   VARIABLE\_TABLE\_REFS\_V view 122  
 is\_draft  
   EVENT\_RULES\_V view 25  
 is\_timeout\_expired  
   EVENT\_RULE\_INSTANCES\_V view 24  
 job\_critical  
   JOB\_HISTORY\_V view 45  
 job\_critical\_latest\_time  
   JOB\_HISTORY\_V view 45  
 job\_definition\_identifier  
   JOB\_DEFINITION\_REFS\_V view 34  
   JOB\_HISTORY\_V view 42  
   JOB\_STATISTICS\_V view 46

job\_definition\_name  
   JOB\_DEFINITION\_REFS\_V view 34  
 job\_description  
   JOB\_STATISTICS\_V view 46  
 job\_end\_time  
   JOB\_HISTORY\_V view 43  
 job\_folder\_id  
   JOB\_DEFINITION\_REFS\_V view 34  
   JOB\_HISTORY\_V view 42  
   JOB\_STATISTICS\_V view 46  
 job\_folder\_name  
   JOB\_DEFINITION\_REFS\_V view 34  
   JOB\_HISTORY\_V view 42  
   JOB\_STATISTICS\_V view 46  
 job\_identifier  
   EVENT\_RULE\_ACTIONS\_V view 22  
   JOB\_DEPS\_V view 35  
 job\_identifier\_in\_run  
   JOB\_HISTORY\_V view 43  
 job\_login\_user  
   JOB\_STATISTICS\_V view 46  
 job\_modify\_user  
   JOB\_STATISTICS\_V view 47  
 job\_name  
   EVENT\_RULE\_ACTIONS\_V view 22  
   JOB\_DEFINITION\_REFS\_V view 34  
   JOB\_DEPS\_V view 35  
   JOB\_HISTORY\_V view 42  
   JOB\_STATISTICS\_V view 46  
 job\_name\_in\_run  
   JOB\_HISTORY\_V view 43  
 job\_number  
   JOB\_HISTORY\_V view 44  
 job\_promoted  
   JOB\_HISTORY\_V view 45  
 job\_run\_date\_time  
   JOB\_HISTORY\_V view 42  
 job\_script\_name  
   JOB\_STATISTICS\_V view 46  
 job\_start\_time  
   JOB\_HISTORY\_V view 42  
 job\_status  
   JOB\_HISTORY\_V view 44  
 job\_stream\_folder\_id  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_STREAM\_DEPS\_V view 50  
   JOB\_STREAM\_REFS\_V view 56  
   RUN\_CYCLE\_REFS\_V view 22, 117  
 Job\_stream\_folder\_id  
   JOB\_DEPS\_V view 36  
 job\_stream\_folder\_name  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_HISTORY\_V view 41  
   JOB\_STREAM\_DEPS\_V view 50  
   JOB\_STREAM\_REFS\_V view 56  
   RUN\_CYCLE\_REFS\_V view 23, 117  
 Job\_stream\_folder\_name  
   JOB\_DEPS\_V view 36  
 job\_stream\_identifier  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_STREAM\_DEPS\_V view 50  
   JOB\_STREAM\_REFS\_V view 56  
   RUN\_CYCLE\_REFS\_V view 23, 117  
   VARIABLE\_TABLE\_REFS\_V view 123  
 job\_stream\_instance\_id  
   JOB\_HISTORY\_V view 45  
 job\_stream\_name  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_DEPS\_V view 36, 36  
   JOB\_STREAM\_DEPS\_V view 50  
   JOB\_STREAM\_REFS\_V view 56  
   RUN\_CYCLE\_REFS\_V view 23, 117  
   VARIABLE\_TABLE\_REFS\_V view 123  
 job\_stream\_name\_in\_run  
   JOB\_HISTORY\_V view 43  
 job\_stream\_valid\_from  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_STREAM\_REFS\_V view 57  
   RUN\_CYCLE\_REFS\_V view 117  
   VARIABLE\_TABLE\_REFS\_V view 123  
 job\_stream\_valid\_to  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_STREAM\_REFS\_V view 57  
   RUN\_CYCLE\_REFS\_V view 117  
 job\_stream\_wks\_identifier  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50  
   RUN\_CYCLE\_REFS\_V view 22, 117  
 job\_stream\_wks\_name  
   JOB\_DEFINITION\_REFS\_V view 33  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50  
   RUN\_CYCLE\_REFS\_V view 22, 117  
 job\_stream\_wks\_name\_in\_run  
   JOB\_HISTORY\_V view 41  
 job\_wks\_identifier  
   EVENT\_RULE\_ACTIONS\_V view 22  
   JOB\_DEFINITION\_REFS\_V view 34  
 job\_wks\_name  
   EVENT\_RULE\_ACTIONS\_V view 22  
   JOB\_DEFINITION\_REFS\_V view 34  
 join\_id  
   JOB\_DEPS\_V view 39  
   JOB\_STREAM\_DEPS\_V view 54  
 join\_name  
   JOB\_DEPS\_V view 40  
   JOB\_STREAM\_DEPS\_V view 54  
 join\_quantity  
   JOB\_DEPS\_V view 40  
   JOB\_STREAM\_DEPS\_V view 54  
 justification\_category  
   AUDIT\_STORE\_RECORDS\_V view 17  
 justification\_description  
   AUDIT\_STORE\_RECORDS\_V view 17  
 justification\_ticket\_num column  
   AUDIT\_STORE\_RECORDS\_V view 17  
 last\_cpu\_time  
   JOB\_STATISTICS\_V view 48  
 last\_elapsed\_time  
   JOB\_STATISTICS\_V view 48  
 last\_run\_date  
   JOB\_STATISTICS\_V view 48  
 late\_end\_runs  
   JOB\_STATISTICS\_V view 48  
 late\_end\_time  
   JOB\_HISTORY\_V view 42  
 late\_start\_runs  
   JOB\_STATISTICS\_V view 48  
 late\_start\_time  
   JOB\_HISTORY\_V view 42  
 line\_of\_business  
   LOG\_MESSAGES\_V view 59  
 local\_job\_name column  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 local\_job\_start\_time  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 local\_job\_stream\_name column  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 local\_workstation\_name  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 log\_id  
   AUDIT\_STORE\_RECORDS\_V view 18  
   log\_time  
     ACTION\_PARAMETERS\_V view 15  
     ACTIONS\_RUNS\_V view 15  
     AUDIT\_STORE\_RECORDS\_V view 17  
     EVENT\_RULE\_INSTANCES\_V view 23  
     JOB\_HISTORY\_V view 45  
     LOG\_MESSAGES\_V view 58  
   log\_type  
     AUDIT\_STORE\_RECORDS\_V view 17  
   long\_duration  
     JOB\_HISTORY\_V view 43  
   long\_duration\_runs  
     JOB\_STATISTICS\_V view 47  
   matching\_criteria  
     REMOTE\_JOB\_REQUESTS\_V view 110  
   max\_cpu\_time  
     JOB\_STATISTICS\_V view 48  
   max\_elapsed\_time  
     JOB\_STATISTICS\_V view 48  
   max\_run\_date  
     JOB\_STATISTICS\_V view 48  
   message  
     ACTION\_RUNS\_V view 16  
     LOG\_MESSAGES\_V view 59  
   min\_cpu\_time  
     JOB\_STATISTICS\_V view 49  
   min\_elapsed\_time  
     JOB\_STATISTICS\_V view 49  
   min\_run\_date  
     JOB\_STATISTICS\_V view 49  
   network\_agent\_identifier  
     INTERNETWORK\_DEPS\_V view 30  
   network\_agent\_name  
     INTERNETWORK\_DEPS\_V view 30  
   notification\_URI  
     REMOTE\_JOB\_REQUESTS\_V view 111  
   object\_definition  
     AUDIT\_STORE\_RECORDS\_V view 18  
   object\_definition\_differences  
     AUDIT\_STORE\_RECORDS\_V view 17  
   object\_identifier  
     AUDIT\_STORE\_RECORDS\_V view 18  
   object\_key  
     AUDIT\_STORE\_RECORDS\_V view 17  
   object\_name  
     AUDIT\_STORE\_RECORDS\_V view 17  
   object\_type  
     AUDIT\_STORE\_RECORDS\_V view 17  
   offset\_type  
     RUN\_CYCLE\_REFS\_V view 120  
   offset\_value  
     RUN\_CYCLE\_REFS\_V view 120  
   owner\_group  
     LOG\_MESSAGES\_V view 59  
   parameter\_list  
     EVENT\_RULE\_ACTIONS\_V 22  
   parameter\_name  
     ACTION\_PARAMETERS\_V view 15  
   parameter\_value  
     ACTION\_PARAMETERS\_V view 15  
   planned\_duration  
     JOB\_HISTORY\_V view 42  
   prompt\_identifier  
     PROMPT\_REFS\_V view 107  
   PROMPTS\_V view 106  
   prompt\_name  
     PROMPT\_REFS\_V view 107  
     PROMPTS\_V view 106  
   prompt\_text  
     PROMPT\_REFS\_V view 107

prompt\_value  
   PROMPTS\_V view 106  
 property\_name  
   PROPERTIES\_V view 109  
 property\_value  
   PROPERTIES\_V view 109  
 recovery\_job\_definition\_id  
   JOB\_STATISTICS\_V view 46  
 recovery\_job\_name  
   JOB\_STATISTICS\_V view 47  
 recovery\_option  
   JOB\_STATISTICS\_V view 47  
 recovery\_prompt  
   JOB\_STATISTICS\_V view 47  
 recovery\_repeat\_affinity  
   JOB\_STATISTICS\_V view 47  
 recovery\_repeat\_interval  
   JOB\_STATISTICS\_V view 47  
 recovery\_repeat\_occurrences  
   JOB\_STATISTICS\_V view 47  
 related\_object\_name  
   AUDIT\_STORE\_RECORDS\_V view 18  
 related\_workstation\_name  
   AUDIT\_STORE\_RECORDS\_V view 17  
 remote\_job\_identifier  
   REMOTE\_JOB\_REQUESTS\_V view 109  
 remote\_job\_start\_time  
   REMOTE\_JOB\_REQUESTS\_V view 109  
 request\_status  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 rerun\_number  
   JOB\_HISTORY\_V view 44  
 rerun\_type  
   JOB\_HISTORY\_V view 44  
 resource\_description  
   RESOURCES\_V view 112  
 resource\_identifier  
   RESOURCE\_REFS\_V view 113  
   RESOURCES\_V view 112  
 resource\_name  
   RESOURCE\_REFS\_V view 113  
   RESOURCES\_V view 111  
 resource\_units  
   RESOURCES\_V view 112  
 response\_type  
   EVENT\_RULE\_ACTIONS\_V view 22  
 return\_code  
   JOB\_HISTORY\_V view 44  
 run\_cycle\_definition  
   RUN\_CYCLE\_REFS\_V view 118  
 run\_cycle\_identifier  
   RUN\_CYCLE\_REFS\_V view 117  
   VARIABLE\_TABLE\_REFS\_V view 123  
 run\_cycle\_inclusive  
   RUN\_CYCLE\_REFS\_V view 119  
 run\_cycle\_name  
   RUN\_CYCLE\_REFS\_V view 117  
   VARIABLE\_TABLE\_REFS\_V view 123  
 run\_cycle\_type  
   RUN\_CYCLE\_REFS\_V view 118  
 run\_cycle\_valid\_from  
   RUN\_CYCLE\_REFS\_V view 118  
 run\_cycle\_valid\_to  
   RUN\_CYCLE\_REFS\_V view 118  
 source  
   LOG\_MESSAGES\_V view 59  
 start\_offset  
   EVENT\_RULES\_V view 26  
 successful\_runs  
   JOB\_STATISTICS\_V view 47  
 suppressed\_runs

  JOB\_STATISTICS\_V view 47  
 time\_interval  
   EVENT\_RULES\_V view 26  
 time\_zone  
   EVENT\_RULES\_V view 26  
 total\_cpu\_time  
   JOB\_HISTORY\_V view 43  
   JOB\_STATISTICS\_V view 48  
 total\_elapsed\_time  
   JOB\_HISTORY\_V view 43  
   JOB\_STATISTICS\_V view 48  
 total\_reruns  
   JOB\_STATISTICS\_V view 48  
 type\_of\_dependency  
   JOB\_DEPS\_V view 35  
   JOB\_STREAM\_DEPS\_V view 49  
 units\_allocated  
   RESOURCE\_REFS\_V view 113  
 units\_available  
   RESOURCE\_REFS\_V view 113  
 user\_login  
   JOB\_HISTORY\_V view 45  
 user\_name  
   AUDIT\_STORE\_RECORDS\_V view 17  
 valid\_from  
   EVENT\_RULES\_V view 26  
 valid\_to  
   EVENT\_RULES\_V view 26  
 variable\_identifier  
   VARIABLES\_V view 121  
 variable\_name  
   VARIABLES\_V view 121  
 variable\_table  
   RUN\_CYCLE\_REFS\_V view 23  
   VARIABLE\_TABLE\_REFS\_V view 122  
   VARIABLES\_V view 121  
 variable\_table\_identifier  
   RUN\_CYCLE\_REFS\_V view 23  
   VARIABLE\_TABLE\_REFS\_V view 122  
   VARIABLES\_V view 121  
 variable\_value  
   VARIABLES\_V view 121  
 workstation\_identifier  
   FILE\_REFS\_V view 27  
   JOB\_STREAM\_REFS\_V view 56  
   RESOURCE\_REFS\_V view 112  
   RESOURCES\_V view 111  
   VARIABLE\_TABLE\_REFS\_V view 122  
 workstation\_license\_type  
   JOB\_HISTORY\_V view 43  
 workstation\_name  
   AUDIT\_STORE\_RECORDS\_V view 17  
   FILE\_REFS\_V view 27  
   JOB\_HISTORY\_V view 41  
   JOB\_STATISTICS\_V view 46  
   JOB\_STREAM\_REFS\_V view 56  
   LOG\_MESSAGES\_V view 59  
   RESOURCE\_REFS\_V view 112  
   RESOURCES\_V view 111  
   VARIABLE\_TABLE\_REFS\_V view 122  
 workstation\_name\_in\_run  
   JOB\_HISTORY\_V view 43  
 condition on abend  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 52  
 condition on execute  
   JOB\_DEPS\_V view 39  
   JOB\_STREAM\_DEPS\_V view 53  
 condition on fail  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 53

condition on success  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 52  
 condition on suppress  
   JOB\_DEPS\_V view 39  
   JOB\_STREAM\_DEPS\_V view 53  
 condition\_on\_abend  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 52  
 condition\_on\_execute  
   JOB\_DEPS\_V view 39  
   JOB\_STREAM\_DEPS\_V view 53  
 condition\_on\_fail  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 53  
 condition\_on\_success  
   JOB\_DEPS\_V view 38  
   JOB\_STREAM\_DEPS\_V view 52  
 condition\_on\_suppress  
   JOB\_DEPS\_V view 39  
   JOB\_STREAM\_DEPS\_V view 53  
 conditional\_dependency\_id  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 52  
 conditional\_dep\_id  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 52

## D

database DB2 on UNIX  
   extracting view information from 12  
 database DB2 on Windows  
   extracting view information from 11  
 DB2 database on UNIX  
   extracting view information from 12  
 DB2 database on Windows  
   extracting view information from 11  
 dDep\_job\_stream\_folder\_id column  
   JOB\_DEPS\_V view 36  
 dep\_job\_critical column  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 51  
 dep\_job\_definition\_identifier column  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 32  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_definition\_name column  
   FILE\_REFS\_V view 29  
   INTERNETWORK\_DEPS\_V view 32  
   JOB\_STREAM\_DEPS\_V view 51, 52  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_folder\_id column  
   FILE\_REFS\_V view 28  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 Dep\_job\_folder\_id column  
   INTERNETWORK\_DEPS\_V view 32  
 dep\_job\_folder\_name column  
   FILE\_REFS\_V view 28  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 Dep\_job\_folder\_name column  
   INTERNETWORK\_DEPS\_V view 32  
 dep\_job\_identifier  
   JOB\_DEPS\_V view 37, 37  
 dep\_job\_identifier column  
   FILE\_REFS\_V view 28

INTERNETWORK\_DEPS\_V view 32  
 JOB\_STREAM\_DEPS\_V view 51  
 PROMPT\_REFS\_V view 108  
 RESOURCE\_REFS\_V view 114  
 dep\_job\_name column  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 32  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_stream\_folder\_id column  
   FILE\_REFS\_V view 27  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 Dep\_job\_stream\_folder\_id column  
   INTERNETWORK\_DEPS\_V view 31  
 dep\_job\_stream\_folder\_name column  
   FILE\_REFS\_V view 27  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 Dep\_job\_stream\_folder\_name column  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
 dep\_job\_stream\_identifier column  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_name column  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50, 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_valid\_from column  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_valid\_to column  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 37  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 dep\_job\_stream\_wks\_identifier column  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_stream\_wks\_name column  
   FILE\_REFS\_V view 27  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_DEPS\_V view 36  
   JOB\_STREAM\_DEPS\_V view 50  
   PROMPT\_REFS\_V view 107  
   RESOURCE\_REFS\_V view 113  
 dep\_job\_wks\_identifier column  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_STREAM\_DEPS\_V view 51

PROMPT\_REFS\_V view 108  
 RESOURCE\_REFS\_V view 114  
 dep\_job\_wks\_name column  
   FILE\_REFS\_V view 28  
   INTERNETWORK\_DEPS\_V view 31  
   JOB\_STREAM\_DEPS\_V view 51  
   PROMPT\_REFS\_V view 108  
   RESOURCE\_REFS\_V view 114  
 displaying  
   view 10  
   view from a DB2 database 11  
   view from an  
     Oracle  
     schema  
       12  
 displaying views  
   granting access 11  
 domains  
   PLAN\_DOMAINS\_V view 59  
 Dynamic Workload Console  
   accessibility v

## E

education v  
 end\_offset column  
   EVENT\_RULES\_V view 26  
 event rule  
   action description  
     EVENT\_RULE\_ACTIONS\_V view 21  
   action identifier  
     EVENT\_RULE\_ACTIONS\_V view 21  
   action provider  
     ACTION\_PARAMETERS\_V view 15  
     ACTION\_RUNS\_V view 16  
     EVENT\_RULE\_ACTIONS\_V view 22  
   action scope  
     EVENT\_RULE\_ACTIONS\_V view 22  
   action type  
     EVENT\_RULE\_ACTIONS\_V view 22  
   ACTION\_RUNS\_V view 15  
   end offset  
     EVENT\_RULES\_V view 26  
   event name  
     EVENT\_CONDITIONS\_V view 21  
   event provider  
     EVENT\_CONDITIONS\_V view 21  
   event rule description  
     EVENT\_RULES\_V view 24  
   event rule identifier  
     EVENT\_RULE\_ACTIONS\_V view 21  
   event rule name  
     EVENT\_CONDITIONS\_V view 21  
     EVENT\_RULE\_ACTIONS\_V view 21  
     EVENT\_RULES\_V view 24  
   event rule status  
     EVENT\_RULES\_V view 25  
   event rule type  
     EVENT\_RULES\_V view 24  
   event scope  
     EVENT\_CONDITIONS\_V view 21  
   event type  
     EVENT\_CONDITIONS\_V view 21  
   EVENT\_CONDITIONS\_V view 21  
   EVENT\_RULE\_ACTIONS\_V view 21  
   EVENT\_RULES\_V view 24  
   filtering predicate  
     EVENT\_CONDITIONS\_V view 21  
   group\_attribute\_list  
     EVENT\_RULES\_V view 26  
   is draft  
     EVENT\_RULES\_V view 25

job identifier  
   EVENT\_RULE\_ACTIONS\_V view 22  
 job name  
   EVENT\_RULE\_ACTIONS\_V view 22  
 job workstation identifier  
   EVENT\_RULE\_ACTIONS\_V view 22  
 job workstation name  
   EVENT\_RULE\_ACTIONS\_V view 22  
 parameter list  
   EVENT\_RULE\_ACTIONS\_V view 22  
 response type  
   EVENT\_RULE\_ACTIONS\_V view 22  
 start offset  
   EVENT\_RULES\_V view 26  
 time interval  
   EVENT\_RULES\_V view 26  
 time zone  
   EVENT\_RULES\_V view 26  
 valid from  
   EVENT\_RULES\_V view 26  
 valid to  
   EVENT\_RULES\_V view 26  
 event rule instance  
   event rule instance status  
     EVENT\_RULE\_INSTANCES\_V view 24  
   event rule name  
     EVENT\_RULE\_INSTANCES\_V view 23  
   event rule type  
     EVENT\_RULE\_INSTANCES\_V view 23  
   EVENT\_RULE\_INSTANCES\_V view 23  
   is timeout expired  
     EVENT\_RULE\_INSTANCES\_V view 24  
   log time  
     EVENT\_RULE\_INSTANCES\_V view 23  
 EVENT\_CONDITIONS\_V view 21  
 event\_name column  
   EVENT\_CONDITIONS\_V view 21  
 event\_provider column  
   EVENT\_CONDITIONS\_V view 21  
 EVENT\_RULE\_ACTIONS\_V view 21  
 event\_rule\_description column  
   EVENT\_RULES\_V view 24  
 event\_rule\_identifier column  
   EVENT\_RULE\_ACTIONS\_V view 21  
 event\_rule\_instance\_status column  
   EVENT\_RULE\_INSTANCES\_V view 24  
 EVENT\_RULE\_INSTANCES\_V view 23  
 event\_rule\_name column  
   ACTION\_PARAMETERS\_V view 15  
   ACTION\_RUNS\_V view 16  
   EVENT\_CONDITIONS\_V view 21  
   EVENT\_RULE\_ACTIONS\_V view 21  
   EVENT\_RULE\_INSTANCES\_V view 23  
   EVENT\_RULES\_V view 24  
   LOG\_MESSAGES\_V view 59  
 event\_rule\_status column  
   EVENT\_RULES\_V view 25  
 event\_rule\_type column  
   ACTION\_RUNS\_V view 16  
   EVENT\_RULE\_INSTANCES\_V view 23  
   EVENT\_RULES\_V view 24  
   LOG\_MESSAGES\_V view 59  
 EVENT\_RULES\_V view 24  
 event\_scope column  
   EVENT\_CONDITIONS\_V view 21  
   LOG\_MESSAGES\_V view 59  
 event\_type column  
   EVENT\_CONDITIONS\_V view 21  
   LOG\_MESSAGES\_V view 59  
 example  
   AUDIT\_STORE\_RECORDS\_V view 18

- CALENDARS\_V view 20
- FILE\_REFS\_V view 29
- JOB\_DEFINITION\_REFS\_V view 34
- JOB\_DEPS\_V view 40
- JOB\_STREAM\_DEPS\_V view 55
- JOB\_STREAM\_REFS\_V view 57
- PROMPTS\_V view 106
- RESOURCE\_REFS\_V view 116
- RESOURCES\_V view 112
- RUN\_CYCLE\_REFS\_V view 120
- VARIABLE\_TABLE\_REFS\_V view 123
- VARIABLES\_V view 121

#### extracting

- DB2 view information 11
- Oracle
  - view information 12
  - view information 10

## F

### file

- dep\_job\_stream\_valid\_from column
  - FILE\_REFS\_V view 27
- dependent job definition identifier
  - FILE\_REFS\_V view 28
- dependent job definition name
  - FILE\_REFS\_V view 29
- dependent job folder id
  - FILE\_REFS\_V view 28
- dependent job folder name
  - FILE\_REFS\_V view 28
- dependent job identifier
  - FILE\_REFS\_V view 28
- dependent job name
  - FILE\_REFS\_V view 28
- dependent job stream folder id
  - FILE\_REFS\_V view 27
- dependent job stream folder name
  - FILE\_REFS\_V view 27
- dependent job stream identifier column
  - FILE\_REFS\_V view 27
- dependent job stream name column
  - FILE\_REFS\_V view 27
- dependent job stream valid to date
  - FILE\_REFS\_V view 28
- dependent job stream workstation identifier
  - FILE\_REFS\_V view 27
- dependent job stream workstation name
  - FILE\_REFS\_V view 27
- dependent job workstation identifier
  - FILE\_REFS\_V view 28
- dependent job workstation name
  - FILE\_REFS\_V view 28
- file identifier
  - FILE\_REFS\_V view 27
- file name
  - FILE\_REFS\_V view 27
- job depending on, output example 29
- job depending on, view 27
- job stream depending on, output example 29
- job stream depending on, view 27
- PLAN\_FILE\_REFS\_V view 60
- PLAN\_FILES\_V view 63
- workstation identifier
  - FILE\_REFS\_V view 27
- workstation name
  - FILE\_REFS\_V view 27
- file\_identifier column
  - FILE\_REFS\_V view 27
- file\_name column

- FILE\_REFS\_V view 27
- FILE\_REFS\_V view 27
  - output example 29
- filtering\_predicate column
  - EVENT\_CONDITIONS\_V view 21
- free\_days\_rule column
  - RUN\_CYCLE\_REFS\_V view 118

## G

- granting
  - access for displaying views 11
- group\_attribute\_list column
  - EVENT\_RULES\_V view 26

## H

- history
  - job folder id
    - JOB\_HISTORY\_V view 42
  - job folder name
    - JOB\_HISTORY\_V view 42
  - of a job, view 41
- history of a job
  - actual\_workstation\_name\_in\_run
    - JOB\_HISTORY\_V view 43
  - job\_definition\_identifier
    - JOB\_HISTORY\_V view 42
  - job\_end\_date\_time
    - JOB\_HISTORY\_V view 43
  - job\_identifier\_in\_run
    - JOB\_HISTORY\_V view 43
  - job\_name
    - JOB\_HISTORY\_V view 42
  - job\_name\_in\_run
    - JOB\_HISTORY\_V view 43
  - job\_number
    - JOB\_HISTORY\_V view 44
  - job\_run\_date\_time
    - JOB\_HISTORY\_V view 42
  - job\_start\_date\_time
    - JOB\_HISTORY\_V view 42
  - job\_status
    - JOB\_HISTORY\_V view 44
  - job\_stream\_name\_in\_run
    - JOB\_HISTORY\_V view 43
  - job\_stream\_workstation\_name\_in\_run
    - JOB\_HISTORY\_V view 41
  - job\_critical
    - JOB\_HISTORY\_V view 45
  - job\_critical\_latest\_time
    - JOB\_HISTORY\_V view 45
  - job\_promoted
    - JOB\_HISTORY\_V view 45
  - job\_stream\_instance\_id
    - JOB\_HISTORY\_V view 45
  - late\_end\_time
    - JOB\_HISTORY\_V view 42
  - late\_start\_time
    - JOB\_HISTORY\_V view 42
  - log\_time
    - JOB\_HISTORY\_V view 45
  - long\_duration
    - JOB\_HISTORY\_V view 43
  - planned\_duration
    - JOB\_HISTORY\_V view 42
  - rerun\_number
    - JOB\_HISTORY\_V view 44
  - rerun\_type
    - JOB\_HISTORY\_V view 44
  - return\_code
    - JOB\_HISTORY\_V view 44
  - total\_cpu\_time
    - JOB\_HISTORY\_V view 43

- total\_elapsed\_time
  - JOB\_HISTORY\_V view 43
- user\_login
  - JOB\_HISTORY\_V view 45
- workstation\_name
  - JOB\_HISTORY\_V view 41
- workstation\_name\_in\_run
  - JOB\_HISTORY\_V view 43
- workstation\_license\_type
  - JOB\_HISTORY\_V view 43

## I

- IBM Workload Scheduler
  - views
    - 15
      - overview 7
  - information\_type column
    - LOG\_MESSAGES\_V view 58
  - internetwork\_dependency
    - Dep job folder id
      - INTERNETWORK\_DEPS\_V view 32
    - Dep job folder name
      - INTERNETWORK\_DEPS\_V view 32
    - Dep job stream folder id
      - INTERNETWORK\_DEPS\_V view 31
    - Dep job stream folder name
      - INTERNETWORK\_DEPS\_V view 31
    - dep\_job\_stream\_identifier column
      - INTERNETWORK\_DEPS\_V view 31
    - dep\_job\_stream\_name column
      - INTERNETWORK\_DEPS\_V view 31
    - dependent\_job\_stream\_valid\_to\_date
      - INTERNETWORK\_DEPS\_V view 31
    - dependent\_job\_definition\_identifier
      - INTERNETWORK\_DEPS\_V view 32
    - dependent\_job\_definition\_name
      - INTERNETWORK\_DEPS\_V view 32
    - dependent\_job\_identifier
      - INTERNETWORK\_DEPS\_V view 32
    - dependent\_job\_name
      - INTERNETWORK\_DEPS\_V view 32
    - dependent\_job\_stream\_valid\_from\_date
      - INTERNETWORK\_DEPS\_V view 31
    - dependent\_job\_stream\_workstation\_identifier
      - INTERNETWORK\_DEPS\_V view 31
    - dependent\_job\_stream\_workstation\_name
      - INTERNETWORK\_DEPS\_V view 31
    - dependent\_job\_workstation\_identifier
      - INTERNETWORK\_DEPS\_V view 31
    - dependent\_job\_workstation\_name
      - INTERNETWORK\_DEPS\_V view 31
  - in a job stream, view 30
  - in a job, view 30
  - internetwork\_dependency\_name
    - INTERNETWORK\_DEPS\_V view 30
  - network\_agent\_identifier
    - INTERNETWORK\_DEPS\_V view 30
  - network\_agent\_name
    - INTERNETWORK\_DEPS\_V view 30
  - view 30
  - internetwork\_dependency\_column
    - INTERNETWORK\_DEPS\_V view 30
  - INTERNETWORK\_DEPS\_V view 30
  - interval\_end\_offset column
    - REMOTE\_JOB\_REQUESTS\_V view 110
  - interval\_start\_offset column
    - REMOTE\_JOB\_REQUESTS\_V view 110
  - is\_default column
    - VARIABLE\_TABLE\_REFS\_V view 122
  - is\_draft column
    - EVENT\_RULES\_V view 25

is\_timeout\_expired column  
EVENT\_RULE\_INSTANCES\_V view 24

## J

### job

contained in a job stream, output example 34  
contained in a job stream, view 33  
depending on a file, output example 29  
depending on a file, view 27  
PLAN\_JOB\_PREDECESSORS\_V view 63  
PLAN\_JOBS\_SUCCESSORS\_V view 77  
PLAN\_JOBS\_V view 87  
that depends on a job stream, output example 55  
that depends on a job stream, view 49  
that depends on a job, output example 40  
that depends on a job, view 35  
that depends on a prompt, view 106  
that depends on internetwork dependency, view 30  
that depends on resource, output example 116  
that depends on resource, view 112

### job dependency

dependent critical job name  
JOB\_DEPS\_V view 37  
dependent job name  
JOB\_DEPS\_V view 37  
dependent job stream folder id  
JOB\_DEPS\_V view 36  
dependent job stream folder name  
JOB\_DEPS\_V view 36  
dependent job stream identifier  
JOB\_DEPS\_V view 36  
dependent job stream name  
JOB\_DEPS\_V view 36  
dependent job stream valid from date  
JOB\_DEPS\_V view 37  
dependent job stream valid to date  
JOB\_DEPS\_V view 37  
dependent job stream workstation identifier  
JOB\_DEPS\_V view 36  
dependent job stream workstation name  
JOB\_DEPS\_V view 36  
job identifier  
JOB\_DEPS\_V view 35  
job name  
JOB\_DEPS\_V view 35  
Job stream folder id  
JOB\_DEPS\_V view 36  
Job stream folder name  
JOB\_DEPS\_V view 36  
job stream name  
JOB\_DEPS\_V view 36, 36  
job stream workstation identifier  
JOB\_DEPS\_V view 36  
job stream workstation name  
JOB\_DEPS\_V view 36  
type of dependency  
JOB\_DEPS\_V view 35

### job history

actual\_workstation\_name in run  
JOB\_HISTORY\_V view 43  
job definition identifier  
JOB\_HISTORY\_V view 42  
job end time  
JOB\_HISTORY\_V view 43  
job folder id  
JOB\_HISTORY\_V view 42  
job folder name

JOB\_HISTORY\_V view 42  
job identifier in run  
JOB\_HISTORY\_V view 43  
job name  
JOB\_HISTORY\_V view 42  
job name in run  
JOB\_HISTORY\_V view 43  
job number  
JOB\_HISTORY\_V view 44  
job run date time  
JOB\_HISTORY\_V view 42  
job start time  
JOB\_HISTORY\_V view 42  
job status  
JOB\_HISTORY\_V view 44  
job stream folder name  
JOB\_HISTORY\_V view 41  
job stream name in run  
JOB\_HISTORY\_V view 43  
job stream workstation name in run  
JOB\_HISTORY\_V view 41  
job\_critical  
JOB\_HISTORY\_V view 45  
job\_critical\_latest\_time  
JOB\_HISTORY\_V view 45  
job\_promoted  
JOB\_HISTORY\_V view 45  
job\_stream\_instance\_id  
JOB\_HISTORY\_V view 45  
late end time  
JOB\_HISTORY\_V view 42  
late start time  
JOB\_HISTORY\_V view 42  
log\_time  
JOB\_HISTORY\_V view 45  
long duration  
JOB\_HISTORY\_V view 43  
planned duration  
JOB\_HISTORY\_V view 42  
rerun number  
JOB\_HISTORY\_V view 44  
rerun type  
JOB\_HISTORY\_V view 44  
return code  
JOB\_HISTORY\_V view 44  
total cpu time  
JOB\_HISTORY\_V view 43  
total elapsed time  
JOB\_HISTORY\_V view 43  
user login  
JOB\_HISTORY\_V view 45  
view 41  
workstation name  
JOB\_HISTORY\_V view 41  
workstation name in run  
JOB\_HISTORY\_V view 43  
job history workstation\_license\_type  
JOB\_HISTORY\_V view 43  
job in a job stream  
job definition identifier  
JOB\_DEFINITION\_REFS\_V view 34  
job definition name  
JOB\_DEFINITION\_REFS\_V view 34  
job folder id  
JOB\_DEFINITION\_REFS\_V view 34  
job folder name  
JOB\_DEFINITION\_REFS\_V view 34  
job name  
JOB\_DEFINITION\_REFS\_V view 34  
job stream folder id  
JOB\_DEFINITION\_REFS\_V view 33

job stream folder name  
JOB\_DEFINITION\_REFS\_V view 33  
job stream identifier  
JOB\_DEFINITION\_REFS\_V view 33  
job stream name  
JOB\_DEFINITION\_REFS\_V view 33  
job stream valid from  
JOB\_DEFINITION\_REFS\_V view 33  
job stream valid to  
JOB\_DEFINITION\_REFS\_V view 33  
job stream workstation identifier  
JOB\_DEFINITION\_REFS\_V view 33  
job stream workstation name  
JOB\_DEFINITION\_REFS\_V view 33  
job workstation identifier  
JOB\_DEFINITION\_REFS\_V view 34  
job workstation name  
JOB\_DEFINITION\_REFS\_V view 34  
job statistics  
abended runs  
JOB\_STATISTICS\_V view 47  
average cpu time  
JOB\_STATISTICS\_V view 48  
average elapsed time  
JOB\_STATISTICS\_V view 48  
job definition identifier  
JOB\_STATISTICS\_V view 46  
job description  
JOB\_STATISTICS\_V view 46  
job folder id  
JOB\_STATISTICS\_V view 46  
job folder name  
JOB\_STATISTICS\_V view 46  
job login user  
JOB\_STATISTICS\_V view 46  
job modify user  
JOB\_STATISTICS\_V view 47  
job name  
JOB\_STATISTICS\_V view 46  
job script name  
JOB\_STATISTICS\_V view 46  
last cpu time  
JOB\_STATISTICS\_V view 48  
last elapsed time  
JOB\_STATISTICS\_V view 48  
last run date  
JOB\_STATISTICS\_V view 48  
late end runs  
JOB\_STATISTICS\_V view 48  
late start runs  
JOB\_STATISTICS\_V view 48  
long duration runs  
JOB\_STATISTICS\_V view 47  
max cpu time  
JOB\_STATISTICS\_V view 48  
max elapsed time  
JOB\_STATISTICS\_V view 48  
max run date  
JOB\_STATISTICS\_V view 48  
min cpu time  
JOB\_STATISTICS\_V view 49  
min elapsed time  
JOB\_STATISTICS\_V view 49  
min run date  
JOB\_STATISTICS\_V view 49  
recovery job definition id  
JOB\_STATISTICS\_V view 46  
recovery job name  
JOB\_STATISTICS\_V view 47  
recovery option  
JOB\_STATISTICS\_V view 47

- recovery prompt
  - JOB\_STATISTICS\_V view 47
- recovery repeat affinity
  - JOB\_STATISTICS\_V view 47
- recovery repeat interval
  - JOB\_STATISTICS\_V view 47
- recovery repeat occurrences
  - JOB\_STATISTICS\_V view 47
- successful runs
  - JOB\_STATISTICS\_V view 47
- suppressed runs
  - JOB\_STATISTICS\_V view 47
- total cpu time
  - JOB\_STATISTICS\_V view 48
- total elapsed time
  - JOB\_STATISTICS\_V view 48
- total reruns
  - JOB\_STATISTICS\_V view 48
- view 46
- workstation name
  - JOB\_STATISTICS\_V view 46
- job stream
  - calendar identifier
    - JOB\_STREAM\_REFS\_V view 57
  - calendar name
    - JOB\_STREAM\_REFS\_V view 57
  - depending on a file, output example 29
  - depending on a file, view 27
  - in which a job appears, output example 34
  - in which a job appears, view 33
  - job stream folder id
    - JOB\_STREAM\_REFS\_V view 56
  - job stream folder name
    - JOB\_STREAM\_REFS\_V view 56
  - job stream identifier
    - JOB\_STREAM\_REFS\_V view 56
  - job stream name
    - JOB\_STREAM\_REFS\_V view 56
  - job stream valid from
    - JOB\_STREAM\_REFS\_V view 57
  - job stream valid to
    - JOB\_STREAM\_REFS\_V view 57
  - output example 57
  - output example 18
  - PLAN\_JOB\_PREDECESSORS\_V view 81
  - PLAN\_JOB\_STREAM\_PREDECESSORS\_V 68
  - PLAN\_JOB\_STREAM\_SUCESSORS\_V view 73
  - run cycle view 116
  - run cycle, output example 120
  - that depends on a job stream, output example 55
  - that depends on a job stream, view 49, 106
  - that depends on a job, output example 40
  - that depends on a job, view 35
  - that depends on a resource, output example 116
  - that depends on a resource, view 112
  - that depends on internetwork dependency, view 30
  - view 56
  - workstation identifier
    - JOB\_STREAM\_REFS\_V view 56
  - workstation name
    - JOB\_STREAM\_REFS\_V view 56
- job stream dependency
  - dependent critical job name
    - JOB\_DEPS\_V view 51
  - dependent job definition name
    - JOB\_STREAM\_DEPS\_V view 51, 52
  - dependent job folder id
    - JOB\_STREAM\_DEPS\_V view 51
  - dependent job stream folder id
    - JOB\_STREAM\_DEPS\_V view 51
  - dependent job name
    - JOB\_STREAM\_DEPS\_V view 51
  - dependent job stream name
    - JOB\_STREAM\_DEPS\_V view 50, 50
  - dependent job stream valid from
    - JOB\_STREAM\_DEPS\_V view 50
  - dependent job stream workstation to
    - JOB\_STREAM\_DEPS\_V view 51
  - dependent job stream workstation identifier
    - JOB\_STREAM\_DEPS\_V view 50, 51
  - dependent job stream workstation name
    - JOB\_STREAM\_DEPS\_V view 50, 51
  - job stream folder id
    - JOB\_STREAM\_DEPS\_V view 50
  - job stream folder name
    - JOB\_STREAM\_DEPS\_V view 50
  - job stream identifier
    - JOB\_STREAM\_DEPS\_V view 50
  - job stream name
    - JOB\_STREAM\_DEPS\_V view 50
  - job stream workstation identifier
    - JOB\_STREAM\_DEPS\_V view 50
  - job stream workstation name
    - JOB\_STREAM\_DEPS\_V view 50
  - type of dependency
    - JOB\_STREAM\_DEPS\_V view 49
- job stream runs
  - calendar identifier
    - RUN\_CYCLE\_REFS\_V view 119
  - calendar name
    - RUN\_CYCLE\_REFS\_V view 119
  - free days rule
    - RUN\_CYCLE\_REFS\_V view 118
  - job stream folder id
    - RUN\_CYCLE\_REFS\_V view 22, 117
  - job stream folder name
    - RUN\_CYCLE\_REFS\_V view 23, 117
  - job stream identifier
    - RUN\_CYCLE\_REFS\_V view 23, 117
  - job stream name
    - RUN\_CYCLE\_REFS\_V view 23, 117
  - job stream valid from
    - RUN\_CYCLE\_REFS\_V view 117
  - job stream valid to
    - RUN\_CYCLE\_REFS\_V view 117
  - job stream workstation identifier
    - RUN\_CYCLE\_REFS\_V view 22, 117
  - job stream workstation name
    - RUN\_CYCLE\_REFS\_V view 22, 117
  - offset type
    - RUN\_CYCLE\_REFS\_V view 120
  - offset\_value
    - RUN\_CYCLE\_REFS\_V view 120
  - run cycle definition
    - RUN\_CYCLE\_REFS\_V view 118
  - run cycle identifier
    - RUN\_CYCLE\_REFS\_V view 117
  - run cycle inclusive
    - RUN\_CYCLE\_REFS\_V view 119
  - run cycle name
    - RUN\_CYCLE\_REFS\_V view 117
  - run cycle type
- RUN\_CYCLE\_REFS\_V view 118
- run cycle valid from
  - RUN\_CYCLE\_REFS\_V view 118
- run cycle valid to
  - RUN\_CYCLE\_REFS\_V view 118
- variable table
  - RUN\_CYCLE\_REFS\_V view 23
- variable table identifier
  - RUN\_CYCLE\_REFS\_V view 23
- job\_critical column
  - JOB\_HISTORY\_V view 45
- job\_critical\_latest\_time column
  - JOB\_HISTORY\_V view 45
- job\_definition\_identifier column
  - JOB\_DEFINITION\_REFS\_V view 34
- job\_history column
  - JOB\_HISTORY\_V view 42
- job\_statistics column
  - JOB\_STATISTICS\_V view 46
- job\_definition\_name column
  - JOB\_DEFINITION\_REFS\_V view 34
- job\_definition\_refs column
  - JOB\_DEFINITION\_REFS\_V view 33
- output example 34
- JOB\_DEPS\_V view
  - output example 40
- job\_description column
  - JOB\_STATISTICS\_V view 46
- job\_end\_time column
  - JOB\_HISTORY\_V view 43
- job\_folder\_id column
  - JOB\_DEFINITION\_REFS\_V view 34
  - JOB\_HISTORY\_V view 42
  - JOB\_STATISTICS\_V view 46
- job\_folder\_name column
  - JOB\_DEFINITION\_REFS\_V view 34
  - JOB\_HISTORY\_V view 42
  - JOB\_STATISTICS\_V view 46
- JOB\_HISTORY\_V view 41
- job\_identifier column
  - EVENT\_RULE\_ACTIONS\_V view 22
- JOB\_DEPS\_V view 35
- job\_identifier\_in\_run column
  - JOB\_HISTORY\_V view 43
- job\_login\_user column
  - JOB\_STATISTICS\_V view 46
- job\_modify\_user column
  - JOB\_STATISTICS\_V view 47
- job\_name column
  - .JOB\_HISTORY\_V view 42
  - EVENT\_RULE\_ACTIONS\_V view 22
  - JOB\_DEFINITION\_REFS\_V view 34
  - JOB\_DEPS\_V view 35
  - JOB\_STATISTICS\_V view 46
- job\_name\_in\_run column
  - JOB\_HISTORY\_V view 43
- job\_number column
  - JOB\_HISTORY\_V view 44
- job\_promoted column
  - JOB\_HISTORY\_V view 45
- job\_run\_date\_time column
  - JOB\_HISTORY\_V view 42
- job\_script\_name column
  - JOB\_STATISTICS\_V view 46
- job\_start\_time column
  - JOB\_HISTORY\_V view 42
- job\_statistics column
  - JOB\_STATISTICS\_V view 46
- job\_status column
  - JOB\_HISTORY\_V view 44
- JOB\_STREAM\_DEPS\_V view 49
  - output example 55
- job\_stream\_folder\_id column
  - JOB\_DEFINITION\_REFS\_V view 33
  - JOB\_STREAM\_DEPS\_V view 50

- JOB\_STREAM\_REFS\_V view 56
- RUN\_CYCLE\_REFS\_V view 22, 117
- job\_stream\_folder\_id column
- JOB\_DEPS\_V view 36
- job\_stream\_folder\_name column
- JOB\_DEFINITION\_REFS\_V view 33
- JOB\_HISTORY\_V view 41
- JOB\_STREAM\_DEPS\_V view 50
- JOB\_STREAM\_REFS\_V view 56
- RUN\_CYCLE\_REFS\_V view 23, 117
- job\_stream\_folder\_name column
- JOB\_DEPS\_V view 36
- job\_stream\_identifier column
- JOB\_DEFINITION\_REFS\_V view 33
- JOB\_DEPS\_V view 36
- JOB\_STREAM\_DEPS\_V view 50
- JOB\_STREAM\_REFS\_V view 56
- RUN\_CYCLE\_REFS\_V view 23, 117
- VARIABLE\_TABLE\_REFS\_V view 123
- job\_stream\_instance\_id column
- JOB\_HISTORY\_V view 45
- job\_stream\_name column
- JOB\_DEFINITION\_REFS\_V view 33
- JOB\_DEPS\_V view 36
- JOB\_STREAM\_DEPS\_V view 50
- JOB\_STREAM\_REFS\_V view 56
- RUN\_CYCLE\_REFS\_V view 23, 117
- VARIABLE\_TABLE\_REFS\_V view 123
- job\_stream\_name\_in\_run column
- JOB\_HISTORY\_V view 43
- JOB\_STREAM\_REFS\_V view 56
- output example 57
- job\_stream\_valid\_from column
- JOB\_DEFINITION\_REFS\_V view 33
- JOB\_STREAM\_REFS\_V view 57
- RUN\_CYCLE\_REFS\_V view 117
- VARIABLE\_TABLE\_REFS\_V view 123
- job\_stream\_valid\_to column
- JOB\_DEFINITION\_REFS\_V view 33
- JOB\_STREAM\_REFS\_V view 57
- RUN\_CYCLE\_REFS\_V view 117
- VARIABLE\_TABLE\_REFS\_V view 123
- job\_stream\_wks\_identifier column
- JOB\_DEFINITION\_REFS\_V view 33
- JOB\_DEPS\_V view 36
- JOB\_STREAM\_DEPS\_V view 50
- RUN\_CYCLE\_REFS\_V view 22, 117
- job\_stream\_wks\_name column
- JOB\_DEFINITION\_REFS\_V view 33
- JOB\_DEPS\_V view 36
- JOB\_STREAM\_DEPS\_V view 50
- RUN\_CYCLE\_REFS\_V view 22, 117
- job\_stream\_wks\_name\_in\_run column
- JOB\_HISTORY\_V view 41
- job\_wks\_identifier column
- EVENT\_RULE\_ACTIONS\_V view 22
- job\_wks\_name column
- EVENT\_RULE\_ACTIONS\_V view 22
- JOB\_DEFINITION\_REFS\_V view 34, 34
- join id
- JOB\_DEPS\_V view 39
- JOB\_STREAM\_DEPS\_V view 54
- join name
- JOB\_DEPS\_V view 40
- JOB\_STREAM\_DEPS\_V view 54
- join quantity
- JOB\_DEPS\_V view 40
- JOB\_STREAM\_DEPS\_V view 54
- join\_id
- JOB\_DEPS\_V view 39
- JOB\_STREAM\_DEPS\_V view 54

- join\_name
- JOB\_DEPS\_V view 40
- JOB\_STREAM\_DEPS\_V view 54
- join\_quantity
- JOB\_DEPS\_V view 40
- JOB\_STREAM\_DEPS\_V view 54
- justification\_category column
- AUDIT\_STORE\_RECORDS\_V view 17
- justification\_description column
- AUDIT\_STORE\_RECORDS\_V view 17
- justification\_ticket\_num column
- AUDIT\_STORE\_RECORDS\_V view 17

## K

- key
- for reading tables 7

## L

- last\_cpu\_time column
- JOB\_STATISTICS\_V view 48
- last\_elapsed\_time column
- JOB\_STATISTICS\_V view 48
- last\_run\_date column
- JOB\_STATISTICS\_V view 48
- late\_end\_runs column
- JOB\_STATISTICS\_V view 48
- late\_end\_time column
- JOB\_HISTORY\_V view 42
- late\_start\_runs column
- JOB\_STATISTICS\_V view 48
- late\_start\_time column
- JOB\_HISTORY\_V view 42
- line\_of\_business column
- LOG\_MESSAGES\_V view 59
- local\_job\_name column
- REMOTE\_JOB\_REQUESTS\_V view 110
- local\_job\_start\_time column
- REMOTE\_JOB\_REQUESTS\_V view 110
- local\_job\_stream\_name column
- REMOTE\_JOB\_REQUESTS\_V view 110
- local\_workstation\_name column
- REMOTE\_JOB\_REQUESTS\_V view 110
- log\_id column
- AUDIT\_STORE\_RECORDS\_V view 18
- LOG\_MESSAGES\_V view 58
- log\_time column
- ACTION\_PARAMETERS\_V view 15
- ACTION\_RUNS\_V view 15
- AUDIT\_STORE\_RECORDS\_V view 17
- EVENT\_RULE\_INSTANCES\_V view 23
- JOB\_HISTORY\_V view 45
- LOG\_MESSAGES\_V view 58
- log\_type column
- AUDIT\_STORE\_RECORDS\_V view 17
- long\_duration column
- JOB\_HISTORY\_V view 43
- long\_duration\_runs column
- JOB\_STATISTICS\_V view 47

## M

- matching\_criteria column
- REMOTE\_JOB\_REQUESTS\_V view 110
- max\_cpu\_time column
- JOB\_STATISTICS\_V view 48
- max\_elapsed\_time column
- JOB\_STATISTICS\_V view 48
- max\_run\_date column
- JOB\_STATISTICS\_V view 48
- message column
- ACTION\_RUNS\_V view 16
- LOG\_MESSAGES\_V view 59
- min\_cpu\_time column

- JOB\_STATISTICS\_V view 49
- min\_elapsed\_time column
- JOB\_STATISTICS\_V view 49
- min\_run\_date column
- JOB\_STATISTICS\_V view 49

## N

- network\_agent\_identifier column
- INTERNETWORK\_DEPS\_V view 30
- network\_agent\_name column
- INTERNETWORK\_DEPS\_V view 30
- notification\_URI column
- REMOTE\_JOB\_REQUESTS\_V view 111

## O

- object\_definition column
- AUDIT\_STORE\_RECORDS\_V view 18
- object\_definition\_differences column
- AUDIT\_STORE\_RECORDS\_V view 17
- object\_identifier column
- AUDIT\_STORE\_RECORDS\_V view 18
- object\_key column
- AUDIT\_STORE\_RECORDS\_V view 17
- object\_name column
- AUDIT\_STORE\_RECORDS\_V view 17
- object\_type column
- AUDIT\_STORE\_RECORDS\_V view 17
- offset\_type column
- RUN\_CYCLE\_REFS\_V view 120
- offset\_value column
- RUN\_CYCLE\_REFS\_V view 120
- Oracle
- 11g schema on UNIX
- extracting view information from 13
- Oracle
- 11g schema on Windows
- extracting view information from 12
- overview
- IBM Workload Scheduler
- views
- 7
- owner\_group column
- LOG\_MESSAGES\_V view 59

## P

- parameter
- ACTION\_PARAMETERS\_V view 15
- view 121
- parameter\_list column
- EVENT\_RULE\_ACTIONS\_V view 22
- parameter\_name column
- ACTION\_PARAMETERS\_V view 15
- parameter\_value column
- ACTION\_PARAMETERS\_V view 15
- parameter, see variable
- output example 121
- variable identifier
- VARIABLES\_V view 121
- variable name
- VARIABLES\_V view 121
- variable table identifier
- VARIABLES\_V view 121
- variable table name
- VARIABLES\_V view 121
- variable value
- VARIABLES\_V view 121
- PLAN\_DOMAINS\_V view 59
- PLAN\_FILES\_REF\_V view 60
- PLAN\_FILES\_V view 63
- PLAN\_JOB\_PREDECESSORS\_V view 63, 81
- PLAN\_JOB\_STREAM\_PREDECESSORS\_V view 68

PLAN\_JOB\_STREAM\_SUCCESORS\_V view 73  
 PLAN\_JOB\_SUCCESORS\_V view 77  
 PLAN\_JOBS\_V view 87  
 PLAN\_PROMPT\_REFS\_V view 94  
 PLAN\_PROMPTS\_V view 97  
 PLAN\_RESOURCE\_REFS\_V view 98  
 PLAN\_RESOURCES\_V view 101  
 PLAN\_WORKSTATIONS\_V view 102  
 planned\_duration column  
   JOB\_HISTORY\_V view 42  
 prompt  
   identifier  
     PROMPTS\_V view 106  
   name  
     PROMPTS\_V view 106  
   on which a job depends, view 106  
   on which a job stream depends, view 106  
   output example 106  
   value  
     PROMPTS\_V view 106  
   view 106  
 prompt dependency  
   dependent job definition identifier  
     PROMPT\_REFS\_V view 108  
   dependent job definition name  
     PROMPT\_REFS\_V view 108  
   dependent job folder id  
     PROMPT\_REFS\_V view 108  
   dependent job identifier  
     PROMPT\_REFS\_V view 108  
   dependent job name  
     PROMPT\_REFS\_V view 108  
   dependent job stream identifier  
     PROMPT\_REFS\_V view 107  
   dependent job stream name  
     PROMPT\_REFS\_V view 107  
   dependent job stream valid from  
     PROMPT\_REFS\_V view 107  
   dependent job stream valid to  
     PROMPT\_REFS\_V view 108  
   dependent job stream workstation identifier  
     PROMPT\_REFS\_V view 107  
   dependent job stream workstation name  
     PROMPT\_REFS\_V view 107  
   dependent job workstation identifier  
     PROMPT\_REFS\_V view 108  
   dependent job workstation name  
     PROMPT\_REFS\_V view 108  
   job folder id  
     PROMPT\_REFS\_V view 108  
   job stream folder id  
     PROMPT\_REFS\_V view 107  
   job stream folder name  
     PROMPT\_REFS\_V view 107  
   prompt identifier  
     PROMPT\_REFS\_V view 107  
   prompt name  
     PROMPT\_REFS\_V view 107  
   prompt text  
     PROMPT\_REFS\_V view 107  
 prompt\_identifier column  
   PROMPT\_REFS\_V view 107  
 prompt\_name column  
   PROMPT\_REFS\_V view 107  
   PROMPTS\_V view 106, 106  
 PROMPT\_REFS\_V view 106  
 prompt\_text column  
   PROMPT\_REFS\_V view 107  
 prompt\_value column  
   PROMPTS\_V view 106  
 prompts

PLAN\_PROMPT\_REFS\_V view 94  
 PLAN\_PROMPTS\_V view 97  
 PROMPTS\_V view 106  
   output example 106  
 PROPERTIES\_V view 109  
 property  
   PROPERTIES\_V 109  
   property name  
     PROPERTIES\_V view 109  
   property value  
     PROPERTIES\_V view 109  
   property\_name column  
     PROPERTIES\_V view 109  
   property\_value column  
     PROPERTIES\_V view 109

## R

reading  
   tables 7  
 recovery\_job\_definition\_id column  
   JOB\_STATISTICS\_V view 46  
 recovery\_job\_name column  
   JOB\_STATISTICS\_V view 47  
 recovery\_option column  
   JOB\_STATISTICS\_V view 47  
 recovery\_prompt column  
   JOB\_STATISTICS\_V view 47  
 recovery\_repeat\_affinity column  
   JOB\_STATISTICS\_V view 47  
 recovery\_repeat\_interval column  
   JOB\_STATISTICS\_V view 47  
 recovery\_repeat\_occurrences column  
   JOB\_STATISTICS\_V view 47  
 related\_object\_name column  
   AUDIT\_STORE\_RECORDS\_V view 18  
 related\_workstation\_name column  
   AUDIT\_STORE\_RECORDS\_V view 17  
 remote\_job\_identifier column  
   REMOTE\_JOB\_REQUESTS\_V view 109  
 REMOTE\_JOB\_REQUESTS\_V view 109  
 remote\_job\_start\_time column  
   REMOTE\_JOB\_REQUESTS\_V view 109  
 request\_status column  
   REMOTE\_JOB\_REQUESTS\_V view 110  
 rerun\_number column  
   JOB\_HISTORY\_V view 44  
 rerun\_type column  
   JOB\_HISTORY\_V view 44  
 resource  
   on which a job depends, output  
     example 116  
   on which a job depends, view 112  
   on which a job stream depends, output  
     example 116  
   on which a job stream depends, view 112  
   output example 112  
   PLAN\_RESOURCE\_REFS\_V view 98  
   PLAN\_RESOURCES\_V view 101  
   resource description  
     RESOURCES\_V view 112  
   resource identifier  
     RESOURCES\_V view 112  
   resource name  
     RESOURCES\_V view 111  
   resource units  
     RESOURCES\_V view 112  
   RESOURCES\_V 111  
   workstation identifier  
     RESOURCES\_V view 111  
   workstation name  
     RESOURCES\_V view 111

resource dependency  
   dependent job definition identifier  
     RESOURCE\_REFS\_V view 114  
   dependent job definition name  
     RESOURCE\_REFS\_V view 114  
   dependent job folder name  
     RESOURCE\_REFS\_V view 114, 114  
   dependent job identifier  
     RESOURCE\_REFS\_V view 114  
   dependent job name  
     RESOURCE\_REFS\_V view 114  
   dependent job stream folder name  
     RESOURCE\_REFS\_V view 113, 113  
   dependent job stream identifier  
     RESOURCE\_REFS\_V view 113  
   dependent job stream name  
     RESOURCE\_REFS\_V view 113  
   dependent job stream valid from  
     RESOURCE\_REFS\_V view 113  
   dependent job stream valid to  
     RESOURCE\_REFS\_V view 114  
   dependent job stream workstation identifier  
     RESOURCE\_REFS\_V view 113  
   dependent job stream workstation name  
     RESOURCE\_REFS\_V view 113  
   dependent job workstation identifier  
     RESOURCE\_REFS\_V view 114  
   dependent job workstation name  
     RESOURCE\_REFS\_V view 114  
   resource identifier  
     RESOURCE\_REFS\_V view 113  
   resource name  
     RESOURCE\_REFS\_V view 113  
   units allocated  
     RESOURCE\_REFS\_V view 113  
   units available  
     RESOURCE\_REFS\_V view 113  
   workstation identifier  
     RESOURCE\_REFS\_V view 112  
   workstation name  
     RESOURCE\_REFS\_V view 112  
 resource\_description column  
   RESOURCES\_V view 112  
 resource\_identifier column  
   RESOURCES\_V view 112  
 resource\_name column  
   RESOURCE\_REFS\_V view 113, 113  
   RESOURCES\_V view 111  
 RESOURCE\_REFS\_V view 112  
   output example 116  
 resource\_units column  
   RESOURCES\_V view 112  
 RESOURCES\_V view 111  
   output example 112  
 response\_type column  
   EVENT\_RULE\_ACTIONS\_V view 22  
 return\_code column  
   JOB\_HISTORY\_V view 44  
 rule  
   AUDIT\_STORE\_RECORDS\_V view 16  
   LOG\_MESSAGES\_V view 58  
 run cycle  
   output example 120  
   view 116  
 run\_cycle\_definition column  
   RUN\_CYCLE\_REFS\_V view 118  
 run\_cycle\_identifier column  
   RUN\_CYCLE\_REFS\_V view 117  
   VARIABLE\_TABLE\_REFS\_V view 123  
 run\_cycle\_inclusive column  
   RUN\_CYCLE\_REFS\_V view 119

run\_cycle\_name column  
 RUN\_CYCLE\_REFS\_V view 117  
 VARIABLE\_TABLE\_REFS\_V view 123  
 RUN\_CYCLE\_REFS\_V view 116  
 output example 120  
 run\_cycle\_type column  
 RUN\_CYCLE\_REFS\_V view 118  
 run\_cycle\_valid\_from column  
 RUN\_CYCLE\_REFS\_V view 118  
 run\_cycle\_valid\_to column  
 RUN\_CYCLE\_REFS\_V view 118

## S

schema  
 Oracle  
 11g  
 extracting view information from 12  
 schema  
 Oracle  
 11g on UNIX  
 extracting view information from 13  
 source column  
 LOG\_MESSAGES\_V view 59  
 start\_offset column  
 EVENT\_RULES\_V view 26  
 statistics  
 abended runs  
 JOB\_STATISTICS\_V view 47  
 average cpu time  
 JOB\_STATISTICS\_V view 48  
 job definition identifier  
 JOB\_STATISTICS\_V view 46  
 job description  
 JOB\_STATISTICS\_V view 46  
 job folder id  
 JOB\_STATISTICS\_V view 46  
 job folder name  
 JOB\_STATISTICS\_V view 46  
 job login user  
 JOB\_STATISTICS\_V view 46  
 job modify user  
 JOB\_STATISTICS\_V view 47  
 job name  
 JOB\_STATISTICS\_V view 46  
 job script name  
 JOB\_STATISTICS\_V view 46  
 last cpu time  
 JOB\_STATISTICS\_V view 48  
 last elapsed time  
 JOB\_STATISTICS\_V view 48  
 last run date  
 JOB\_STATISTICS\_V view 48  
 late end runs  
 JOB\_STATISTICS\_V view 48  
 late start runs  
 JOB\_STATISTICS\_V view 48  
 long duration runs  
 JOB\_STATISTICS\_V view 47  
 max cpu time  
 JOB\_STATISTICS\_V view 48  
 max elapsed time  
 JOB\_STATISTICS\_V view 48  
 max run date  
 JOB\_STATISTICS\_V view 48  
 min cpu time  
 JOB\_STATISTICS\_V view 49  
 min elapsed time  
 JOB\_STATISTICS\_V view 49  
 min run date  
 JOB\_STATISTICS\_V view 49  
 recovery job definition id

JOB\_STATISTICS\_V view 46  
 recovery job name  
 JOB\_STATISTICS\_V view 47  
 recovery option  
 JOB\_STATISTICS\_V view 47  
 recovery prompt  
 JOB\_STATISTICS\_V view 47  
 successful runs  
 JOB\_STATISTICS\_V view 47  
 suppressed runs  
 JOB\_STATISTICS\_V view 47  
 total cpu time  
 JOB\_STATISTICS\_V view 48  
 total elapsed time  
 JOB\_STATISTICS\_V view 48, 48  
 total\_reruns  
 JOB\_STATISTICS\_V view 48  
 workstation name  
 JOB\_STATISTICS\_V view 46  
 statistics of job  
 view 46  
 statistics recovery repeat affinity  
 JOB\_STATISTICS\_V view 47  
 statistics recovery repeat interval  
 JOB\_STATISTICS\_V view 47  
 statistics recovery repeat occurrences  
 JOB\_STATISTICS\_V view 47  
 status  
 event rule  
 EVENT\_RULES\_V view 25  
 successful\_runs column  
 JOB\_STATISTICS\_V view 47  
 suppressed\_runs column  
 JOB\_STATISTICS\_V view 47

## T

table  
 columns 7  
 technical training v  
 time\_interval column  
 EVENT\_RULES\_V view 26  
 time\_zone column  
 EVENT\_RULES\_V view 26  
 total\_cpu\_time column  
 JOB\_HISTORY\_V view 43  
 JOB\_STATISTICS\_V view 48  
 total\_elapsed\_time  
 JOB\_HISTORY\_V view 43  
 total\_elapsed\_time column  
 JOB\_STATISTICS\_V view 48  
 total\_reruns column  
 JOB\_STATISTICS\_V view 48  
 training  
 technical v  
 type\_of\_dependency column  
 JOB\_DEPS\_V view 35  
 JOB\_STREAM\_DEPS\_V view 49

## U

units\_allocated column  
 RESOURCE\_REFS\_V view 113  
 units\_available column  
 RESOURCE\_REFS\_V view 113  
 UNIX  
 extracting view information 10  
 extracting view information from a DB2  
 database 11, 12  
 extracting view information from an  
 Oracle  
 11g schema  
 13  
 user

granting access to display views 11  
 user\_login column  
 JOB\_HISTORY\_V view 45  
 user\_name column  
 AUDIT\_STORE\_RECORDS\_V view 17

## V

valid\_from column  
 EVENT\_RULES\_V view 26  
 valid\_to column  
 EVENT\_RULES\_V view 26  
 variable  
 output example 121  
 variable identifier  
 VARIABLES\_V view 121  
 variable name  
 VARIABLES\_V view 121  
 variable table identifier  
 VARIABLES\_V view 121  
 variable table name  
 VARIABLES\_V view 121  
 variable value  
 VARIABLES\_V view 121  
 variable table  
 is\_default  
 VARIABLE\_TABLE\_REFS\_V view 122  
 job\_stream\_identifier  
 VARIABLE\_TABLE\_REFS\_V view 123  
 job\_stream\_name  
 VARIABLE\_TABLE\_REFS\_V view 123  
 job\_stream\_valid\_from  
 VARIABLE\_TABLE\_REFS\_V view 123  
 job\_stream\_valid\_to  
 VARIABLE\_TABLE\_REFS\_V view 123  
 output example 123  
 run\_cycle\_identifier  
 VARIABLE\_TABLE\_REFS\_V view 123  
 run\_cycle\_name  
 VARIABLE\_TABLE\_REFS\_V view 123  
 variable table identifier  
 VARIABLE\_TABLE\_REFS\_V view 122  
 variable table name  
 VARIABLE\_TABLE\_REFS\_V view 122  
 view 122  
 workstation\_identifier  
 VARIABLE\_TABLE\_REFS\_V view 122  
 workstation\_name  
 VARIABLE\_TABLE\_REFS\_V view 122  
 variable\_identifier column  
 VARIABLES\_V view 121  
 variable\_name column  
 VARIABLES\_V view 121  
 variable\_table column  
 RUN\_CYCLE\_REFS\_V view 23  
 VARIABLE\_TABLE\_REFS\_V view 122  
 VARIABLES\_V view 121  
 variable\_table\_identifier column  
 RUN\_CYCLE\_REFS\_V view 23  
 VARIABLE\_TABLE\_REFS\_V view 122  
 VARIABLES\_V view 121  
 output example 123  
 variable\_value column  
 VARIABLES\_V view 121  
 VARIABLES\_V view 121  
 output example 121  
 view  
 ACTION\_PARAMETERS\_V 15  
 ACTION\_RUNS\_V 15  
 AUDIT\_STORE\_RECORDS\_V 16

AUDIT\_STORE\_RECORDS\_V output example 18  
 CALENDARS\_V 20  
 CALENDARS\_V output example 20 displaying 10  
 displaying from a DB2 database 11  
 displaying from an Oracle schema 12  
 EVENT\_CONDITIONS\_V 21  
 EVENT\_RULE\_ACTIONS\_V 21  
 EVENT\_RULE\_INSTANCES\_V 23  
 EVENT\_RULES\_V 24  
 FILE\_REFS\_V 27  
 FILE\_REFS\_V output example 29  
 granting access to users 11  
 INTERNETWORK\_DEPS\_V 30  
 JOB\_DEFINITION\_REFS\_V 33  
 JOB\_DEFINITION\_REFS\_V output example 34  
 JOB\_DEPS\_V 35  
 JOB\_DEPS\_V output example 40  
 JOB\_HISTORY\_V 41  
 JOB\_STATISTICS\_V 46  
 JOB\_STREAM\_DEPS\_V output example 55  
 JOB\_STREAM\_DEPS\_V view 49  
 JOB\_STREAM\_REFS\_V 56  
 JOB\_STREAM\_REFS\_V output example 57  
 LOG\_MESSAGES\_V 58  
 PLAN\_DOMAINS\_V 59  
 PLAN\_FILE\_REFS\_V 60  
 PLAN\_FILES\_V 63  
 PLAN\_JOB\_PREDECESSORS\_V 63, 81  
 PLAN\_JOB\_STREAM\_PREDECESSORS\_V 68  
 PLAN\_JOB\_STREAM\_SUCCESSORS\_V 73  
 PLAN\_JOB\_SUCCESSORS\_V 77  
 PLAN\_JOBS\_V 87  
 PLAN\_PROMPT\_REFS\_V 94  
 PLAN\_PROMPTS\_V 97  
 PLAN\_RESOURCE\_REFS\_V 98  
 PLAN\_RESOURCES\_V 101  
 PLAN\_WORKSTATIONS\_V 102  
 PROMPT\_REFS\_V 106  
 PROMPTS\_V 106  
 PROMPTS\_V output example 106  
 PROPERTIES\_V 109  
 REMOTE\_JOB\_REQUESTS\_V 109  
 RESOURCE\_REFS\_V 112  
 RESOURCE\_REFS\_V output example 116  
 RESOURCES\_V 111  
 RESOURCES\_V output example 112  
 RUN\_CYCLE\_REFS\_V 116  
 RUN\_CYCLE\_REFS\_V output example 120  
 VARIABLE\_TABLE\_REFS\_V 122  
 VARIABLE\_TABLE\_REFS\_V output example 123  
 VARIABLES\_V 121  
 VARIABLES\_V output example 121

workstation\_identifier column  
 FILE\_REFS\_V view 27  
 JOB\_STREAM\_REFS\_V view 56  
 RESOURCE\_REFS\_V view 112  
 RESOURCES\_V view 111  
 VARIABLE\_TABLE\_REFS\_V view 122  
 workstation\_license\_type column  
 JOB\_HISTORY\_V view 43  
 workstation\_name column  
 AUDIT\_STORE\_RECORDS\_V view 17  
 FILE\_REFS\_V view 27  
 JOB\_HISTORY\_V view 41  
 JOB\_STATISTICS\_V view 46  
 JOB\_STREAM\_REFS\_V view 56  
 LOG\_MESSAGES\_V view 59  
 RESOURCE\_REFS\_V view 112  
 RESOURCES\_V view 111  
 VARIABLE\_TABLE\_REFS\_V view 122  
 workstation\_name\_in\_run column  
 JOB\_HISTORY\_V view 43

## W

Windows  
 extracting view information 10  
 extracting view information from a DB2 database 11  
 extracting view information from an Oracle 11g schema 12  
 workstation  
 PLAN\_WORKSTATIONS\_V view 102